

ironwear[®]

Specifications

Respiratory Protection

Style #1502

- > Disposable 3-Ply Facemask with ear-loops
- > Ideal for procedures where moderate to light amounts of fluid, spray and/or aerosols are produced
- > Meets EN14683 Rating – Type IIR Standard.

> ASTM LEVEL 2:

Moderate Fluid Resistance: 120 mmHg

Filtration Efficiency: BFE ≥ 98%
PFE ≥ 98%
@ 0.1 micron

Breathability - Delta P: < 5.0 mm H₂O/cm²**Flame Spread:** Class 1

Description

- > **Material:** 100% polypropylene
- > **Numer of Layers:** 3

Packaging

- > **Case Weight:** 17.65 lb / 8 kg
- > **Case Dimensions (in):** 20.5" x 15" x 13.4"
- > **Case Dimensions (cm):** 52cm x 38cm x 34cm
- > **Packaging:** 50 / box, 2000 / carton

Test	Type IIR ASTM LEVEL 2: 120 mm Hg
BFE (Bacterial Filtration Efficiency) at 3.0 micron ASTM F2101	≥ 98%
PFE (Particulate Filtration Efficiency) at 0.1 micron ASTM F2299	≥ 98%
Delta P (Differential Pressure) MIL-M-36954C, mm H ₂ O/cm ²	< 5.0
Fluid Resistance to Synthetic Blood ASTM 1862, mm Hg	120
Flame Spread 16 CFR part 1610	Class 1

2020 Seabird Way
Riviera Beach, FL 33404

Toll Free (800) 329-2235

ironwear.com
sales@ironwear.com

