

DATE: 2/15/2018

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00122213

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETNA, LA. 70054-0009
504-364-2678

VENDOR: **BASIC SUPPLY, LLC**

BUYER: SFOLSE

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH	
INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES	<u>2-3 WEEKS</u>
INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK	_____
INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK	_____

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: _____
 NUMBER: _____
 NUMBER: _____
 NUMBER: _____

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***	
FIRM NAME: BASIC SUPPLY, LLC	
SIGNATURE: (Must be signed here) 	TITLE: MANAGER
PRINT OR TYPE NAME: JOHN ATKINSON	
ADDRESS: PO BOX 63066	
CITY, STATE: LAFAYETTE, LA	ZIP: 70596
TELEPHONE: () 337-769-0122	FAX: () 337-247-7699
EMAIL ADDRESS: charlotte@basicsupply.com	

TOTAL PRICE OF ALL BID ITEMS: \$ 1760.00

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00122213

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	4.00	EA	<p>LUBRIPLATE GREASE FOR THE JEFFERSON PARISH WB DRAINAGE DEPARTMENT</p> <p>0010 - LUBRIPLATE GREASE L0072-039 NO. 630-2(1/4 DRUM)</p> <p>DELIVER TO HERO PUMP STATION 4644 PETERS ROAD HARVEY LA 70058</p> <p>152-1/4DRUM</p>	440.00	1760.00



152

WHITE MULTIPURPOSE LUBRICANT

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

152 White Multipurpose Lubricant is a quality lithium base grease and a lead-free whiting agent. 152 White Multipurpose Lubricant is suited for temperatures up to 350°F (176°C) and slow to medium speeds. It provides excellent lubricity under extreme pressure conditions.

APPLICATION

152 White Multipurpose Lubricant is used for lubrication of automobiles, trucks, tractors, light and heavy industrial machinery, sleeve bearings, ball and roller bearings, brake assemblies, and virtually any other equipment requiring lubrication. It is especially used where darker colored staining greases cannot be tolerated.

BENEFITS

- Multipurpose
- Excellent lubricity
- Contains lead-free whiting agent

TYPICAL OBSERVATIONS

	152N1	152N2
Color	Tan	Tan
Texture	Smooth Paste	Smooth Paste
Thickener	Lithium Soap	
Density, lb/gal @77°F (25°C)	7.25	7.50
Specific Gravity, @ 77°F (25°C)	0.868	0.898
Dropping Point, ASTM D-2265	>380°F (>193°C)	>380°F (>193°C)
Flash Point, ASTM D-92	>400°F (>204°C)	>400°F (>204°C)
Penetration, ASTM D-217 worked @ 77°F (25°C)	310–340	265–295
Base Oil Viscosity @40°C, cSt	168	168
@ 100°C	13	13
Viscosity Index	58	58
Corrosion Preventive Properties ASTM D-1743 @ 125°F (51°C)	Pass	Pass
Evaporation Loss, ASTM D-972 @ 210°F (98°C)	1.11%	1.11%
Oil Separation, ASTM D-1742 @ 77°F (25°C)	Nil	Nil
Oxidation Stability, ASTM D-942 @ 210°F (98°C), 72 hrs. PSI Loss	3	3
Water Washout, ASTM D-1264 @ 100°F (37°C)	1.20	1.20
Shelf Life (unopened container)	Two years	Two years

