



ASmart LIGHT CO., LIMITED  
E-mail: sales@asmart-light.com  
www.asmart-light.com



P/N: AST-CLW07-027WXYA1-abck

Note:

AST= Company name

CLW07 = Product series, LED Corn Light

027W = Rating Power

X = LED manufacturer, A=HONGLI, B=SAMSUNG

Y = Cover type, X=C, for Clear cover;


X=F, for Frosted cover

a=represent the lamp base type, can be "E" for E39, "EX" for EX39, BLANK for E26,

b=represent the Top cover material, can be "P" or "M", "P" for plastic, "M" for metal.

c=represents CCT, can be two digital.

## DIMENSIONS



## NOTICE FOR USER

- Please turn off power before install or change assembly parts.
- The input voltage and lamps should be matched, after connecting the power line, Please make sure the wiring section is insulated.
- Make sure to remove or bypass the ballast in the fixtures before install the lamps.
- Suitable for damp locations. Do not use with dimmers.
- Suitable for use in enclosed luminaires, min. lamp compartment dimensions: 340\*200\*200MM.
- No-professionals, must not install and disassemble the lamps.

## ADVANTAGE

- UL cUL certificate.
- E26 E39 EX39 lamp base.
- 360 degree lighting.
- Can be with clear or frosted cover.
- IP65 Waterproof Rating.
- Big heat sink, NO fan.
- Internal driver, input voltage AC100-277V.
- Meet 4KV surge immunity level.
- Sealant pouring for whole driver and lamp plastic housing.
- Long lifespan and good heat dissipation.
- Direct replacement for Metal Halide, easy installation.
- Fits many different fixtures to replace traditional lamps.

## APPLICATION


- Widely used in supermarket, warehouse, garage, home, office, hotel, hospital, school, street, garden etc.

## SPECIFICATIONS

OPTICAL	Input Power	27W
	Lumen	3510-3780 LM (Clear) / 2970-3240 LM (Frosted)
	Lumen Efficacy	130-140M/W (Clear) / 110-120 LM/W (Frosted)
	Color Temperature	2700-6500K
	CRI	>80
	Viewing Angle	360 Degree
ELECTRICAL	Input Voltage	100-277VAC 50/60Hz
	PF	≥0.9
	THD	≤20%
	Equivalent	60W CFL, 100W MHL/HPS/HID
MATERIALS	LED Brand	HONGLI /SAMSUNG
	LED Type	SMD2835
	LED QTY	80 PCS
	Housing	PC + Aluminum
	Housing Color	Any colour
	Cover	Clear / Frosted
	Waterproof Rating	IP65
OTHERS	Operating Temperature	-25℃ TO 45℃
	Operating Humidity	20%-70% RH
	Storage Temperature	-40℃ TO 80℃
	Storage Humidity	10%-75% RH
	Warranty Time	5 Years

## PACKAGE



	Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
Inner box	253*120*120 MM	1 PC	0.58 KG	0.7 KG
Outer box	495*380*275 MM	12 PCS	7.0 KG	9.4 KG



## LIGHT DISTRIBUTION TESTING PARAMETERS

Remark: The testing data comes directly from the product test.

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 133.35 lm/W
MODEL		I <sub>max</sub> (cd)	498.5	S/MH (C0/180)	2.21	
NOMINAL POWER (W)	27	LOR (%)	100.0	S/MH (C90/270)	2.13	
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	3571.7	η UP, DN (C0-180)	23.6, 31.5	
NOMINAL FLUX (lm)	3571.66	CIE CLASS	DIFFUSE	η UP, DN (C180-360)	18.0, 26.9	
LAMPS INSIDE	1	η up (%)	41.6	CIBSE SHR NOM	2.00	
TEST VOLTAGE (V)	120	η down (%)	58.4	CIBSE SHR MAX	0.00	



## TROUBLE SHOOTINGS

Troubles	Check points
Flickering of the light	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies.
Out of working	Please check the connection.