


Stainless Steel

Wire Rope Clips



Item # 2

• Type 316



Light Duty

Heavy Duty



ITEM#		Size in Inches	Min. # of Clips Required	Amount of Wire Rope to Turn Back	Torque in Pounds ft*		Approx. Weight Each in Pounds	
Heavy Duty	Light Duty				HD	LD	HD	LD
WC116SS316	WC116SS316M	1/16	2	2 1/2"	3.0	2.0	-	.017
WC18SS316	WC18SS316M	1/8	2	3 1/4"	4.5	3.0	.043	.023
WC316SS316	WC316SS316M	3/16	2	3 3/4"	7.5	4.5	.063	.06
WC14SS316	WC14SS316M	1/4	2	4 3/4"	15	15	.12	.10
WC516SS316	WC516SS316M	5/16	2	5 1/4"	30	15	.18	.15
WC38SS316	WC38SS316M	3/8	2	6 1/2"	45	30	.36	.25
WC12SS316	WC12SS316M	1/2	3	11 1/2"	65	45	.52	.43
WC58SS316	WC58SS316M	5/8	3	12"	95	75	.89	.68
WC34SS316	WC34SS316M	3/4	4	18"	130	75	1.04	.84
WC78SS316	WC78SS316M	7/8	4	19"	225	130	1.68	1.3
WC1SS316	WC1SS316M	1	5	26"	225	130	1.86	1.61

* Torque values shown are based on clean unlubricated threads Wire Rope Clips are not designed for load carrying purposes. Therefore working load limits have not been established.