

## Features & Benefits

- No rewiring needed
- Works with fluorescent electronic instant start ballast
- Long life
- High CRI
- Instant on, no delay
- Convenient and quick installation
- Utilizes existing instant start or rapid start sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Glass tube for superior optical performance
- Wide View Angle
- 5 Year Warranty
- New Version with Integrated ArmorCoat  
For use in food areas and refrigerated food displayers



\* EMERGENCY BALLAST RESTRICTIONS



**RetroFlex™**  
LED T8 LAMP • Simplicity.  
Commercial Grade LED T8 Lamp

## Specification Data

Order Code	Length	Lamp Power	System Power	CCT	Initial Lumens	CRI	Beam Angle	Lamp Efficacy	System Efficacy	Life	DLC
L48T8/835/15G-EB-AC 48	16	19	3500	2200	82	325	135	115	50000		
L48T8/840/15G-EB-AC 48	16	19	4000	2200	82	325	135	115	50000		
L48T8/850/15G-EB-AC 48	16	19	5000	2200	82	325	135	115	50000		

\* Based on Normal Ballast Factor.

## Ordering Information

EXAMPLE: **L48T8/840/15G-EB-AC**

L	48	T8	8	40	15 G	- EB	- AC
Manufacturer's Code	Normal Length 48=48"	Lamp Shape T8=T8	CRI 8=>80	CCT 50 =5000K 40 =4000K 35 =3500K	Wattage 15G-15W	Electronic Ballast Compatible	ArmorCoat Shatterproof Coating

\* Not compatible with products equipped with battery backup and/or emergency ballasts.

\* Please refer to "Ballast Compatibility List" on Related Downloads.

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.