

- **High Tensile Double Synthetic Fiber Braids** - Contributes to low volumetric expansion and eliminates loss of strength from moisture absorption.
- **Abrasion Resistant Polyether-Urethane** - Polyurethane cover provides exceptional cut, abrasion and fungus resistance.
- **Slither® Cover** - Cover is ultra slippery; allows hose to maneuver around and through difficult sewer bends.
- **Pressure Testing** - All Piranha® factory-assembled hoses are 100% pressure tested.
- **Reel Installation** - Ideal for truck and trailer mounts.

Industry Standards

- **Blue Cover = 3,000 PSI**

Lengths

- **Stock Lengths** - 400, 500, and 600 foot rolls.
- **Custom Lengths** - Available and made to order.

Specifications

Size Code	16
Nominal I.D.	1 in 25.4 mm
Cover Color	Blue
Nominal O.D.	1.48 in 37.6 mm
Max. Operating Pressure	3000 psi 206.80 bar
Min. Burst Pressure	7500 psi 517.10 bar
Min. Bend Radius	8 in
Weight	0.41 lbs/ft
Application	Sewer Cleaning
Style	Braided
Total Length	600 ft
Inside Tube Material	Polyolefin
Cover Material	Polyether-urethane
Reinforcement Material	High tensile double synthetic fiber braid
Performance	Standard High Working Pressure

Fittings & Tooling

MALE
16NPT16 - Piranha® 1" male NPT end fitting to be used with HPBU-16, 3,000 PSI sewer hose

EMALE
16FS16 - Piranha® 1" female end fitting to be used with HPBU-16, 3,000 PSI sewer hose

WRENCH
S16 - Piranha® 1" die set to be used with HPBU-16, 3,000 PSI sewer hose

MENDER
16MEND - Piranha® 1" mender to be used with HPBU-16, 3,000 PSI sewer hose

MALE PUSHER
PT16 - Piranha® 1" male pusher to be used with HPBU-16, 3,000 PSI sewer hose

EMALE PUSHER