

DATE: 11/21/2024

INVITATION TO BID  
THIS IS NOT AN ORDER

Page: 5

BID NO.: 50-00146846

**JEFFERSON PARISH**

PURCHASING DEPARTMENT  
P.O. BOX 9  
GRETNA, LA. 70054-0009  
504-364-2678

VENDOR: 27118 BLANK BID COPY VENDOR

PURCHASING SPECIALIST:  
RTRAN

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

**DELIVERY: FOB JEFFERSON PARISH**

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

2 Weeks

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK

N/A

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK

N/A

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form by placing the addendum number as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: N/A  
NUMBER: N/A  
NUMBER: N/A  
NUMBER: N/A

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) N/A


**\*\*\* ALL BIDDERS MUST COMPLETE SECTION BELOW \*\*\***

FIRM NAME:

Rocky Mountain Recreation LLC

SIGNATURE:

(Must be signed here)



TITLE:

President

PRINT OR TYPE NAME:

Janeil Norman

ADDRESS:

PO Box 68

CITY, STATE:

Albion, ID

ZIP:

83311

TELEPHONE:

( 208 ) 670-5079

FAX:

( ) N/A

EMAIL ADDRESS:

rockymtnrecllc@gmail.com

TOTAL PRICE OF ALL BID ITEMS: \$ 8,999.50

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00146846

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	10.00	EA	<p>PURCHASE OF TRANSMITTER EQUIPMENT FOR THE JEFFERSON PARISH DEPARTMENT OF SCADA</p> <p>0001: ULTRASONIC LEVEL TRANSMITTER, 2"MPT "ECHOSONIC II", 8M"- 26.2', WHOUT FOB, PART# LU28-00.</p> <p>DELIVER TO: SCADA DEPARTMENT 4901 JEFFERSON HWY., SUITE C (6390) JEFFERSON, LA 70123</p>	\$ 899.95	\$ 8,999.50



Brand: [Flowline](#) Part #: LU28-00 Model #: EchoSonic II

## Flowline LU28-00 EchoSonic II Ultrasonic Liquid Transmitter

### **Flowline, LU28-10, EchoSonic II 26.2' Metric Ultrasonic Liquid Level Transmitter**

The general purpose ultrasonic level transmitter provides continuous level measurement with a 4-20 mA signal output, and is configured via free WebCal software. This non-contact liquid level sensor is ideally suited for corrosive, sticky or waste liquids, and is selected for bulk storage, tanker truck, day tank, process tank, waste sump, neutralization tank, open channel, chemical feed and clarifier applications.

#### **Features:**

- Offered in 4 measurement ranges from 26.2'
- Configuration is fast and easy via WebCal software and USB adapter
- Narrow 3" beam width for applications with limited measurement space
- Short 8" dead band maximizes the measurable filling capacity of the tank
- PVDF transducer and 6P polycarbonate enclosure for corrosive liquids
- Automatic temperature compensation for accurate measurement

# Technical Details

Range:	8" to 26.2' (20cm to 8m)
Accuracy:	± 0.2% of range
Resolution:	0.079" (2mm)
Dead Band:	8" (20cm)
Beam Width:	3" (7.6cm)
Configuration:	WebCal PC Windows USB 2.0
Memory:	Non-volatile
Supply Voltage:	24 VDC (loop)
Consumption:	0.5W
Loop Resistance:	500 ohms @ 24 VDC
Signal Output:	4-20 mA, two-wire
Signal Invert:	4-20 mA or 20-4 mA
Signal Fail-Safe:	4 mA, 20 mA, 21 mA, 22 mA or hold last
Process Temp.:	F: -4° to 140°, C: -20° to 60°
Temp. Comp.:	Automatic
Ambient Temp.:	F: -31° to 140°, C: -35° to 60°
Pressure:	MWP = 30 PSI (2 bar)
Enclosure Rating:	Type 6P, encapsulated, corrosion resistant & submersible
Encl. Material:	Polycarbonate
Trans. Material:	PVDF
Cable Jacket Mat.:	Polyurethane
Cable Type:	4-conductor, shielded
Cable Length:	10' (3m)
Process Mount:	2" Metric
Mount Gasket:	Viton
Certificates:	General purpose
Compliance:	CE, RoHS
Approvals:	cFMus