

DATE: 5/19/2021

Page: 6

BID NO.: 50-00134539

**BID FORM**  
Non Public Works

All Public Work Projects are required to use the Louisiana Uniform Public Work Bid Form

All prices must be held firm unless an escalation provision is requested in this bid. Jefferson Parish will allow one escalation during the term of the contract, which may not exceed the U.S. Bureau of Labor Statistics National Index for all Urban Consumers, unadjusted 12 month figure. The most recently published figure issued at the time an adjustment is requested will be used. A request must be made in writing by the vendor, and the escalation will only be applied to purchases made after the request is made.

Are you requesting an escalation provision?

YES \_\_\_\_\_ NO X

MAXIMUM ESCALATION PERCENTAGE REQUESTED N/A %

INITIAL BID PRICES WILL REMAIN FIRM THROUGH THE DATE OF June 8, 2023.

For the purposes of comparison of bids when an escalation provision is requested, Jefferson Parish will apply the maximum escalation percentage quoted by the bidder to the period to which it is applied in the bid. The initial price and the escalation will be used to calculate the total bid price. It will be assumed, for comparison of prices only, that an equal amount of material or labor is purchased each month throughout the entire contract.

**DELIVERY: FOB JEFFERSON PARISH**

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES 14-21 Days ARO

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) N/A

**THIS SECTION MUST BE COMPLETED BY BIDDER:**

FIRM NAME: North America Fire Equipment Co., Inc. (NAFECO)

ADDRESS: 1515 West Moulton Street

CITY, STATE: Decatur, AL ZIP: 35601

TELEPHONE: (256) 353-7100 FAX: (256) 355-0852

EMAIL ADDRESS: ronald.woodall@nafeco.com

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form by placing the addendum number as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: N/A

NUMBER: \_\_\_\_\_

NUMBER: \_\_\_\_\_

NUMBER: \_\_\_\_\_

TOTAL PRICE OF ALL BID ITEMS: \$ 98,725.00

AUTHORIZED  
SIGNATURE: Ronald Woodall

Ronald Woodall

Printed Name

TITLE: Vice President

SIGNING INDICATES YOU HAVE READ AND COMPLY WITH THE INSTRUCTIONS AND CONDITIONS.

NOTE: All bids should be returned with the BID NUMBER and BID OPENING DATE indicated on the outside of the envelope submitted to the Purchasing Department.



DATE: 5/19/2021

Page 7

## INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00134539

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	270.00	PR	<p>TWO (2) YEAR CONTRACT FOR THE SUPPLY OF LEATHER STRUCTURAL FIRE FIGHTING BOOTS FOR THE JEFFERSON PARISH EAST BANK CONSOLIDATED FIRE DEPARTMENT</p> <p>0010 MEN'S LEATHER SUPREME STRUCTURAL 14" PULL-ON FIRE FIGHTING BOOTS</p> <p>MFR: GLOBE MFR PART NO. 1201400</p> <p>TWO (2) YEAR CONTRACT FOR LEATHER STRUCTURAL FIRE FIGHTING BOOTS FOR THE JEFFERSON PARISH EAST BANK CONSOLIDATED FIRE DEPARTMENT</p>	<p>\$359.00</p> <p><i>Bidding LION Knockdown Elite Leather Boot, Mens, 804-6389</i></p>	<p>\$96,930.00</p>
2	5.00	PR	<p>0020 WOMEN'S LEATHER SUPREME STRUCTURAL 14" PULL-ON FIRE FIGHTING BOOTS</p> <p>MFR: GLOBE MFR PART NO. 120140W</p>	<p>\$359.00</p> <p><i>Bidding LION Knockdown Elite Leather Boot, Womens, 504-6389</i></p>	<p>\$1,795.00</p>



**NAFECO™**  
 1515 West Moulton Street  
 Decatur, Alabama 35601  
 800-628-6233  
 Fax (256) 355-0852  
[www.nafeco.com](http://www.nafeco.com)

## CORPORATE RESOLUTION

EXCERPT FROM MINUTES OF MEETING OF THE BOARD OF DIRECTORS OF  
North America Fire Equipment Co., Inc.

INCORPORATED.

AT THE MEETING OF DIRECTORS OF North America Fire Equipment Co.,  
INCORPORATED, DULY NOTICED AND HELD ON Wed., June 2, 2021,  
A QUORUM BEING THERE PRESENT, ON MOTION DULY MADE AND SECONDED. IT  
WAS:

RESOLVED THAT Ronald Woodall, Vice President, BE AND IS HEREBY  
APPOINTED, CONSTITUTED AND DESIGNATED AS AGENT AND ATTORNEY-IN-  
FACT OF THE CORPORATION WITH FULL POWER AND AUTHORITY TO ACT ON  
BEHALF OF THIS CORPORATION IN ALL NEGOTIATIONS, BIDDING, CONCERNS  
AND TRANSACTIONS WITH THE PARISH OF JEFFERSON OR ANY OF ITS AGENCIES,  
DEPARTMENTS, EMPLOYEES OR AGENTS, INCLUDING BUT NOT LIMITED TO, THE  
EXECUTION OF ALL BIDS, PAPERS, DOCUMENTS, AFFIDAVITS, BONDS, SURETIES,  
CONTRACTS AND ACTS AND TO RECEIVE ALL PURCHASE ORDERS AND NOTICES  
ISSUED PURSUANT TO THE PROVISIONS OF ANY SUCH BID OR CONTRACT, THIS  
CORPORATION HEREBY RATIFYING, APPROVING, CONFIRMING, AND ACCEPTING  
EACH AND EVERY SUCH ACT PERFORMED BY SAID AGENT AND ATTORNEY-IN-  
FACT.


I HEREBY CERTIFY THE FOREGOING TO BE  
A TRUE AND CORRECT COPY OF AN  
EXCERPT OF THE MINUTES OF THE ABOVE  
DATED MEETING OF THE BOARD OF  
DIRECTORS OF SAID CORPORATION, AND  
THE SAME HAS NOT BEEN REVOKED OR  
RESCINDED.

Brian Oaks  
SECRETARY-TREASURER

Brian Oaks

6/3/2021

DATE



**Non-Public Works Bid**

**AFFIDAVIT**

**STATE OF** Alabama

**PARISH/COUNTY OF** Morgan

BEFORE ME, the undersigned authority, personally came and appeared: Ronald  
Woodall, (Affiant) who after being by me duly sworn, deposed and said that  
he/she is the fully authorized Vice President of North America Fire  
Equipment Co., Inc. (Entity),  
the party who submitted a bid in response to Bid Number 50-00134539, to the Parish of  
Jefferson.

Affiant further said:

**Campaign Contribution Disclosures**

**(Choose A or B, if option A is indicated please include the required  
attachment):**

**Choice A** \_\_\_\_\_ Attached hereto is a list of all campaign contributions, including  
the date and amount of each contribution, made to current or  
former elected officials of the Parish of Jefferson by Entity,  
Affiant, and/or officers, directors and owners, including  
employees, owning 25% or more of the Entity during the two-year  
period immediately preceding the date of this affidavit or the  
current term of the elected official, whichever is greater. Further,  
Entity, Affiant, and/or Entity Owners have not made any  
contributions to or in support of current or former members of the  
Jefferson Parish Council or the Jefferson Parish President through  
or in the name of another person or legal entity, either directly or  
indirectly.

**Choice B** X there are **NO** campaign contributions made which would require  
disclosure under Choice A of this section.

Debt Disclosures

**(Choose A or B, if option A is indicated please include the required attachment):**

**Choice A** \_\_\_\_\_ Attached hereto is a list of all debts owed by the affiant to any elected or appointed official of the Parish of Jefferson, and any and all debts owed by any elected or appointed official of the Parish to the Affiant.


**Choice B**   X   There are NO debts which would require disclosure under Choice A of this section.

**Affiant further said:**

That Affiant has employed no person, corporation, firm, association, or other organization, either directly or indirectly, to secure the public contract under which he received payment, other than persons regularly employed by the Affiant whose services in connection with the construction, alteration or demolition of the public building or project or in securing the public contract were in the regular course of their duties for Affiant; and

*[The remainder of this page is intentionally left blank.]*

That no part of the contract price received by Affiant was paid or will be paid to any person, corporation, firm, association, or other organization for soliciting the contract, other than the payment of their normal compensation to persons regularly employed by the Affiant whose services in connection with the construction, alteration or demolition of the public building or project were in the regular course of their duties for Affiant.




Signature of Affiant

Ronald Woodall

Printed Name of Affiant

SWORN AND SUBSCRIBED TO BEFORE ME

ON THE 3rd DAY OF June, 20 21

  
Notary Public

Angela Diane Henderson

Printed Name of Notary

n/a

Notary/Bar Roll Number

My commission expires 7/5/22.



**TWO (2) YEAR CONTRACT FOR THE SUPPLY OF  
Leather Structural Firefighting 14" Pull-On Boots  
FOR THE JEFFERSON PARISH EAST BANK CONSOLIDATED  
FIRE DEPARTMENT**

**Scope** – This specification will outline the requirements for leather structural firefighting 14" pull-on bunker boots.

These specifications completed by selecting whether the quoted items comply or provide exception to each of the below sections. Any and all exceptions for each section *must be clearly stated for each heading* and included in the bid submission. *Use additional pages for exceptions, if necessary.*

**NFPA 1971 and NFPA 1992 Certified**

Boots must meet or exceed the requirements of NFPA 1971, *Standard on Protective Ensembles for Structural Firefighting and Proximity Firefighting, Current Edition* for Structural Fire Fighting and NFPA 1992, *Standard on Liquid Splash-Protective Ensembles and Clothing for Hazardous Materials Emergencies, Current Edition*.

☒ Comply      ☐ Exception

**General Design**

14 inch Pull-On athletic footwear (cement construction) boot, black flame-resistant and water-resistant leather, double-stitched leather joining seams, hi-vis yellow and silver reflective trim, leather-trimmed webbing pull straps, padded leather collar, padded leather flex joints in the shaft above vamp and heel, liquid and chemical resistant breathable bootie liner, cut-resistant and thermal protective bootie-shield liner, composite safety toe cap, composite shank, composite penetration-resistant insole barrier, molded shin guard, flame-resistant synthetic rubber molded cup outsole and toe bumper, 3D lasting board, molded composite heel counter, internal heel fit system, and a removable molded footbed as well as an additional insert for use in conjunction with the footbed.

☒ Comply      ☐ Exception

**Slip Resistance**

Boots must exceed the minimum test values for slip resistance (average of left and right foot) as detailed below to provide superior performance in dry, wet, and frosted ice conditions. Boots that do not exceed these minimums in all conditions shall not be acceptable. Bidders must promptly supply a Technical Services Report from a recognized independent testing laboratory upon request showing the boots bid exceed this requirement.

Test Method: SATRA TM144:2011

Slip Resistance of Footwear and Floorings  
Load = 500 N

Dry Clay Quarry Tile: Forepart > 1.00

Heel > 1.00  
Wet Clay Quarry Tile: Forepart > 0.60  
Heel > 0.60  
Frosted Ice -7°C Run 1: Forepart = 0.28  
Heel = 0.28  
Frosted Ice -7°C Run 4: Forepart > 0.12  
Heel > 0.12

For maximum slip resistance each outsole shall have Siping lines. Siping lines cut into flat areas open up when flexed to provide additional traction on water and ice. The boot shall also include self-cleaning lugs and an omni-direction tread pattern designed for superior performance in all terrains and when working on ladders.

☒ Comply ☐ Exception

### **Flexibility**

Boots must reach the Maximum Flex Angle of 48 degrees without exceeding the critical bending moment with a resulting stiffness index less than 10.0 as detailed below to provide maximum flexibility. Boots that do not meet this requirement shall not be acceptable. Bidders must promptly supply a Technical Services Report from a recognized independent testing laboratory upon request showing the boots bid meet this requirement.

Test Method: SATRA TM194:2004

Longitudinal stiffness of footwear

☒ Comply ☐ Exception

### **FireStorm Leather**

Boots shall be made from heavy-duty, flame-resistant and water-resistant full-grain cattle hide leather measuring 2.0 – 2.2 mm of thickness for durable tear and puncture resistance. Tumbled full-grain cattle hide leather shall be utilized in collar and flex areas for mobility. The leather shall be chrome tanned to withstand high temperature with minimal shrinkage, re-tanned to impart water resistance and low water absorption, and finished to retain maximum breathability. Leather shall meet or exceed the following physical tests:

Water Penetration	ASTM D2099	15,000 flex minimum
Dynamic Water Absorption	ASTM D2099	15% maximum
Static Water Absorption	ASTM D6015	30% maximum
Slit Tearing Strength	ASTM D2212	30 pound minimum
Moisture Vapor Transmission	ASTM D5052	350 g/meter <sup>2</sup> /24 hours minimum
Flame Resistance	NFPA 1971	afterflame no more than 2.0 sec, not melt or drip, no burn through

☒ Comply ☐ Exception

### **CROSSTECH® Footwear Fabric**

A full-height, full sock, bootie liner made from a package of Omaha lining fabric, 300g felt insulation, and CROSSTECH® moisture barrier shall be provided for a liquid resistant and breathable moisture barrier as well as thermal protection as defined by the specified NFPA standards.

☒ Comply ☐ Exception



**Athletic Footwear (Cement) Construction Outsole**

For optimum flexibility, comfort, and weight reduction, the boot shall include a VIBRAM® Synthetic Rubber Sculpted, Contoured Cup Outsole cemented to the bottom and sides of the upper using a 2-part cross-linking adhesive that forms a bond stronger than the materials it attaches. The outsole must be made from a flame, abrasion, oil, acid, and slip resistant compound engineered for high-traction, cold-weather resistance, and durability. Goodyear welt or direct attach construction methods shall not be acceptable.

  X   Comply             Exception

**Bootie-Shield Liner**

A protective bootie-shield of KEVLAR® fiber blend stitchbonded non-woven batting weighing 4.0 oz/yd<sup>2</sup> shall be positioned between the leather shell and the CROSSTECH® moisture barrier bootie to provide abrasion and cut resistance and additional thermal protection. Boots that do not have an additional Flame Resistant (FR) protective bootie-shield between the leather shell and the CROSSTECH® moisture barrier bootie shall not be acceptable.

  X   Comply             Exception

**Composite Safety Toe Cap**

The safety toe shall consist of a composite material that is lighter than steel, does not transmit heat or cold, and will spring back to shape after impact. Metal toe caps shall not be acceptable.

  X   Comply             Exception

**Padded Leather Collar**

The padded collar shall have a rolled top edge formed by folding over the leather to help the boots slide against the pants liner and reduce the potential for the pants liner to hang up on the top of the boots as well as to reduce abrasion against the wearer's calf.

  X   Comply             Exception

**Composite Penetration Resistant Insole Barrier**

Penetration resistance shall be provided by a composite insole to maximize flexibility and insulate from heat or cold transmission. Must exceed NFPA standards for safety. Metal plates shall not be acceptable.

  X   Comply             Exception

**3D Composite Lasting Board**

Boot uppers shall be lasted to a molded and contoured dual-density lasting board with a built-in flex zone in the forefoot and a torsionally stable heel. Flat fiber board lasting boards shall not be acceptable.

  X   Comply             Exception

**Composite Shank**

The shank shall consist of a composite material that is lighter than steel, does not transmit heat or cold, and springs back to shape better. Metal shank shall not be acceptable.

☒ X Comply      ☐ Exception

**Molded Heel Counter**

Boots shall have a molded heel counter of water-resistant composite material individually molded to fit each size perfectly. Leather or fiber board heel counters shall not be acceptable.

☒ X Comply      ☐ Exception

**Padded Shin Guard**

Boots shall include a padded composite shin guard to provide extra protection when working on a ladder. Moisture absorbing natural fiber padding shall not be acceptable.

☒ X Comply      ☐ Exception

**Synthetic Rubber Toe Bumper**

Boots shall have a molded Flame Resistant (FR) synthetic rubber toe bumper to provide abrasion resistance when crawling. The toe bumper shall be cemented and 2-needle stitched to the vamp.

☒ X Comply      ☐ Exception

**3M SCOTCHLITE™ Reflective Material**

Boots shall have flame-resistant fluorescent yellow and silver 3M SCOTCHLITE™ reflective material sewn to both sides of the shaft for added visibility.

☒ X Comply      ☐ Exception

**Webbing Pull-Straps**

Boots shall have NOMEX® webbing pull-straps with leather trim securely attached to the leather uppers by inserting into to collar seam to minimize stitching through the leather. Pull strength must be a minimum of 120 lbs when tested with a single handle.

☒ X Comply      ☐ Exception

**Internal Fit System**

Boots shall have an anatomical foam insert that wraps around the top and sides of the heel with an opening to fit and hold the back of the heel securely while cushioning the ankle.

☒ X Comply      ☐ Exception

**3D Molded Footbeds System**

Boots shall have a removable urethane foam footbed. The footbeds are contoured to cradle and cushion the bottom of the foot and to provide arch support. The footbeds shall have a moisture-wicking and anti-microbial fabric top layer. A second pair of 3D molded footbeds that are thicker in the forefoot is provided with every pair for a custom fit. This thicker footbed provides a snugger fit.

☒ X Comply      ☒ X Exception

**Sizes**

Boots must be available in Men's full sizes 5 – 18 and half sizes 5½ – 15½ in Narrow, Medium, Wide, and X-Wide widths. Boots must also be available in a Wide Calf model in the same size

range that will provide an additional 3 inches in circumference at the calf to fit those with larger calves. Boots must be available in Women's full sizes 5 – 12 and half sizes 5½ – 11½ in Narrow, Medium, Wide, and X-Wide widths.

☐ Comply ☒ Exception

#### **Resoling Service**

The winning vendor shall have resoling services available at their factory as needed.

☐ Comply ☒ Exception

#### **Country of Origin**

Boots shall be manufactured in the United States.

☐ Comply ☒ Exception

#### **Third Party Testing and Listing Program**

The footwear shall be tested for compliance to NFPA Standard 1971 and 1992 by a recognized independent testing lab which shall certify and list compliance to that standard. Such certification shall be denoted by the independent testing labs mark on the certification label affixed to the boots.

☒ Comply ☐ Exception

#### **Labels**

Appropriate warning label(s) shall be permanently affixed to each boot. Additionally, the label(s) shall include the following information.

Compliance to applicable NFPA Standard(s); current edition(s).

Independent Testing Lab mark

Manufacturer's name

Manufacturer's address

Manufacturer's boot identification number

Date of manufacture

Size

☒ Comply ☐ Exception

#### **ISO Certification/Registration**

The manufacturer shall be certified and registered to ISO Standard 9001 to assure a satisfactory level of quality.

☒ Comply ☐ Exception

#### **Warranty**

The manufacturer shall warrant these boots to be free from defects in materials and workmanship for one year when properly used and cared for.

☒ Comply ☐ Exception

#### **Sizing by Vendor**

The vendor shall be available to perform all sizing requirements.

X   Comply             Exception

### **PPE Record Keeping**

The manufacturer shall make available at no-charge, a password protected data based backed website that allows all brands of PPE assets are being recorded. The website shall have the functionality to allow the manufacturer to import all of the pertinent data into the department's account so that the initial data entry by fire department personnel is eliminated.

The website shall allow for the department to use a barcode scanner, if desired, to scan the Interleaved 2 of 5 barcode found in the gear by going to the Search the Serial Number page in PPE record keeping program, and scanning the asset's barcoded serial number.

  X   Comply             Exception

### **Exceptions to Specifications**

Any and all exceptions to the above specifications must be clearly stated for each heading. Use additional pages for exceptions, if necessary.

- 1) 3D MOLDED FOOTBED SYSTEM - Insole is provided, however not a 2nd pair.
- 2) SIZES - The LION By Thorogood Knockdown Elite is available in Mens sizes 5-16 (half sizes, medium/wide/extra wide widths). The LION By Thorogood Knockdown Elite is available in Womens sizes 5-10 (half sizes, narrow/medium/wide widths).
- 3) RESOLING SERVICE - Resoling service is not required or available.
- 4) COUNTRY OF ORIGIN - The LION by Thorogood Knockdown Elite boot is not made in the US.



## KnockDown Elite 14" Leather Boot



No matter how many times the alarm sounds during your shift, these black flame-resisting leather upper KnockDown boots go on with ease. Once your foot slides in, the ankle lock system holds you firmly in place until you use the handy heel kick plate to take them off. Our exclusive Vibram® Fire & Ice All-Terrain Sole provides exceptional traction on any surface; including pitched roofs and steep embankments. It stands up to the heat and will help keep a steady foot when fighting winter fires and the water turns to ice. The PTFE Moisture Barrier also repels dangerous fluids. Take a hit to the heel thanks to the Poron® XRD® padding - the same impact protection used in motocross racing. Composite Safety Toe, Lenzi L-Protection® insole, and steel triple-rib ladder shank protect your foot from impact and the strain of working on ladders. And because you might be on your feet for hours, the dual-density removable insole molds to the shape of your foot to keep you comfortable until you're back at the station.

- Waterproof, flame-resisting leather upper with abrasion-resisting rubber toe and heel protection.
- Removable dual-density polyurethane insole
- Lenzi L-Protection® flexible, non-metallic, puncture-resisting insole
- Steel triple-rib ladder shank
- Exclusive Vibram® ATS sole with Fire & Ice technology
- Cement construction
- Certified to meet NFPA 1971 structural & NFPA 1992 liquid splash
- Meets ASTM F2413-11
- CSA Z195-14 Edition-7



**3M Scotchlite™**  
Reflective Material HI-VIS

STYLE #	SLIP-RESISTING	WATERPROOF	PUNCTURE-RESISTING	BLOOD-BORNE PATHOGENS	EH/SD	TOE PROTECTION	STRUCTURAL & HAZMAT	SIZES:	N	M	W	XW
804-6389	✓	●	✓	●	EH	Comp [75]	✓	MEN'S	5-16	5-16	5-16	5-16
504-6389	✓	●	✓	●	EH	Comp [75]	✓	WOMEN'S	5-10	5-10	5-10	5-10

## TECHNICAL FEATURES

Structural  
CERTIFIED  
NFPA 1971

Hazmat  
CERTIFIED  
NFPA 1992



- A. Air Venting System
- B. Water-Proof, Breathable Membrane
- C. Easy-Doff Heel Kick Plate
- D. Non-Metallic Composite Safety Toe
- E. Ankle Lock System and Ankle Protection
- F. All-Terrain Sole and Side Wall Lugs



CALL 1.800.421.2926



## **NFPA FIRE BOOT WARRANTY**

### **LEATHER FOOTWEAR**

All leather Thorogood NFPA products manufactured by Weinbrenner Shoe Company or its authorized distributors are guaranteed to be free of any manufacturing or material defects for a period of one year from date of purchase with the exception of the sole which shall be warranted for the usable life of the boot. (Normal sole wear is not considered a defect.)

See warranty hang tag attached to boots for complete details. You must activate your warranty. Register your warranty at [weinbrennerusa.com/warranty](http://weinbrennerusa.com/warranty) or call 1-800-826-0002.

This is a limited warranty. Thorogood makes no other warranties including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. In no event will Weinbrenner Shoe Company be liable for incidental or consequential damages even if it has been advised of the possibility of such damages.





# CERTIFICATE OF LIABILITY INSURANCE

DATE (MM/DD/YYYY)

03/10/2021

THIS CERTIFICATE IS ISSUED AS A MATTER OF INFORMATION ONLY AND CONFERS NO RIGHTS UPON THE CERTIFICATE HOLDER. THIS CERTIFICATE DOES NOT AFFIRMATIVELY OR NEGATIVELY AMEND, EXTEND OR ALTER THE COVERAGE AFFORDED BY THE POLICIES BELOW. THIS CERTIFICATE OF INSURANCE DOES NOT CONSTITUTE A CONTRACT BETWEEN THE ISSUING INSURER(S), AUTHORIZED REPRESENTATIVE OR PRODUCER, AND THE CERTIFICATE HOLDER.

**IMPORTANT:** If the certificate holder is an ADDITIONAL INSURED, the policy(ies) must have ADDITIONAL INSURED provisions or be endorsed. If SUBROGATION IS WAIVED, subject to the terms and conditions of the policy, certain policies may require an endorsement. A statement on this certificate does not confer rights to the certificate holder in lieu of such endorsement(s).

PRODUCER Stovall Marks Insurance 2601 Danville Rd SW  Decatur AL 35603	CONTACT NAME: Kerrie Scott PHONE (A/C, No, Ext): (256) 355-7951 FAX (A/C, No): (256) 350-2022 E-MAIL ADDRESS: kscott@stovallmarks.com
INSURED  North America Fire Equipment Co., Inc. Dba Nafeco 1515 W. Moulton St.  Decatur AL 35601	INSURER(S) AFFORDING COVERAGE INSURER A: Mesa Underwriters Specialty Insurance Company NAIC # 36838 INSURER B: Employers Mutual Casualty Company 21415 INSURER C: Evanston Insurance Company 35378 INSURER D: Ala SIWCF/Midwest Employers Casualty Co. 23612 INSURER E: INSURER F:

## COVERAGES

CERTIFICATE NUMBER: CL2131006829

REVISION NUMBER:

THIS IS TO CERTIFY THAT THE POLICIES OF INSURANCE LISTED BELOW HAVE BEEN ISSUED TO THE INSURED NAMED ABOVE FOR THE POLICY PERIOD INDICATED. NOTWITHSTANDING ANY REQUIREMENT, TERM OR CONDITION OF ANY CONTRACT OR OTHER DOCUMENT WITH RESPECT TO WHICH THIS CERTIFICATE MAY BE ISSUED OR MAY PERTAIN, THE INSURANCE AFFORDED BY THE POLICIES DESCRIBED HEREIN IS SUBJECT TO ALL THE TERMS, EXCLUSIONS AND CONDITIONS OF SUCH POLICIES. LIMITS SHOWN MAY HAVE BEEN REDUCED BY PAID CLAIMS.

INSR LTR	TYPE OF INSURANCE	ADDL INSD	SUBR VVD	POLICY NUMBER	POLICY EFF (MM/DD/YYYY)	POLICY EXP (MM/DD/YYYY)	LIMITS
A	<input checked="" type="checkbox"/> COMMERCIAL GENERAL LIABILITY <input type="checkbox"/> CLAIMS-MADE <input checked="" type="checkbox"/> OCCUR  GEN'L AGGREGATE LIMIT APPLIES PER: <input checked="" type="checkbox"/> POLICY <input type="checkbox"/> PROJECT <input type="checkbox"/> LOC OTHER:	Y		MP0101001000052	12/12/2020	12/12/2021	EACH OCCURRENCE \$ 3,000,000 DAMAGE TO RENTED PREMISES (Ea occurrence) \$ 100,000 MED EXP (Any one person) \$ 5,000 PERSONAL & ADV INJURY \$ 3,000,000 GENERAL AGGREGATE \$ 3,000,000 PRODUCTS - COMP/OP AGG \$ 3,000,000 \$
B	AUTOMOBILE LIABILITY <input checked="" type="checkbox"/> ANY AUTO <input type="checkbox"/> OWNED AUTOS ONLY <input type="checkbox"/> HIRED AUTOS ONLY <input type="checkbox"/> SCHEDULED AUTOS <input type="checkbox"/> NON-OWNED AUTOS ONLY	Y		5E82722	03/10/2021	03/10/2022	COMBINED SINGLE LIMIT (Ea accident) \$ 1,000,000 BODILY INJURY (Per person) \$ BODILY INJURY (Per accident) \$ PROPERTY DAMAGE (Per accident) \$ \$
C	UMBRELLA LIAB <input checked="" type="checkbox"/> OCCUR EXCESS LIAB <input type="checkbox"/> CLAIMS-MADE DED RETENTION \$			XOBW8894321	03/10/2021	03/10/2022	EACH OCCURRENCE \$ 1,000,000 AGGREGATE \$ 1,000,000 \$
D	WORKERS COMPENSATION AND EMPLOYERS' LIABILITY ANY PROPRIETOR/PARTNER/EXECUTIVE OFFICER/MEMBER EXCLUDED? (Mandatory in NH) If yes, describe under DESCRIPTION OF OPERATIONS below	Y/N N	N/A	0374500PRAL129001	01/01/2021	01/01/2022	PER STATUTE OTH-ER E.L. EACH ACCIDENT \$ 1,000,000 E.L. DISEASE - EA EMPLOYEE \$ 1,000,000 E.L. DISEASE - POLICY LIMIT \$ 1,000,000

DESCRIPTION OF OPERATIONS / LOCATIONS / VEHICLES (ACORD 101, Additional Remarks Schedule, may be attached if more space is required)

## CERTIFICATE HOLDER

## CANCELLATION

SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, NOTICE WILL BE DELIVERED IN ACCORDANCE WITH THE POLICY PROVISIONS.

AUTHORIZED REPRESENTATIVE

© 1988-2015 ACORD CORPORATION. All rights reserved.