

# 3M™ Diamond Grade™ DG³ Reflective Sheeting 4090, White, 48 in x 50 yd

UPC #: 00051135340738, 3M Stock #: 7000004891, Previous 3M Stock #: 75030132486,  
Your Catalog #: Manage



Standard | In Stock: 114 Roll

Est. Lead Time: 2 Working Days

- 3M™ Diamond Grade™ DG³ Reflective Sheeting Series 4000 offers superior reflectivity at short and long distances
- Meets today’s highest published performance specifications
- Disadvantaged sign placement locations such as overhead or left shoulder
- One of the brightest durable sheeting for cost-efficient guidance
- Provides level of luminance needed by older drivers
- Accommodates drivers of large vehicles
- Fluorescent for added visibility during dawn, daytime, dusk and inclement weather
- Pressure-sensitive adhesive
- Warranted performance for up to 10 years

## Specifications

\* Smallest Saleable Unit

### Details

|                   |                    |
|-------------------|--------------------|
| Adhesive Features | Solvent-free       |
| Adhesive Type     | Pressure-sensitive |
| Availability      | Standard           |
| Brand             | Diamond Grade™     |
| Construction      | Microprismatic     |

|                                       |  |
|---------------------------------------|--|
| <b>eClass 14 Classification Group</b> | 35030590   |
| <b>Factory ISO Certification</b>      | No ISO Certification information available                         |
| <b>Imaging Method</b>                 | Digital Print<br>Overlay/Electronic Cut<br>Screenprint             |
| <b>Liner</b>                          | Yes  |
| <b>Overall Length (Imperial)</b>      | 50 yd  |
| <b>Overall Length (Metric)</b>        | 45.72 m  |
| <b>Overall Width (Imperial)</b>       | 48 in  |
| <b>Overall Width (Metric)</b>         | 1219.2 mm  |
| <b>Performance Level</b>              | Diamond Grade  |
| <b>Performance Tier</b>               | DG3  |
| <b>Product Code</b>                   | 4090   |
| <b>Product Color</b>                  | White  |
| <b>Product Series</b>                 | 4090   |
| <b>Product Usage</b>                  | Regulated Rigid Traffic Signs                                      |
| <b>Reflective Technology</b>          | Microprismatic   |
| <b>Service Life</b>                   | 12 Year  |
| <b>Shelf Life</b>                     | 1095 Days  |
| <b>Smallest Saleable Unit*</b>        | Case   |
| <b>Specifications Met</b>             | ASTM D4956 Type XI<br>ASTM D4956 Type IX<br>ASTM D4956 Type XI CWZ |
| <b>Substrate</b>                      | Plywood<br>Aluminum  |

## Dimensions and Classifications

|                            |                  |
|----------------------------|------------------|
| <b>Case Gross Weight*</b>  | 81.4 US pound    |
| <b>Case Height*</b>        | 11.3 Inch        |
| <b>Case Length*</b>        | 51.7 Inch        |
| <b>Case Width*</b>         | 10.2 Inch        |
| <b>Pallet Gross Weight</b> | 1,349.2 US pound |
| <b>Pallet Height</b>       | 1.4 Yard         |
| <b>Pallet Length</b>       | 1.4 Yard         |
| <b>Pallet Width</b>        | 1.2 Yard         |
| <b>Roll Gross Weight</b>   | 81.4 US pound    |
| <b>ECCN</b>                | EAR99            |
| <b>Harmonized Code</b>     | 3919905010       |

## Packaging and Identifications

|                                     |  |
|-------------------------------------|--|
| <b>Primary Shipping Location</b>    | DeKalb, Illinois   |
| <b>Country of Origin</b>            | USA  |
| <b>Country of Origin Disclaimer</b> | This is to advise you that as of this date, the Country of Origin for the product(s) displayed is as follows. This origin is for purposes of Normal Trade Relations (NTR) duty treatment, is for import/export documentation only, and is not intended to be used for any other purpose such as sales to government entities or Free Trade Agreement eligibility. Government procurement laws and Free Trade Agreements require application of specific criteria that may result in a different Country of Origin than indicated. These determinations are specific to Solventum ID. |
| <b>UPC/EAN - Billing (Roll)</b>     | 00051135340738   |
| <b>UPC/EAN – Shipper (Case)*</b>    | 00051135340738   |
| <b>per Case*</b>                    | 1 Roll   |
| <b>per Pallet</b>                   | 16 Roll  |

## Transportation

|   |   |
|---|---|
| <b>Transport Protective Service</b>   | PROTECTIVE SERVICE NOT REQUIRED   |
| <b>NMFC Item</b>  | 150930  |
| <b>NMFC Sub</b>   | 02  |
| <b>NMFC Class</b>   | 060.0   |
| <b>Flash Point</b>  | No Flash Point  |
| <b>United States Department of Transportation - Ground (US DOT, 49 CFR)</b> | NOT REGULATED   |
| <b>United States Department of Transportation - Vessel (US DOT, 49 CFR)</b> | NOT REGULATED   |
| <b>International Air Transport Association (IATA)</b>                       | NOT REGULATED   |
| <b>International Maritime Organization (IMO)</b>                            | NOT REGULATED   |
| <b>Transportation Disclaimer</b>  | These transportation classifications are provided as a customer service. AS THE SHIPPER YOU REMAIN RESPONSIBLE FOR COMPLYING WITH ALL THE APPLICABLE LAWS AND REGULATIONS, INCLUDING PROPER TRANSPORTATION CLASSIFICATION AND PACKAGING. 3M's transportation classifications are based on product formulations, packaging, 3M policies and 3M's understanding of applicable current regulations and is valid for the original 3M package only. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and NOT THE PACKAGING, LABELING OR MARKING REQUIREMENTS. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements. |
| <b>Air Shipping Available</b>   | Yes   |
| <b>Dry Ice Shipping Required</b>  | No  |

## Details

- 3M™ Diamond Grade™ DG<sup>3</sup> Reflective Sheeting Series 4000 offers superior reflectivity at short and long distances
- Meets today's highest published performance specifications
- Disadvantaged sign placement locations such as overhead or left shoulder
- One of the brightest durable sheeting for cost-efficient guidance
- Provides level of luminance needed by older drivers
- Accommodates drivers of large vehicles
- Fluorescent for added visibility during dawn, daytime, dusk and inclement weather
- Pressure-sensitive adhesive
- Warranted performance for up to 10 years

3M™ Diamond Grade™ Reflective Sheeting offers industry-leading retroreflectivity, conspicuity and legibility because of its highly efficient retroreflective optics. It helps improve safety by providing higher luminance values at distances most critical to drivers.

3M™ Diamond Grade™ DG<sup>3</sup> Reflective Sheeting is a highly reflective, durable, microprismatic lens sheeting with pressure sensitive adhesive.