

DATE: 4/03/2025

INVITATION TO BID  
THIS IS NOT AN ORDER

Page: 5

BID NO.: 50-00147354

**JEFFERSON PARISH**

PURCHASING DEPARTMENT  
P.O. BOX 9  
GRETNA, LA. 70054-0009  
504-364-2678

VENDOR: 27118 BLANK BID COPY VENDOR

PURCHASING SPECIALIST:  
SCHAMPAGNE

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

**DELIVERY: FOB JEFFERSON PARISH**

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

10 - 14 Days

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK

N/A

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK

N/A

In the event that addenda are issued with this bid, bidders **MUST** acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form by placing the addendum number as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: N/A  
NUMBER: N/A  
NUMBER: N/A  
NUMBER: N/A

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) N/A

**\*\*\* ALL BIDDERS MUST COMPLETE SECTION BELOW \*\*\***

FIRM NAME:

Rocky Mountain Recreation LLC

SIGNATURE:

(Must be signed here)



TITLE:

President

PRINT OR TYPE NAME:

Janeil Norman

ADDRESS:

PO Box 68

CITY, STATE:

Albion, ID

ZIP:

83311

TELEPHONE:

(208) 670-5079

FAX:

( ) N/A

EMAIL ADDRESS:

rockymtnrecllc@gmail.com

TOTAL PRICE OF ALL BID ITEMS: \$ 26,295.85

## INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00147354

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	1.00	EA	PURCHASE OF PARTS FOR JEFFERSON PARISH DEPARTMENT OF STREETS		
			0010 D185T4F ROTAIR 185CFM KOHLER DIESEL PORTABLE AIR COMPRESSOR	\$ 24,595.00	\$ 24,595.00
2	1.00	EA	JEFFERSON PARISH WESTBANK STREETS REPLACING UNIT 4571		
			0020 HD76075OLP HEAVY DUTY SPRING RETRACTABLE HOSE REEL - 3/8" X 75'	\$ 650.85	\$ 650.85
3	1.00	EA	HOSE, 1/4" MNPT, 300 PSI		
			0030 ESTIMATED SHIPPING	\$ 1050.00	\$ 1050.00
			***AS PER ATTACHED SPECIFICATION***		
			SHIP TO: JEFFERSON PARISH DEPARTMENT OF FLEET 4901 JEFFERSON HIGHWAY NEW ORLEANS, LA 70121		

# D185T4F

POWERFUL + COMPACT



Take on every job with the versatile D185T4F air compressor. The D185T4F is designed so you can complete jobs with the right tools. The combination of standard and optional features make the D185T4F the right machine for any application.

- › 5-Year/Unlimited Hour Airend Warranty
- › The metal enclosure resists dents and fading, as well as protects major components from job site hazards
- › Deep Sea Controller offers flexible control with built-in monitoring and protection
- › Intelligent Start/Stop System prevents cold-starting and blowback
- › Kohler's quiet and efficient engine operates without a DPF
- › The standard tool box is positioned to easily place and remove accessories
- › The optional Dual Pressure System allows you to work on applications that need 150 psi

## OPTIONS

Dual Pressure System | Hose Reel | Cold Weather Package | Telematics | Skid Support | Aftercooler

## D185T4F TECHNICAL DATA

COMPRESSOR	
Operating Pressure	100 psi (150 psi with Dual Pressure Option)
Free Air Delivery	185 cfm (145 cfm with Dual Pressure Option)
Minimum Working Pressure	73 psi
Drive System Engine-Airend	Direct Drive
Oil Cooling Capacity	2.75 gal
Outlet Valves	2 X 3/4"
Battery Capacity	12V 100Ah 790A
Fuel Tank Capacity	23 gal
Fuel Consumption	1.6 gph
Dimensions with Running Gear	L- 124" W- 53" H- 54"
Dimensions with Skid Configuration	L-70" W-42" H-55"
Dry Weight with Running Gear	1,960 lbs
Dry Weight with Skid Configuration	1,960 lbs
DIESEL ENGINE	
Engine Make	KOHLER
Engine Type	KDI 1903 TCR
Engine System	4 stroke - High Pressure Common Rail
Displacement	1903 cc
No. Cylinders	3
Aspiration	Turbo Intercooler
Max Engine Power @ 2600 RPM	49 HP
Max Engine Speed	2600 RPM
Min Engine Speed	1700 RPM
Cooling System	Water
Cooling System Capacity	3.70 gal
Lubrication System	Oil
Lubrication System Capacity	2.57 gal
Max Ambient Temperature	122°F
Min Working Temperature	14°F

### SERVICE + SUPPORT

- > 5-Year / Unlimited Hour ELGi Airend Warranty
- > 1-Year / 2000-Hour Full Machine Warranty
- > 3-Year / 4000-Hour Kohler Engine Warranty
- > Parts + Service Help - P: 704-523-4123 | E: [portableservice@elgi.com](mailto:portableservice@elgi.com) | [portableparts@elgi.com](mailto:portableparts@elgi.com)



# SH, MP & HP SERIES HEAVY DUTY HOSE REELS

**COXREELS® SH Series "Super Hub™" spring driven hose reels, like the P Series, have a long history of dependable performance.** The larger chassis and frame accommodate longer lengths and larger diameters of hose. Coxreels' original Super Hub™ dual axle support system increases the stability during operation, reduces vibration and strengthens the structural integrity of the reel.



Double axle support with Super Hub™

## SH, MP & HP SERIES :: REEL SPECIFICATIONS

### SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE

### DESIGN & STRUCTURE

- Sturdy single pedestal reel features Coxreels' exclusive Super Hub™ dual axle support system
- Guide arm adjusts to wall, floor, vehicle & overhead positions
- Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation

### RETRACTION

- Controlled retraction speed up to 80% slower on **EZ-COIL** models :: See page 7 for details
- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

### SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

### POSSIBLE FIELDS OF APPLICATION


- Air/Water Services
- Pneumatic Tools
- Washdown
- Lubrication
- Service / Mechanic / Utility Vehicles
- Chemical Fluid Transfer
- General Industrial
- Manufacturing Plants & Facilities
- Maintenance, Repair & Operations
- Automotive & Fleet Service Centers

### ACCESSORIZE YOUR REEL :: PG 52

- O-Rings & Swivels
- Mounting Brackets
- Hoses
- Assorted Reel Accessories

## SH, MP & HP SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.		MODEL	APRX. LBS.	
LOW PRESSURE			Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.						
SH-N-160	1/4"	1/2"	60	300	50	-	SHL-N-160	45	1
SH-N-350	3/8"	5/8"	50	300	50	EZ-SH-350	SHL-N-350	44	2
SH-N-360	3/8"	5/8"	60	300	53	-	SHL-N-360	46	2
SH-N-375	3/8"	5/8"	75	300	68	EZ-SH-375	SHL-N-375	59	3
SH-N-3100	3/8"	5/8"	100	300	71	EZ-SH-3100	SHL-N-3100	60	3
SH-N-435	1/2"	3/4"	35	300	49	-	SHL-N-435	43	2
SH-N-440	1/2"	3/4"	40	300	52	-	SHL-N-440	45	2
SH-N-450	1/2"	3/4"	50	300	54	EZ-SH-450	SHL-N-450	46	2
SH-N-475	1/2"	3/4"	75	300	68	EZ-SH-475	SHL-N-475	57	4
SH-N-4100	1/2"	3/4"	100	300	81	EZ-SH-4100	SHL-N-4100	66	4
SH-N-525	3/4"	1 1/16"	25	300	52	EZ-SH-525	SHL-N-525	45	5
SH-N-535	3/4"	1 1/16"	35	300	57	-	SHL-N-535	47	5
SH-N-550	3/4"	1 1/16"	50	300	69	EZ-SH-550	SHL-N-550	56	6
MEDIUM PRESSURE			Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 250°F.						
MP-N-340	3/8"	1 1/16"	40	3,000	63	-	MPL-N-340	53	2
MP-N-350	3/8"	1 1/16"	50	3,000	65	EZ-MP-350	MPL-N-350	53	2
MP-N-435	1/2"	1 3/16"	35	2,500	61	-	MPL-N-435	51	2
MP-N-440	1/2"	1 3/16"	40	2,500	62	-	MPL-N-440	51	2
MP-N-450	1/2"	1 3/16"	50	2,500	67	EZ-MP-450	MPL-N-450	53	7
MP-N-525	3/4"	1 1/16"	25	1,500	61	-	MPL-N-525	51	5
MP-N-535	3/4"	1 1/16"	35	1,500	68	-	MPL-N-535	54	5
HIGH PRESSURE			Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 250°F.						
HP-N-140	1/4"	9/16"	40	5,000	62	-	HPL-N-140	53	7
HP-N-150	1/4"	9/16"	50	5,000	64	EZ-HP-150	HPL-N-150	53	7
HP-N-160	1/4"	9/16"	60	5,000	70	-	HPL-N-160	56	7
HP-N-335	3/8"	1 1/16"	35	4,000	61	-	HPL-N-335	52	7
HP-N-340	3/8"	1 1/16"	40	4,000	64	-	HPL-N-340	54	7
HP-N-350	3/8"	1 1/16"	50	4,000	65	EZ-HP-350	HPL-N-350	53	8

To order **EZ-Coil®** equipped models less hose, please add prefix "EZ-"

## REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	7 5/8"	21 1/4"	19 1/2"	6"	6"	4"	5"
2	8 1/4"	21 1/4"	19 1/2"	6"	6"	4"	5"
3	8 1/4"	25 1/2"	24"	6"	6"	4"	5"
4	8 3/4"	25 1/2"	24"	6"	6"	4"	5"
5	9 3/8"	21 1/4"	19 1/2"	6"	6"	4"	5"
6	9 7/8"	25 1/2"	24"	6"	6"	4"	5"
7	8 3/4"	21 1/4"	19 1/2"	6"	6"	4"	5"
8	9 1/4"	21 1/4"	19 1/2"	6"	6"	4"	5"
Overall Dimensions				Base		Mounting Pattern	

