Catalog Number	71624
UPC Number	60198671624
Description	LED Ultra Thin Recessed Canopy Fixture 60W Voltage: 120/208/240/277



Shown with optional
recessed mounting Bezel/Trim
Cat# 71620

QPL ID #
P69Y1HN1

Features


Integral Cooling Fin Releases the Heat Efficiently to Maintain the Life of LEDs and LED Driver
Corrosion Die Cast Aluminum Housing
Prismatic Polycarbonate Lens
Superior Architectural White Powder Coat Finish
LG LEDs
Stainless Steel Hardware
5 Threaded Apertures - (1) Back, (4) Sides
50,000+ Hour Life Expectancy

General

Material:	Diecast Aluminum Housing
Lens:	Prismatic Polycarbonate Lens
Finish:	White Powdercoat
Lamp Type:	LED Array
Photocell:	Optional
Color Temperature:	5000K

Dimension Information

Length:	8-3/4"
Width:	8-3/4"
Height:	3-5/16""



Specifications

Color Temperature:	5000K
Lumens:	6,055
Wattage Rating:	60W
Light Pattern:	153° Beam Angle
CRI:	≥73
Input Current:	.49A
Temperature Rating:	-40°F to 131°F
Voltage Rating:	120/208/240/277

Packaging

Box Qty	1

Certifications

cULus	Yes
DLC	Yes
IP65(Nema 4X)	Yes
Warranty	5 Year