

DATE: 1/16/2019

INVITATION TO BID  
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00125291

**JEFFERSON PARISH**

PURCHASING DEPARTMENT  
P.O. BOX 9  
GRETN, LA. 70054-0009  
504-364-2678

VENDOR:

BUYER: MBUTTERY

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

**DELIVERY: FOB JEFFERSON PARISH**

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

5-6 WEEKS

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: \_\_\_\_\_

NUMBER: \_\_\_\_\_

NUMBER: \_\_\_\_\_

NUMBER: \_\_\_\_\_

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) \_\_\_\_\_

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***	
FIRM NAME: <u>Cimsco</u>	
SIGNATURE: (Must be signed here) <u>[Signature]</u>	TITLE: <u>SALES</u>
PRINT OR TYPE NAME: <u>JEFF DEVILLIER</u>	
ADDRESS: <u>1840 LWA RD</u>	
CITY, STATE: <u>METairie, LA</u>	ZIP: <u>70001</u>
TELEPHONE: <u>(504) 835-7319</u>	FAX: <u>(504) 832-0820</u>
EMAIL ADDRESS: <u>JEFF@Cimscoinc.com</u>	

TOTAL PRICE OF ALL BID ITEMS: \$ 10172.63

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	1.00	EA	<p>PURCHASE OF RUBBER FLAP CHECK VALVE FOR EAST BANK WATER PLANT</p> <p>0010 GOLDEN ANDERSON 24 IN. FIGURE SB200-D (OR EQUAL) RUBBER FLAPPER CHECK VALVE</p> <p>WATER DEPT.-EB WATER PLANT-MERVIN GRAVES</p> <p>THIS WILL BE USED TO REPLACE AN EXISTING VALVE ON THE EB WATER PLANT TRANSFER PUMP NUMBER 2.</p> <p>LOCATION:</p> <p>JEFFERSON PARISH EB WATER PLANT 3600 JEFFERSON HWY., BLDG. D JEFFERSON, LA 70121</p> <p>ATTN: MERVIN GRAVES 504-838-4398</p>	10172.63	10172.63
2	.00			-	-

## Rubber Flapper Check Valve

### 1.0 GENERAL

- A. Provide one (1) – Golden Anderson 24" Figure SB200-D or equivalent rubber flapper check valve. This shall be to replace one existing valve on the East Bank Water Treatment Plant transfer pumps. Face to face shall measure 48 inches.
- B. Winning bidder shall have valve delivered to the East bank Water Treatment Plant within 6 weeks from the date that bid is awarded.

### 1.1 QUALITY ASSURANCE

- A. Supplier shall, at the request of purchasing, provide detailed product data and descriptive literature including dimensions, weight, headloss, pressure rating, materials of construction and cross sectional drawings clearly illustrating the individual components.

### 2.0 PRODUCT

#### Rubber Flapper Check Valve

- A. The valve shall be rated for 250 PSI, have integral ANSI Class 125/150 flanged connections and employ only one (1) moving part – the flexible disc. The body shall have a “full waterway” with a flow area not less than the nominal pipe area through the valve. To minimize closure time, the valve shall seat on a 45 degree angle.
- B. The cover shall be removable and allow removal of the flexible disc without removing the valve from the line. The cover shall be of a “domed” shape to facilitate self-cleaning. There shall be a threaded port with pipe plug to permit installation of a visual or electrical position indicator. A mechanical position indicator shall also be provided for a visual indication of the disc position.
- C. The flexible disc shall be one piece and precision molded with alloy steel and nylon reinforcement and an integral O-ring style seat for drop tight seating at low pressure.
- D. The spring assist shall be one-piece construction formed with a large radius to allow smooth movement and provide rapid valve closure. The spring assist shall be secured to the cover using Type 316 screws and field replaceable without removing the valve from the line and or the need for special tools.

### 2.1 MATERIALS

- A. Valve body and cover shall be made from ductile iron per ASTM A536 Grade 65-45-12.
- B. The flexible disc shall be made from Buna-N (NBR) rubber.
- C. The spring assist shall be made from type 316 stainless steel.
- D. The valve body and cover shall be factory coated internally and externally with 12-16 mill of fusion bonded epoxy and be NSF-61 certified for contact with drinking water.