

DATE: 4/22/2019

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00126388

JEFFERSON PARISH
PURCHASING DEPARTMENT
P.O. BOX 9
GRETN, LA. 70054-0009
504-364-2678

VENDOR:

BUYER: MBUTTERY

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in wprkman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES _____

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK _____

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK _____

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: _____


NUMBER: _____

NUMBER: _____

NUMBER: _____

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

***** ALL BIDDERS MUST COMPLETE SECTION BELOW *****

FIRM NAME:	
PELICAN CONSTRUCTION SUPPLIES	SALES
SIGNATURE:	TITLE:
(Must be signed here) 	
PRINT OR TYPE NAME:	
Bryan D. Slate	
ADDRESS:	
305 23RD STREET	
CITY, STATE:	ZIP:
KENNER, LA	70062
TELEPHONE:	FAX:
504 468-1234	(504) 468 1211
EMAIL ADDRESS:	
bryan@pelicansupplies.com	

TOTAL PRICE OF ALL BID ITEMS: \$ 4,455.00

DATE: 4/22/2019

Page: 5

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00126388

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	108.00	EA	<p>PURCHASE OF STOCK FOR THE WEST BANK DRAINAGE WAREHOUSE</p> <p>0010 - STRONG PLUG, 1 MIN CURE TIME LEAK STOP IN A 50LB PAIL TO REPAIR MANHOLES AND CATCH BASINS, "STRONG PLUG", 42 PER PALLET</p> <p>SK#00-0482270</p> <p>DELIVER TO: JP WESTBANK WAREHOUSE 1500 RIVER PARK ROAD BRIDGE CITY LA 70094</p>	41.25	4,455.00

Remit To:
PO BOX 95
Kenner, LA 70063-0095
Phone (504) 468-1234

Pelican Construction Supplies

"Your Concrete Accessory Source"
Prompt Service Backed by Quality Manufacturers

305 23rd Street
Kenner, LA 70062
Fax (504) 468-1211
Watts (800) 982-5428

*****QUOTE***** 012257
QUOTE TO: QUOTE EXPIRES: 05/31/19
JEFFERSON DEPT. OF GENERAL SVC JP WESTBANK WAREHOUSE
PROCUREMENT PURCHASING DIV. 1500 RIVER PARK ROAD
P.O. BOX 9 BRIDGE CITY, LA 70094
GRETNA, LA 70054-0009

CONTACT: CASIO PHONE: (504) 349-5886

QUOTE#	ORDER-DTE	SALESPERS	REQ-DATE	SHIP VIA	WGHT	PGE
012257	APR 22 2019	HOU	APR 22 2019	PELICAN TRUCK		

CJST#	CUST PO NUMBER	DOC-REQ#	SUB TERMS	FREIGHT TRMS	FOB	INSD SALES
JEFGEN	MEADOW PLUG		NET 30	PREPAID	ORIGIN	BS

LIN	OR'D PRODUCT	UNIT	DESCRIPTION	UNIT \$	EXTENDED
001	108 CPWRPLUG	EA	50 LB MEADOW PLUG	41.25	4455.00
002					

SUB-TOTAL AMOUNT 4455.00

LOUISIANA EXEMPT 101

TOTAL AMOUNT 4455.00

WE APPRECIATE YOUR BUSINESS!!

RETURN POLICY: All returns subject to a restocking charge. No returns after 30 days.

PRODUCT DATA

MasterFormat: 03 62 13

W. R. MEADOWS.
SEAIGHT

NO. 389

SEPTEMBER 2014
(Supersedes March 2006)

MEADOW-PLUG™

One Component, Super Fast Setting, Hydraulic Repair Mortar

DESCRIPTION

MEADOW-PLUG is a specially blended, extremely fast setting, hydraulic cement product designed to instantly stop running water or fluid seepage in concrete or masonry structures. This single-component, high-strength repair mortar permanently plugs non-moving cracks, joints and voids.

USES

Once mixed with water to a putty-like consistency, MEADOW-PLUG may be hand formed to quickly stop active fluid leaks in basements, tunnels, swimming pools, sewers, non-potable water tanks, voids around pipes, and wall tie holes. It seals construction joints between floors and walls. MEADOW-PLUG is versatile enough for either vertical or horizontal applications; below-, above- or on-grade. Its controlled expansion formulation permanently holds the repair in place on exterior, interior, and even underwater installations.

FEATURES/BENEFITS

- Fast initial set/Stops liquid flow immediately.
- Expands as it sets/Forms a permanent water stop.
- Mixes with water only/Easy to use.
- Horizontal, vertical, interior, exterior/Highly versatile.
- Above grade, below grade, underwater/Multi-purpose.
- Non-metallic, non-corrosive/Will not stain.
- May be top-coated within one hour/Saves time.
- Good sulfate resistance/Suitable for wastewater and sewer applications.

PACKAGING

50 lb. (22.7 kg) Pails
8 lb. (3.6 kg) Tubs

COVERAGE

Yield: 0.45 ft.³ (0.012 m³)

Coverage

	Pail	Tub
¾" x ¾" (19 mm x 19 mm)	115 linear feet (35 m)	18 Linear Feet (5.4 m)
½" x ½" (12.7 mm x 12.7 mm)	259 Linear Feet (78 m)	41 Linear Feet (12.5 m)
¼" x ¼" (6.3 mm x 6.3 mm)	1036 Linear Feet (315 m)	165 Linear Feet (50 m)

SHELF LIFE

One year from date of manufacture when stored indoors on pallets in a dry, cool area. Do not store product outside.

TECHNICAL DATA

Compressive strength (Per ASTM C 109) at:

15 min.	850 psi (5.86 MPa)
1 hour	1225 psi (8.44 MPa)
1 day	2650 psi (18.27 MPa)
28 days	6000 psi (41.38 MPa)

Set time (Per ASTM C 191)

Initial: 2 minutes
Final: 3 minutes

All technical data is typical information, but may vary due to testing methods, conditions and operators.

Surface Preparation ... Cut or notch out the crack, joint, or void to a minimum dimension of ¾" x ¾" (19.1 mm x 19.1 mm). To ensure proper mechanical lock, the bottom of the newly notched opening should be wider than the top. (Avoid "V" type notches or cuts.)

CONTINUED ON REVERSE SIDE...

W. R. MEADOWS, INC.
P.O. Box 338 • HAMPSHIRE, IL 60140-0338
Phone: 847/214-2100 • Fax: 847/683-4544
1-800-342-5976
www.wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA
FORT WORTH, TX / BENICIA, CA / POMONA, CA
GOODYEAR, AZ / MILTON, ON / ST. ALBERT, AB

Mixing and Placement ... Mix MEADOW-PLUG with enough potable water to form a thick putty consistency (approximately a 4:1 powder-to-water ratio by volume). Do not mix more MEADOW-PLUG than can be placed in one minute. Force MEADOW-PLUG directly into prepared crack and hold in place, maintaining pressure until material hardens. Avoid overworking the material. Just prior to final set, MEADOW-PLUG may be "shaved" to match the profile of the area surrounding the patch. If repairing a dry crack, wet cure immediately for at least fifteen minutes or until set is fully achieved. **Do not use on any moving joints.**

PRECAUTIONS


MEADOW-PLUG is recommended for concrete, masonry and block repairs only. Do not apply below 40° F (4° C) or above 90° F (32° C) or when rain is imminent. Protect from freezing for a minimum of 24 hours. Do not bridge moving cracks. Extend existing control and expansion joints through MEADOW-PLUG. Do not add any admixtures. Exceeding liquid requirements shall result in reduced physical properties. Realize that set time will decrease as the product, air, substrate, and mixing liquid temperature increases and will increase as the temperature decreases. Protect from conditions that may cause early water loss: windy conditions, low humidity, high temperature, direct sunlight. Early water loss is exasperated in thin applications. Failure to follow industry standard practices may result in decreased material performance.

LEED INFORMATION

May help contribute to LEED credits:

- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

For most recent data sheet, further LEED information, and SDS, visit
www.wrmeadows.com.



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.