

DATE: 4/21/2016

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00116403

JEFFERSON PARISH
PURCHASING DEPARTMENT
P.O. BOX 9
GRETN, LA. 70054-0009
504-364-2678

VENDOR:

BUYER: LFRANCIS

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work is to be done in a workman-like manner, according to standard practices. Any deviations or alterations from the specifications must be indicated and backup documentation supplied with your quotation.

DELIVERY: FOB JEFFERSON PARISH

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

2 DAY ARO

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: _____

NUMBER: _____

NUMBER: _____

NUMBER: _____

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***

FIRM NAME:

SPAHR ENTERPRISES, INC.

SIGNATURE:

(Must be signed here)

TITLE:

PRINT OR TYPE NAME:

ADDRESS:

CITY, STATE:

ZIP:

TELEPHONE:

FAX:

EMAIL ADDRESS:

TOTAL PRICE OF ALL BID ITEMS: \$ 3593.70

DATE: 4/21/2016

INVITATION TO BID FROM JEFFERSON PARISH - continued

Page: 5

BID NO.: 50-00116403

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	2.00	DRUM	SUPPLY OF OIL FOR THE JEFFERSON PARISH DEPARTMENT OF PUBLIC WORKS - DRAINAGE		
			0010 55 gallon drum Valvoline premium blue 15w-40		119790
2	2.00	DRUM	Ship to: Bonnabel Pump Station 1500 Beverly Gardens Dr. Metairie La, 70006		
			0020 55 gallon drum Valvoline Premium Blue 15w-40		119790
3	2.00	DRUM	Ship to: Suburban Pump Station 4800 Lake Villa Dr. Metairie, La		
			0030 55 gallon drums Valvoline Premium Blue 15w-40		119790
			Ship to: Duncan Pump Station 1800 Joe Yenni Blvd Kenner, La 70065		
			Contact: Cordell Farrar 504-838-4374		
			SHALL RETAILER TRIPUP 15W40 15 SUBMITTED AS EQUAL QUALITY FOR ALL LOCATIONS		



Technical Data Sheet

Shell Rotella® T Triple Protection™ 15W-40 (CI-4) • Low Emissions • Extra Life - Improved Protection

Triple Protection Technology - Heavy Duty Diesel Engine Oils

Shell Rotella® T Triple Protection oil use the latest "Low-SAPS" additive technology to protect under the most severe conditions found in modern low emission engines. The protective power of the oil is enhanced through the use of high purity "Group II" base oils that provide increased additive activity. It delivers significant improvements in Wear protection, deposit control and resistance to breakdown under high temperatures*.

The exclusive low-ash formulation helps protect the exhaust catalysts and particulate traps found on the latest low emission vehicles. Recommended by a wide range of OEMs, suitable for both the latest low-emissions and older model equipment.

* Compared to API CI-4 Plus oils





ENERGISED PROTECTION
And going to your toughest operating conditions

Performance, Features & Benefits

- **Outstanding wear protection**
Demonstrated over millions of miles of customer service, Shell Rotella® T Triple Protection provides significantly better Wear protection than previous generation oils to maximize engine efficiency and prolong engine life.
- **Exceptional Engine cleanliness**
Formulated with improved soot control and an exclusive detergent system to deliver outstanding piston and Engine cleanliness.
- **Emissions system Compatibility**
The advanced low-ash formulation helps control blocking of particulate filters and poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.
- **Outstanding shear stability**
A continued heritage of outstanding shear stability for viscosity control and optimal oil pressure in your engine.
- **Exceptional low temperature properties**
Helps speed cold starts.

Main Applications



- **Severe duty heavy duty Diesel engines**
Provides outstanding protection for virtually all heavy duty Diesel engines, including the latest emission controlled engines using EGR and containing a Diesel Particulate Filter.

• Off-highway applications

Suitable for use in agricultural, mining, logging, and construction applications, even with high levels of fuel Sulfur.

• Hard working diesel and Gasoline engines

Suitable for use in pick-up trucks, sport-utility vehicles (SUVs), mini-vans and motorcycles.

Specifications, Approvals & Recommendations

- API: CJ-4, CI-4 Plus, CI-4, CH-4, CG-4, CF-4, CF.
- API: SM, SL, SJ, SH
- ACEA: E9, E7
- JASO DH-2, MA, MA2
- Caterpillar: ECF-1A, ECF-2, ECF-3
- Cummins: CES 20081
- DDC: 93K218
- Deutz: DQC III-10 LA
- Mack: EO-O Premium Plus
- Ford: WSS-M2C171-E
- MAN: M3575
- MB Approval: 228.31
- MTU: Category 2.1
- Renault Trucks: RLD-3
- Volvo VDS-4

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk, or the OEM Approvals website.

Typical physical Characteristics

Properties			Method	Shell Rotella T Triple Protection 15W-40 (CI-4)
SAE Viscosity Grade				15W-40
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	120
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	15.5
Viscosity Index			ASTM D2270	135
density	@15°C	kg/l	ASTM D4052	0.879
Sulfated Ash		%	ASTM D874	1.0
Total Base Number		mg KOH/g	ASTM D2896	10.1
Flash Point (COC)			ASTM D92	204
Pour Point		°C	ASTM D97	-30

These Characteristics are typical of current production. While future production will conform to Shell's specification, variations in These Characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Rotella T Triple Protection is unlikely to present any significant health or safety hazard when properly used in the recommended Application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Product recommendations for applications and specifications not covered here may be obtained from your Shell representative.



doc08237620160427093707

4/27/2016 9:38 AM

Adobe Acrobat D...

104 KB

SPAHR ENTERPRISES, INC.
INDUSTRIAL OIL & SUPPLY

FACSIMILE TRANSMITTAL SHEET

TO:

JEANETTE RASH

FROM:

David Spahr

COMPANY:

DATE:

FAX NUMBER:

364-2693

TOTAL NO. OF PAGES INCLUDING COVER:

5

PHONE NUMBER:

364-2678

PHONE NUMBER

504-368-5823

RE:

B.O.# 50-10116483

FAX NUMBER

504-368-7500

If any additional information is needed, please call 504-368-5823

NOTES/COMMENTS:

Thanks Again !!



David Spahr