



- Use in a straight line pull only
- Never shock load
- Never side load
- Inspect eyebolts before each use

*Item # 3*

- Always apply load in a gradually increasing manner
- If used in angular lift, (up to 45°) reduce WLL by 30%
- Seat eyebolt properly

## Eye Bolts – Regular Nut

- Forged Carbon Steel
- Hot Dip Galvanized
- Heavy Hex Nut

ITEM#	Size in inches	Working Load Limit in lbs. (Straight Pull)	Approx. Weight Each in Pounds	Dimensions in Inches		
	Diam. x Shank A x B			C	D	E
EB142GR	1/4 x 2	500	.066	1.50	.50	1.00
EB144GR	1/4 x 4	500	.091	2.50	.50	1.00
EB516214GR	5/16 x 2 1/4	800	.133	1.50	.62	1.25
*EB516414GR	5/16 x 4 1/4	800	.25	2.50	.62	1.25
EB38212GR	3/8 x 2 1/2	1,200	.243	1.50	.75	1.50
EB38412GR	3/8 x 4 1/2	1,200	.295	2.50	.75	1.50
EB386GR	3/8 x 6	1,200	.352	2.50	.75	1.50
EB122GR	1/2 x 2	2,200	.41	1.88	1.00	2.00
EB12314GR	1/2 x 3 1/4	2,200	.503	1.50	1.00	2.00
EB126GR	1/2 x 6	2,200	.661	3.00	1.00	2.00
EB128GR	1/2 x 8	2,200	.82	3.00	1.00	2.00
EB1210GR	1/2 x 10	2,200	.88	3.00	1.00	2.00
EB1212GR	1/2 x 12	2,200	1.14	3.00	1.00	2.00
EB584GR	5/8 x 4	3,500	1.03	2.00	1.25	2.50
EB586GR	5/8 x 6	3,500	1.18	3.00	1.25	2.50
EB588GR	5/8 x 8	3,500	1.35	3.00	1.25	2.50
EB5810GR	5/8 x 10	3,500	1.54	3.00	1.25	2.50
EB5812GR	5/8 x 12	3,500	1.67	4.00	1.25	2.50
EB5815GR	5/8 x 15	3,500	2.01	5.00	1.25	2.50
EB5818GR	5/8 x 18	3,500	2.18	6.00	1.25	2.50
EB5821GR	5/8 x 21	3,500	2.74	6.00	1.25	2.50
EB5824GR	5/8 x 24	3,500	2.84	6.00	1.25	2.50
EB34412GR	3/4 x 4 1/2	5,200	1.69	2.00	1.50	3.00
EB346GR	3/4 x 6	5,200	1.84	3.00	1.50	3.00
EB348GR	3/4 x 8	5,200	2.08	3.00	1.50	3.00
EB3410GR	3/4 x 10	5,200	2.35	3.00	1.50	3.00
EB3412GR	3/4 x 12	5,200	2.57	4.00	1.50	3.00
EB785GR	7/8 x 5	7,200	2.70	2.50	1.75	3.50
EB788GR	7/8 x 8	7,200	3.08	4.00	1.75	3.50
EB7812GR	7/8 x 12	7,200	4.00	4.00	1.75	3.50
EB16GR	1 x 6	10,000	4.21	3.00	2.00	4.00
EB19GR	1 x 9	10,000	4.68	4.00	2.00	4.00
EB112GR	1 x 12	10,000	5.40	4.00	2.00	4.00