

ADHESION TO STEEL:	50 oz/in PSTC-101
TENSILE STRENGTH:	42 lb/in ASTM D-1000
ELONGATION:	N/A
TEMPERATURE APPLICATION:	N/A
TEMPERATURE OPERATING:	40° to 200°F

DATA SHEET:

 [CDNT 528 Premium Gaffers Tape - "Best Seller"](https://4eelo4yoy1u3wlv52vzht3m-wpengine.netdna-ssl.com/wp-content/uploads/2015/09/product-sheet-528GB-black.pdf)
(<https://4eelo4yoy1u3wlv52vzht3m-wpengine.netdna-ssl.com/wp-content/uploads/2015/09/product-sheet-528GB-black.pdf>) (PDF)

SHELF LIFE:

Typical shelf life is one (1) year from date of manufacture (DOM).

RECOMMENDED STORAGE CONDITIONS:

Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

NOTES:

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are