

LED Wall Pack (MWP01)

Up to 8,100 + Lumens

Medium Wall Pack **30W&45W&70W**
Dimensions:14.213x13.07x7.402in.



Up to 16,400 + Lumens

Large Wall Pack **90W & 135W**
Dimensions:18x9.75x8.72in.
Available with **480V**



Accessories



Photocell - Button, 120V/120-277V

USE: Photocell is field installed or
Pre-installed in factory by requesting

NEW



Emergency Battery Backup

NO. EB-8W/90min-1
USE: 900lm 90min.
Only suitable for 45W, 70W.

ENHANCED LED PERFORMANCE IN A CLASSIC DESIGN

The LED wallpacks offer maximum light output for general purpose area and security lighting. They efficiently deliver lumens, and consume less energy than traditional wallpack MH technologies. This versatile luminaire is ideal for replacing existing MH fixtures. Applications: Security, pathway and perimeter lighting, Building entryways and walkways.

MEDIUM WALL PACK

SKU	WP30W27V50KD	WP45W27V50KD	WP70W27V50KD
LIGHT OUTPUT	3,400 Lumens	5,300 Lumens	8,100 Lumens
COLOR TEMP	5000K	5000K	5000K
POWER CONSUMPTION	30W	45W	70W
CRI	82	70	70
REPLACES	100W MH	175W MH	250W MH
PRICE			

LARGE WALL PACK

SKU	WP90W27V50KD	WP135W27V50KD
LIGHT OUTPUT	11,200 Lumens	16,400 Lumens
COLOR TEMP	5000K	5000K
POWER CONSUMPTION	90W	135W
CRI	70	70
REPLACES	320W MH	400W MH
PRICE		



UL LISTING

UL listed for wet location.

DESIGNLIGHTS CONSORTIUM

DLC qualified at 4000K and 5000K.

LEDs

LM-80 certified high performance and reliable lumileds LEDs.

VOLTAGE

Voltage is 120-277V/347V

HOUSING AND FINISH

Die-cast aluminum with durable dark bronze coat finish.

INSTALLATION

Junction box or wall mounted directly.

AMBIENT TEMPERATURE

Suitable for use in -40 C to 40 C.

WARRANTY

5 years limited warranty.

Full Cutoff LED Wall Pack (MWP02)

Up to 7,350 + Lumens

Medium Full Cutoff Wall Pack **45W&70W**
Dimensions:14.212x9.251x8.779in.



Up to 14,000 + Lumens

Large Full Cutoff Wall Pack **90W&135W**
Dimensions:18.098x10.81x9.75in.



ENHANCED LED PERFORMANCE IN A CLASSIC DESIGN

The LED wallpacks offer maximum light output for general purpose area and security lighting. They efficiently deliver lumens, and consume less energy than traditional wallpack MH technologies. This versatile luminaire is ideal for replacing existing MH fixtures. Applications: Security, pathway and perimeter lighting, Building entryways and walkways.

MEDIUM FULL CUTOFF WALL PACK

SKU	WPF45W27V50KD	WPF70W27V50KD
LIGHT OUTPUT	4,900 Lumens	7,350 Lumens
COLOR TEMP	5000K	5000K
POWER CONSUMPTION	45W	70W
CRI	82	82
REPLACES	175W MH	250W MH
PRICE		

LARGE FULL CUTOFF WALL PACK

SKU	WPF90W27V50KD	WPF135W27V50KD
LIGHT OUTPUT	9,500 Lumens	14,000 Lumens
COLOR TEMP	5000K	5000K
POWER CONSUMPTION	90W	135W
CRI	82	82
REPLACES	320W MH	400W MH
PRICE		

UL LISTING

UL listed for wet location.

DESIGNLIGHTS CONSORTIUM

DLC qualified at 4000K and 5000K.

LEDs

LM-80 certified high performance and reliable lumileds LEDs.

VOLTAGE

Voltage is 120-277V/347V

HOUSING AND FINISH

Die-cast aluminum with durable dark bronze coat finish.

INSTALLATION

Junction box or wall mounted directly.

AMBIENT TEMPERATURE

Suitable for use in -40 C to 50 C.

WARRANTY

5 years limited warranty.



Accessories



Photocell - Button, 120V/120-277V

USE: Photocell is field installed
or Pre-installed in factory by requesting