

DATE: 10/07/2021

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 5

BID NO.: 50-00136115

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETNA, LA. 70054-0009
504-364-2678

VENDOR:

BUYER: MBUTTERY

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH	
INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES	_____ N/A _____
INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK	_____ N/A _____
INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK	_____ N/A _____

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form by placing the addendum number as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: N/A

NUMBER: _____

NUMBER: _____

NUMBER: _____

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) N/A

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***	
FIRM NAME: The McPherson Companies, Inc.	
SIGNATURE: (Must be signed here)	TITLE: Government & Municipal Sales Contract Manager
PRINT OR TYPE NAME: Ryan Harrison	
ADDRESS: 5051 Cardinal Street	
CITY, STATE: Trussville, AL	ZIP: 35173
TELEPHONE: (205) 308-3028	FAX: (205) 661-4597
EMAIL ADDRESS: lubeorders@mcphersonoil.com (ordering) / rharrison@mcphersonoil.com	



TOTAL PRICE OF ALL BID ITEMS: \$ 1,656.00

RH

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00136115

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	600.00	EA	<p>One Time Purchase of Lithium Grease for the Public Works Eastbank Warehouse</p>		
			<p>0001 - Grease, lithium complex, multi-purpose, 14 ounce cartridge, extreme pressure, high temperature, base oil viscosity 220 at 40 degrees C and 18.3 at 100 degrees C, Albida EP no. 2, Shell no. S3 V220C 2 Mag1#00723 (0017010)</p> <p>Please have items shipped to:</p> <p>Eastbank Warehouse 4901 Jefferson Hwy Suite C Jefferson, LA 70121</p>	<p>Protect Tacky Red Tubes (SEE SPECS) ((10tubes)x(5)/Case) (50 Tubes/Case)</p> <p>\$2.76/Tube</p>	<p>\$1,656.00</p> <p>12 Cases</p>

PROTECK™

Lubricants

Proteck Tacky Red



PROTECK TACKY RED GREASE

DESCRIPTION: Proteck Tacky Red Grease is a red multipurpose tacky lithium complex grease. Made from highly refined base oils, Proteck Tacky Red Grease is fortified with specialty additives that allow it to meet a wide range of applications. Proteck Tacky Red is formulated with rust and corrosion inhibitors, designed to give your equipment the highest levels of protection over a wide temperature range of 0 oF to 350 oF.

APPLICATIONS: Recommended for extended service in heavy duty automotive, trucks and construction equipment. Good for wheel bearings, universal joints, chassis and fifth wheel; NLGI Rating GC-LB.

FEATURES:

BENEFITS:

Excellent oxidation and corrosion protection	Increase life of steel and copper alloy bearings
Good EP properties	Increase wear protection
Exhibits good water resistance	Allows all weather use
Good low temperature pumpability	Allows use year round.

TYPICAL SPECIFICATIONS:

SPECIFICATIONS	TEST METHOD	PROTECK TACKY RED
NL GI Grade		2
Thickener		Lithium Complex
Texture		Smooth and Tacky
Color		RED
Base Oil Viscosity @40oC	ASTM D 445	224
Base Oil Viscosity @100oC	ASTM D 445	17.4
Drop Point, oF	ASTM D 2265	450+
Worked Penetration at 25oC	ASTM D 217	265-295
Oil Separation, 25oC 24 hours in %	ASTM D 1742	1
Timken OK Load lbs	ASTM D 2509	50
Weld Load, kg	ASTM D 2783	315
Wear Scar Diameter, mm	ASTM D 2266	0.6
Water Washout, wt. % Loss@ 175oF	ASTM 1264	10 max
Load Wear Index		50

Health and safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment