



CENTRALBIDDING
FROM CENTRAL AUCTION HOUSE

**5000130136 ONE (1) YEAR CONTRACT FOR 2020 HEAVY DUTY
VEHICLES FOR JEFFERSON PARISH FLEET MANAGEMENT.**
Jefferson Parish Government

Project documents obtained from www.CentralBidding.com
20-Apr-2020 02:42:40 PM



Bid Number 50 - 130136

**ONE (1) YEAR CONTRACT FOR 2020 HEAVY DUTY VEHICLES FOR
JEFFERSON PARISH DEPARTMENT OF FLEET MANAGEMENT.**

MARCH 26, 2020 AT 2:00 PM

ATTENTION VENDORS!!!

**Please review all pages and respond accordingly, complying with all provisions
in the technical specifications and Jefferson Parish Instructions for Bidders and
General Terms and Conditions. All bids must be received in the Purchasing
Department by the bid due date and time.**

**Jefferson Parish Purchasing Department
200 Derbigny Street
General Government Building, Suite 4400
Gretna, LA 70053
Donna Reamey
Dreamey@Jeffparish.net
504-364-2684**

SPECIFICATIONS

Contract for Model Year 2020 Heavy Duty Vehicles for Jefferson Parish Department of Fleet Management

Louisiana State Dealer's License:

In accordance with LA RS 32:1254 et seq and LA RS 38:2212.8, a Louisiana State Dealers License is required. **All bidders must provide a copy of their Louisiana Dealer's License with their bid submission. Failure to submit this copy shall result in bid rejection.**

Order Placement and Delivery of New Vehicles:

Upon order placement approved by Fleet Management, the successful vendor shall deliver vehicles within 220 days of order placement. All vehicles shall be delivered with four (4) sets of keys.

Color of Vehicles (Exterior and Interior):

Exterior: Vehicles must be delivered in either white or red as specified by Fleet Management upon order placement.

Interior: Jefferson Parish will accept any available interior color, however this will be subject to approval by Jefferson Parish Fleet Management.

Servicing of Vehicles:

Successful vendor must pick up and/or deliver vehicles for factory maintenance and/or warranty services within twenty-four (24) hours of notification by the Jefferson Parish Fleet Management Department. The vehicles will be picked up and delivered to 4901 Jefferson Hwy., Suite A, Jefferson, LA 70121.

Brand Names:

Where brand names are specified, it is for the purpose of establishing minimum standard of quality. Bids may be submitted for products for equal quality, provided the brand names are specified in the respective line items as indicated. Complete equivalent product data will be required **with** bid submission. **Failure to provide this documentation will result in bid rejection.**

Pricing:

All pricing shall be firm until end of the 2020 model year or until contract expiration whichever is later. All pricing for dealer options must be invoiced at manufacturer's cost. **Bidders must submit complete manufacturer's cost list with bid submission. Failure to submit will result in bid rejection.**

Vehicle Warranty Information:

All new vehicles must be delivered complete with standard factory warranty. **Warranty period (years/mileage) must be provided with bid submission. Failure to submit will result in bid rejection.**

Insurance:

The bidder (contractor) will be responsible for maintaining all insurance coverages as required by the laws of the State of Louisiana and Jefferson Parish requirements. The bidder (contractor) **must** submit all current insurance certificates **with** the bid submission. Bidder must also comply with the insurance requirement as described in Jefferson Parish resolution No. 113646 in regards to general liability and auto insurance. **In addition, the vendor must supply proof of garage liability insurance. Failure to comply will cause your bid to be rejected.**

Vehicle Manuals:

Upon delivery of new vehicles, the successful vendor must provide (2) sets of manuals as indicated by each appropriate line item. Electronic copies of these manuals may be supplied at the successful vendor's cost.

Safety Specifications for All Vehicles:

Must meet or exceed all federal and state safety standards.

DATE: 3/11/2020
BID NO.: 50-00130136

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 1

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETN, LA. 70054-0009
504-364-2678

BUYER: DREAMEY@jeffparish.net

BIDS WILL BE RECEIVED IN THE WEST BANK PURCHASING DEPT, SUITE 4400, JEFFERSON PARISH GENERAL GOVERNMENT BUILDING, 200 DERBIGNY STREET, GRETN, LA 70053 UNTIL 2:00 PM, 3/26/2020 AND PUBLICLY OPENED THEREAFTER.

For convenience, bidders may also submit bids in the East Bank Purchasing Department, Suite 404, Jefferson Parish Joseph S. Yenni Building, 1221 Elmwood Park Blvd., Jefferson LA 70123. However, if submitting bids on the day of bid opening, bidders must submit at the West Bank location only. All bids will be publicly opened at the West Bank location.

At no charge, bidders may also submit via Jefferson Parish's electronic procurement page by visiting www.jeffparishbids.net to register for this free site. Additional instructions are included in the text box highlighting electronic procurement.

LATE BIDS WILL NOT BE ACCEPTED

Unless submitting via online (see Page 3), each bid must be submitted in a sealed envelope bearing on the outside; the name of the Bidder, his address, and the name of the project for which the bid is submitted and the bid number.

NOTE: ONLY BIDS WRITTEN IN INK OR TYPEWRITTEN, AND PROPERLY SIGNED BY A MEMBER OF THE FIRM OR AUTHORIZED REPRESENTATIVE, WILL BE ACCEPTED. PENCIL AND/OR PHOTOSTATIC FIGURES OR SIGNATURES SHALL RESULT IN BID REJECTION.

INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

THE FOLLOWING INSTRUCTIONS APPLY TO ALL BIDS

All bids submitted are subject to these instructions and general conditions and any special conditions and specifications contained herein, all of which are made part of this bid proposal reference. By submitting a bid, vendor agrees to comply with all provisions of Louisiana Law as well be in compliance with the Jefferson Parish Code of Ordinances, Louisiana Code of Ethics, applicable Jefferson Parish ethical standards and Jefferson Parish Resolution No. 113646 and/or Resolution No. 113647.

Jefferson Parish adheres to the Louisiana Code of Governmental Ethics, contained in Louisiana Revised Statutes Annotated, R.S. 42:1101, et seq. Vendor/Proposer by this submission, warrants that there are no "conflicts of interest" related to this procurement that would violate applicable Louisiana Law. Violation of the Louisiana Code of Governmental Ethics may result in rescission of contract, permit or licenses, and the imposition of fines and/or penalties, without contractual liability to the public in accordance with applicable law.

All vendors submitting bids should register as a Jefferson Parish vendor if not already yet registered. Registration forms may be downloaded from <http://purchasing.jeffparish.net> and by clicking on Vendor Information. Current W-9 forms with respective Tax Identification numbers and vendor applications may be submitted at any time; however, if your company is not registered and/or a current W-9 form is not on file, vendor registration is mandatory. Vendors may experience a delay in payment if your company is not a registered vendor with Jefferson Parish.

All quotations shall be based on F.O.B. Agency warehouse or job site, anywhere within the Parish as designated by the Purchasing Department. This provision does not apply to public works projects

JEFFERSON PARISH requires all products to be new (current) and all work must be performed according to standard practices for the project. Unless otherwise specified, no aftermarket parts will be accepted. Unless otherwise specified, all workmanship and materials must have at least one (1) year guaranty, in writing, from the date of delivery and/or acceptance of the project. Any deviations or alterations from the specifications must be indicated and/or supporting documentation supplied with bid submission.

Bidders should submit all questions in writing via email to the buyer's email address as indicated above, no later than Five (5) working days prior to the bid opening. Bid numbers should be mentioned in all requests. If submitting online, vendors may send questions via the E-Procurement site no later than Five (5) working days prior to the bid opening.

If this bid requires a pre-bid conference (see Additional Requirements section), bidders are advised that such conference will be held to allow bidders the opportunity to identify any discrepancies in the bid specifications and seek further clarification regarding instructions. The Purchasing Department will issue a written response to bidders' questions in the form of an Addendum. Please note that all official communication will be expressed in the form of an addendum.

All formal Addenda require written acknowledgement on the bid form by the bidder. Failure to acknowledge an Addendum on the bid form shall cause the bid to be rejected. JEFFERSON PARISH reserves the right to award bid to next lowest responsive and responsible bidder in this event.

JEFFERSON PARISH will accept one price for each item unless otherwise indicated. Two or more prices for one item will result in bid rejection. Bidders are required to complete, sign and return the bid form and/or complete and return the associated line item pricing forms as indicated. Vendors must not alter the bid forms. Doing so will cause the bid to be rejected.

A corporate resolution or written evidence of the individual signing the bid having such authority must be submitted with the bid. Failure to comply will cause bid to be rejected. For corporate entities, such written evidence may be a printout of the Louisiana Secretary of State's website listing the signatory as an officer. Such printout shall be included with the bid submission. Bids submitted by Owners or Sole Proprietorships must include certification that he or she owns the entity for which the bid is signed. This documentation must be submitted with the bid. Failure to do so will result in bid rejection.

NOTE: A sample corporate resolution can be downloaded from our website <http://purchasing.jeffparish.net> or you may provide your own document. A sample certification of sole proprietorship can also be downloaded from our website <http://purchasing.jeffparish.net> or you may provide your own document.

INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

A. AWARD OF CONTRACT: JEFFERSON PARISH reserves the right to award contracts or place orders on a lump sum or individual item basis, or such combination, as shall in its judgment be in the best interest of JEFFERSON PARISH. Every contract or order shall be awarded to the LOWEST RESPONSIVE and RESPONSIBLE BIDDER, taking into consideration the CONFORMITY WITH THE SPECIFICATIONS and the DELIVERY AND/OR COMPLETION DATE. SPLIT AWARDS MADE TO SEVERAL VENDORS WILL ONLY BE GRANTED TO THOSE DEEMED RESPONSIVE AND RESPONSIBLE.

All bid prices shall remain valid for 45 days. Jefferson Parish and the lowest responsive and responsible bidder(s) by mutual written consent may mutually agree to extend the deadline for award by one (1) or more extensions of thirty (30) calendar days.

PROTESTS: Only those vendors that submit bids in response to this solicitation may protest any element of the procurement, in writing to the Director of the Purchasing Department. Written protest must be received within 48 hours of the release of the bid tabulation by the Purchasing Department. After consultation, the Parish Attorney's Office will then respond to protests in writing. (For more information, please see Chapter 2, Article VII, Division 2, Sec. 2-914.1 of the Jefferson Parish Code of Ordinances.)

PREFERENCE: Unless federal funding is directly spent by Jefferson Parish for this purchase, preference is hereby given to materials, supplies, and provisions produced, manufactured or grown in Louisiana, quality being equal to articles offered by competitors outside the state. "LSA – R.S. 38:2251-2261"

B. USE OF BRAND NAMES AND STOCK NUMBERS: Where brand names and stock numbers are specified, it is for the purpose of establishing certain minimum standards of quality. Bids may be submitted for products of equal quality, provided brand names and stock numbers are specified. Complete product data may be required prior to award.

C. CANCELLATION OF CONTRACT: JEFFERSON PARISH reserves the right to cancel all or any part if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel any contract at anytime and for any reason by issuing a THIRTY (30) day written notice to the contractor.

For good cause and as consideration for executing a contract with Jefferson Parish, vendor conveys, sells, assigns and transfers to Jefferson Parish or its assigns all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of Louisiana, relating to the particular good or services purchased or acquired by Jefferson Parish.

D. PRICES: Jefferson Parish is exempt from paying sales tax under LSA-R.S. 47:301 (8)(c). All prices for purchases by Jefferson Parish of supplies and materials shall be quoted in the unit of measure specified and unless otherwise specified, shall be exclusive of state and Parish taxes. The price quoted for work shall be stated in figures. In the event there is a difference in unit prices and totals, the unit price shall prevail.

Quantities listed are for bidding purposes only. Actual requirements may be more or less than quantities listed.

Bidders are not to exclude from participation in, deny the benefits of, or subject to discrimination under any program or activity, any person in the United States on the grounds of race, color, national origin, or sex; nor discriminate on the basis of age under the Age Discrimination Act of 1975, or with respect to an otherwise qualified handicapped individual as provided in Section 504 of the Rehabilitation Act of 1973, or on the basis of religion, except that any exemption from such prohibition against discrimination on the basis of religion as provided in the Civil Rights Act of 1964, or Title VI and VII of the Act of April 11, 1968, shall also apply. This assurance includes compliance with the administrative requirements of the Revenue Sharing final handicapped discrimination provisions contained in Section 51.55 (c), (d), (e), and (k)(5) of the Regulations. New construction or renovation projects must comply with Section 504 of the 1973 Rehabilitation Act, as amended, in accordance with the American National Standard Institute's specifications (ANSI A17.1-1961).

Jefferson Parish and its partners as the recipients of federal funds are fully committed to awarding a contract(s) to firm(s) that will provide high quality services and that are dedicated to diversity and to containing costs. Thus, Jefferson Parish strongly encourages the involvement of minority and/or woman-owned business enterprises (DBE's, including MBE's, WBE's and SBE's) to stimulate participation in procurement and assistance programs.

INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

The purpose and intention of this invitation to bid is to afford all suppliers an equal opportunity to bid on all construction, maintenance, repair, operating supplies and/or equipment listed in this bid proposal. JEFFERSON PARISH WILL ACCEPT ONE BID ONLY FROM EACH VENDOR. Items bid must meet specifications.

Advertised bids will be tabulated and a copy of the tabulation will be forwarded to each responding bidder.

IN ACCORDANCE WITH STATE REGULATIONS JEFFERSON PARISH OFFERS ELECTRONIC PROCUREMENT TO ALL VENDORS

This electronic procurement system allows vendors the convenience of reviewing and submitting bids online. This is a secure site and authorized personnel have limited read access only. Bidders are encouraged to submit electronically using this free service; while the website accepts various file types, one single PDF file containing all appropriate and required bid documents is preferred. Bidders submitting uploaded images of bid responses are solely responsible for clarity. If uploaded images/documents are not legible, then bidder's submission will be rejected. Please note all requirements contained in this bid package for electronic bid submission.

Please visit our E-Procurement Page at www.jeffparishbids.net to register and view Jefferson Parish solicitations. For more information, please visit the Purchasing Department page at <http://purchasing.jeffparish.net>.

The general specifications for construction projects and the purchase of materials, services and/or supplies are those adopted by the JEFFERSON PARISH Council by Resolution No. 113646 or 113647 dated 12/09/09. The general conditions adopted by this resolution shall be considered as much a part of this document as if they were written wholly herein. A copy may be obtained from the Office of the Parish Clerk, Suite 6700, Jefferson Parish General Government Building, 200 Derbigny Street, Gretna, LA 70053. You may also obtain a copy by visiting the Purchasing Department webpage at <http://purchasing.jeffparish.net> and clicking on Online Forms.

ADDITIONAL REQUIREMENTS FOR THIS BID

PLEASE MATCH THE NUMBERS PRINTED IN THIS BOX WITH THE
CORRESPONDING INSTRUCTIONS BELOW.

10,12,13,15

1. All bidders must attend the MANDATORY pre-bid conference and will be required to sign in and out as evidence of attendance. In accordance with LSA R.S. 38:2212(l), all prospective bidders shall be present at the beginning of the MANDATORY pre-bid conference and shall remain in attendance for the duration of the conference. Any prospective bidder who fails to attend the conference or remain for the duration shall be prohibited from submitting a bid for the project.
2. Attendance to this pre-bid conference is optional. However, failure to attend the pre-bid conference shall not relieve the bidder of responsibility for information discussed at the conference. Furthermore, failure to attend the pre-bid conference and inspection does not relieve the successful bidder from the necessity of furnishing materials or performing any work that may be required to complete the work in accordance with the specification with no additional cost to the owner.
3. Contractor must hold current applicable JEFFERSON PARISH licenses with the Department of Inspection and Code Enforcement. Contractor shall obtain any and all permits required by the JEFFERSON PARISH Department of Inspection and Code Enforcement. The contractor shall be responsible for the payment of these permits. All permits must be obtained prior to the start of the project. Contractor must also hold any and all applicable Federal and State licenses. Contractor shall be responsible for the payment of these permits and shall obtain them prior to the start of the project.
4. A LA State Contractor's License will be required in accordance with LSA R.S. 37-2150 et. seq. and such license number will be shown on the outside of the bid envelope. Failure to comply will cause the bid to be rejected. Additionally if submitting the bid electronically, then the license number must be entered in the appropriate field in the Electronic Procurement system. Failure to comply will cause the bid to be rejected.
5. It is the bidder's responsibility to visit the job site and evaluate the job before submitting a bid.
6. Job site must be clean and free of all litter and debris daily and upon completion of the contract. Passageways must be kept clean and free of material, equipment, and debris at all times. Flammable material must be removed from the job site daily because storage will not be permitted on the premises. Precautions must be exercised at all times to safeguard the welfare of JEFFERSON PARISH and the general public.

INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

7. PUBLIC WORKS BIDS: All awards for public works in excess of \$5,000.00 will be reduced to a formal contract which shall be recorded at the contractor's expense with the Clerk of Court and Ex-Officio Recorder of Mortgages for the Parish of Jefferson. A price list of recordation costs may be obtained from the Clerk of Court and Ex-Officio Recorder of Mortgages for the Parish of Jefferson. All awards in excess of \$25,000.00 will require both a performance and a payment bond. Unless otherwise stated in the bid specifications, the performance bond requirements shall be 100% of the contract price. Unless otherwise stated in the bid specifications, the payment bond requirements shall be 100% of the contract price. Both bonds shall be supplied at the signing of the contract.
8. NON-PUBLIC WORKS BIDS: A performance bond will be required for this bid. The amount of the bond will be 100% of the contract price unless otherwise indicated in the specifications. The performance bond shall be supplied at the signing of the contract.
9. NON-PUBLIC WORKS BIDS: A payment bond will be required for this bid. The amount of the bond will be 100% of the contract price unless otherwise indicated in the specifications. The payment bond shall be supplied at the signing of the contract.
10. All bidders must comply with the requirements stated in the attached "Standard Insurance Requirements" sheet attached to this bid solicitation. Failure to comply with this instruction will result in bid rejection.
11. A bid bond will be required with bid submission in the amount of 5% of the total bid, unless otherwise stated in the bid specifications. Acceptable forms shall be limited to cashier's check, certified check, or surety bid bond. All sureties must be in original format (no copies). If submitting a bid online, vendors must submit an electronic bid bond through the respective online clearinghouse bond management system(s) as indicated in the electronic bid solicitation on Central Auction House. No scanned paper copies of any bid bond will be accepted as part of the electronic bid submission.
12. This is a requirements contract to be provided on an as needed basis. JEFFERSON PARISH makes no representations or warranties with regard to minimum guaranteed quantities unless otherwise stated in the bid specifications.
13. Freight charges should be included in total cost when quoting. If not quoted FOB DELIVERED, freight must be quoted as a separate item. Bid may be rejected if not quoted FOB DELIVERED or if freight charges are not indicated on bid form.
14. PUBLIC WORKS BIDS - Completed, Signed and Properly Notarized Affidavits Required; This applies to all solicitations for construction, alteration or demolition of public buildings or projects, in conformity with the provisions contained in LSA-RS 38:2212.9, LSA-RS 38:2212.10, LSA-RS 38:2224, and Sec 2-923.1 of the Jefferson Parish Code of Ordinances. For bidding purposes, all bidders must submit with bid submission COMPLETED, SIGNED and PROPERLY NOTARIZED Affidavits, including: Non-Collusion Affidavit, Non-Collusion Affidavit, Campaign Contribution Affidavit, Debt Disclosures Affidavit and E-Verify Affidavit. For the convenience of vendors, all affidavits have been combined into one form entitled PUBLIC WORKS BID AFFIDAVIT. This affidavit must be submitted in its original format, and without material alteration, in order to be compliant and for the bid to be considered responsive. A scanned copy of the completed, signed and properly notarized affidavit may be submitted with the bid, however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.
15. NON PUBLIC WORK BIDS - Completed, Signed and Properly Notarized Affidavits Required in conformity with the provisions contained in LSA - RS 38:2224 and Sec 2-923.1 of the Jefferson Parish Code of Ordinances. For bidding purposes, all bidders must submit with bid submission COMPLETED, SIGNED and PROPERLY NOTARIZED Affidavits, including: Non-Collusion Affidavit, Debt Disclosures Affidavit and Campaign Contribution Affidavit. For the convenience of vendors, all affidavits have been combined into one form entitled NON PUBLIC WORKS BID AFFIDAVIT. This affidavit must be submitted in its original format, and without material alteration, in order to be compliant and for the bid to be considered responsive. A scanned copy of the completed, signed and properly notarized affidavit may be submitted with the bid, however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.
16. The ensuing contract for this bid solicitation may be eligible for FEMA reimbursement and/or Federal funding/reimbursement. As such, the referenced appendix will be applicable accordingly and shall be considered a part of the bid documents. All applicable certifications must be duly completed, signed and submitted with bid submission. Failure to submit applicable certifications with bid submission will result in bid rejection.
17. For this project, the Contractor shall not pay any state or local sales or use taxes on materials and equipment which are affixed and made part of the immovable property of the project or which permanently incorporated in the project (hereinafter referred to as "applicable materials and equipment"). All purchases of applicable materials or equipment shall be made by the contractor on behalf of and as the agent of Jefferson Parish (Owner), a political subdivision of the State of Louisiana. No state and local sales and use taxes are owed on applicable materials and equipment under the provisions of Act 1029 of the 1991 Regular Session - Louisiana Revised Statute 47:301(8)(c). Owner will furnish contractor a certificate form which certifies that Owner is not required to pay such state or local sales and use taxes, and contractor shall furnish a copy of such certificate to all vendors or suppliers of the applicable materials and equipment.

It shall be the duty of every parish officer, employee, department, agency, special district, board, and commission; and the duty of every contractor, subcontractor, and licensee of the parish, and the duty of every applicant for certification of eligibility for a parish contract or program, to cooperate with the Inspector General in any investigation, audit, inspection, performance review, or hearing pursuant to JPCO 2-155.10(19). By signing this document, every corporation, partnership, or person contracting with PARISH, whether by cooperative endeavor, intergovernmental agreement, bid, proposal, application or solicitation for a parish contract, and every application for certification of eligibility for a parish contract or program, attests that it understands and will abide by all provisions of JPCO 2-155.10.

DATE: 3/11/2020

Page: 5

BID NO.: 50-00130136

BID FORM
Non Public Works

All Public Work Projects are required to use the Louisiana Uniform Public Work Bid Form

All prices must be held firm unless an escalation provision is requested in this bid. Jefferson Parish will allow one escalation during the term of the contract, which may not exceed the U.S. Bureau of Labor Statistics National Index for all Urban Consumers, unadjusted 12 month figure. The most recently published figure issued at the time an adjustment is requested will be used. A request must be made in writing by the vendor, and the escalation will only be applied to purchases made after the request is made.

Are you requesting an escalation provision?

YES _____ NO X _____

MAXIMUM ESCALATION PERCENTAGE REQUESTED _____%

INITIAL BID PRICES WILL REMAIN FIRM THROUGH THE DATE OF _____

For the purposes of comparison of bids when an escalation provision is requested, Jefferson Parish will apply the maximum escalation percentage quoted by the bidder to the period to which it is applied in the bid. The initial price and the escalation will be used to calculate the total bid price. It will be assumed, for comparison of prices only, that an equal amount of material or labor is purchased each month throughout the entire contract.

DELIVERY: FOB JEFFERSON PARISH

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

120 Days ARO

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

THIS SECTION MUST BE COMPLETED BY BIDDER:

FIRM NAME: iTA Truck Sales & Service, LLC

ADDRESS: 2835 NW Evangeline Thwy.

CITY, STATE: Lafayette, LA

ZIP: 70507

TELEPHONE: (337) 234.9425

FAX: (337) 234.4814

EMAIL ADDRESS: bspringer@ita-trucks.com

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: 1

NUMBER: 2

NUMBER: _____

NUMBER: _____

TOTAL PRICE OF ALL BID ITEMS: \$ 1,036,309.00

AUTHORIZED

SIGNATURE: 

Ben Springer

Printed Name

TITLE: Marketing Manager

SIGNING INDICATES YOU HAVE READ AND COMPLY WITH THE INSTRUCTIONS AND CONDITIONS.

NOTE: All bids should be returned with the BID NUMBER and BID OPENING DATE indicated on the outside of the envelope submitted to the Purchasing Department.

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	2.00	EA	<p>ONE (1) YEAR CONTRACT FOR 2020 HEAVY DUTY VEHICLES FOR JEFFERSON PARISH FLEET MANAGEMENT.</p> <p>0001 - 2020 52,000 GVWR HEAVY DUTY CAB AND CHASSIS</p> <p>GVW: 52,000 LBS. CA 108 IN. ENGINE-DIESEL-12.8 380 HD OR EQUAL HP 380 MIN TORQUE 1350 LB. FT C.I.D. 12.8L AIR FILTER-DRY TYPE PAPER ELEMENT SINGLE EXHAUST-HORIZONTAL MUFFLER WITH VERTICAL STACK. 12 VOLT STARTER OIL FILTER-FULL FLOW FUEL/WATER SEPARATOR ** AUTOMATIC TRANSMISSION** REAR AXLE ROCKWELL RT 40-145 40,000 LBS.</p> <p>TOP SPEED: 60 MPH FRONT AXLE: 12,000 LBS FRONT SUSPENSION: 12,000 LBS. REAR SUSPENSION: 40,000 LBS. HENDRICKSON BRAKES-FULL AIR FRONT CAM-16.5 IN X 7.0 IN. AIR COMPRESSOR-MIN 13.2 CFM AIR DRYER BENDIX AD-9 HEATED AUTOMATIC SLACK ADJUSTERS AUTOMATIC MOISTURE ADJUSTER ON WET TANK FRAME: 30.0SM 110,000 PSI DOUBLE CHANNEL BOLTED DUAL AIR HORNS HOOD AND FENDER ASSEMBLY TILT TYPE INTEGRAL POWER STEERING PINTLE HITCH-HOLLAND PHT 750 PINTLE HITCH PROVIDED WITH FULL REINFORCEMENT TO TRUCK MOUNTED AT PROPER HEIGHT TO MATCH TRAILER. TOW HOOKS-HEAVY DUTY REAR TWO HOOKS MOUNTED ON THE OUTSIDE OF FRAME WITH CASE HARDENED BOLTS. ELECTRICAL-ALTERNATOR 90 AMPS BATTERIES MIN. NO. 2 TOTAL CCA 1850 EMERGENCY FLASHERS 5 CAB LIGHTS HALOGEN HEADLIGHTS TURN SIGNAL-STANDARD TAIL LIGHTS-TWO WITH INTERGRAL STOP/TURN TWO REVERSE LIGHTS BACKUP ALARM-ELECTRIC CIRCUIT PROTECTORS REAR CLEARANCE LIGHTS TRIO BAR FUEL TANK-IN STEP TYPE 45 GAL CAPACITY TIRES-11 R22.5 HIGHWAY TREAD FRONT MUD REAR WITH SPARE. CAB-STANDARD TRIM SUN VISOR-LEFT AND RIGHT SEAT IN VINYL-MID BACK DRIVERS WITH TWO MAN PASSENGER SEAT SAFETY BELTS.</p>	\$85,231.00	\$170,462.00

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
2	1.00	EA	RADIO-AM/FM INSTRUMENTATION-AIR CLEANER RESTRICTION INDICATOR PARKING BRAKE CONTROL-DASH MOUNTED SPEEDOMETER MPH/KMH WITH ODOMETER WARNING LIGHTS: AMPS, FUEL WARNING LIGHT WATER IN FUEL LIGHT, LOW OIL PRESSURE, LOW COOLANT LEVEL, HIGH COOLANT TEMP BUZZERS: AIR PRESSURE GAUGES: VOLTOMETER OR AMMETER, OIL PRESSURE, WATER TEMPERATURE, FUEL, AIR PRESSURE. TACHOMETER CAB EXTERIOR: WEST COAST MIRRORS 7 IN. X 16 IN. WITH 5 IN ROUND CONVEX MIRROR MOUNTED BELOW WINDSHIELD-TINTED WINDSHIELD WIPERS-2 SPEED, INTERMITTENT WITH WASHER. WHEELS-22.5 X 8.25 TO HOLE STEEL DISC ISO HUB PILOT MOUNTED TRAILER PACKAGE WITH AIR AND ELECTRIC CONNECTION (7 PIN TRAILER PLUG) TO REAR OF FRAME SERVICE ABILITY-VEHICLE TO BE DELIVERED COMPLETELY SERVICED AND IN READY TO WORK CONDITION. AC FACTORY INSTALLED 2 SERVICE MANUALS 2 PARTS MANUALS 2 WIRING DIAGRAMS IF MFG. STILL PROVIDES, IF NO MANAUL OR DIAGRAM, CD'S WILL BE ACCEPTED. 2 UNIT OVERHAUL MANUALS 4 SETS OF KEYS ALL STANDARD FACTORY EQUIPMENT		
			0002 - 2020 25,000 LB/29,000 LBS. CAB AND CHASSIS GVW: 25,000 LBS. CA:108 IN. ENGINE:6.7 LITER V8 DIESEL H.P.: 220 AT 2300 RPM 8 CYLINDER TURBO AND AIR TO AIR AFTER COOLER. MIN TORQUE: 520 FT. LBS. AIR FILTER: DRY TYPE PAPER ELEMENT HORIZONTAL MUFFLER WITH VERTICAL STACK. 12 V STARTER OIL FILTERS: FULL FLOW FUEL/WATER SEPARATOR ENGINE OIL COOLER ENGINE COOLANT FILTER/CONDITIONER TRANSMISSION: FORD 6R140 6 SPPED **AUTOMATIC TRANSMISSION** REAR AXLE: SINGLE SPEED FRONT SUSPENSION: 8,000 LBS. CAPACITY REAR SUSPENSION: 15,5000 LBS. CAPACITY AUXILLARY SPRINGS: 4,500 LBS BRAKES: FULL AIR, AIR PARKING BRAKES SPRING SET TYPE WITH DASH MOUNTED CTRL	\$53,819.00	\$53,819.00

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
			AIR COMPRESSOR: MIN. 12 CFM AIR DRYER: BENDIX-WESTINGHOUSE AD-9 HEATED AUTOMATIC SLACK ADJUSTERS AUTOMATIC MOISTURE EJECTOR ON WET TANK DRIVESHAFT: SPICER U-JOINTS 1610 H.D. FRAME: SINGLE CHANNEL FRAME 14.2 MIN SECTION MODULUS 12.64 SM HORN: SINGLE ONLY AVAILABLE HOOD AND FENDER ASSEMBLY-TILT TYPE INTEGRAL POWER STEERING TIRES-10R22.5 HIGHWAY TREAR IONING ELECTRICAL: ALTERNATOR-85 AMPS BATTERIES: MIN. NO. 2 TOTAL CCA 1800 EMERGENCY FLASHERS CAB LIGHTS-5 HEAD LIGHT-HOLOGEN TURN SIGNALS-STANDARD TAIL LIGHTS-TWO WITH INTEFRAL STOP-RUN REVERSE LIGHT-2 BACK UP CAMERA CIRCUIT PROTECTORS FUEL TANK-STEP TYPE-MIN. 45 GALLON TIRES-10R22.5 HIGHWAY TREAT FRONT MUD AND SNOW REAR SPARE-WHEEL CAB-STANDARD TRIM CAB INTERIOR-VINYL FLOOR COVERING-NO CARPET HEATER SUN VISORS-LEFT AND RIGHT SEAT BELTS RADIO-AM/FM INSTRUMENT PANEL: AIR CLEANER RESTRICTION INDICATOR MOUNTED ON DASH PARKING BRAKE CONTROL-DASH MOUNTED SPEEDOMETER-MPH/KHM WITH ODOMETER WARNING LIGHTS: LOW OIL PRESSURE LOW COOLANT LEVEL, HIGH COOLANT TEMPERATURE, FUEL WARNING LIGHT, WATER IN FUEL WARNING LIGHT BUZZERS: LOW AIR PRESSURE GAUGES: VOLTMETER OR AMPMETER OIL PRESSURE TEMPERATURE FUEL AIR PRESSURE TACHOMETER WINDSHIELD WIPERS-2 SPEED INTERMITTENT WITH WASHER WHEELS-22.5 X 7.5 HOLE 10 STEEL DISC. ISO HUB PILOT MOUNTED ALL STANDARD FACTORY EQUIPMENT TO MEET STATE AND FEDERAL STANDARDS. 2 SERVICE MANUALS 2 PARTS MANUALS 2 WIRING DIAGRAMS IF MFG. STILL PROVIDES, IF NO MANUAL OR DIAGRAMS-CD'S WILL BE ACCEPTED. 4 SETS OF KEYS.		
3	4.00	EA	0003 - 2020 33,000 LB/37,000 LB. CAB AND CHASSIS	\$57,229.00	\$228,916.00

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
			GVW: 33,000 LBS. CA 84 INCHES ENGINE-6.7L V8 TURBO CHARGE H.P.-250 AT 2300 RPM TURBO WITH AIR AFTER COOLER MIN TORQUE-660 LBS. AIR FILTER-DRY TYPE PAPER ELEMENT SINGLE EXHAUST-VERTICAL WITH RAIN CAP 12 VOLT STARTER OIL FILTER-FULL FLOW FUEL WATER SEPARATOR ENGINE OIL COOLER ENGINE COOLANT FILTER/CONDITIONER WATER CONDITIONER NOT REQUIRED TRANSMISSION-FORD 6R140 6 SPEED ** AUTOMATIC TRANSMISSION** AUTOMATIC WITH PTO PROVISION REAR AXLE-12,000 LB. GVW FRONT SUSPENSION-12,000 LB. CAPACITY REAR SUSPENSION -21,000 LB. CAPACITY AUXILLARY SPRINGS-4,500 LBS. BRAKES-FULL AIR FRONT CAM-15 IN X 4 IN REAR CAM-16.5 IN X 7 IN AIR PARKING BRAKES-SPRING SET TYPE WITH DASH MOUNTED CONTROLS AIR COMPRESSOR-MIN. 15.5 CFM AIR DRYER-BENDIX WESTINGHOUSE AD-9 HEATED AUTOMATIC SLACK ADJUSTERS AUTOMATIC MOISTURE EJECTOR ON WET TANK DRIVESHAFT-SPICER U-JOINTS 1610 H.D. SPICER 1710-MERITOR 12T FRAME-14.18 SM AND 120,000 PSI 15.48 SECTION MODULAR 120,000 PSI HOOD AND FENDER ASSEMBLY-TILT TYPE ELECTRICAL-ALTERNATOR-13 AMPS BATTERIES-MIN NO. 2 TOTAL CCA 1800 EMERGENCY FLASHERS FIVE CAB LIGHTS HALOGEN HEADLIGHTS HORN-DUAL AIR TURN SIGNALS-STANDARD TWO RESERVE LIGHTS CIRCUIT PROTECTORS FUEL TANK-LH STEP TYPE-50 GALLON ALUMINUM-STEEL TIRES-11R22.5 HIGHWAY TREAD FRONT MUD AND SNOW REAR SPARE-WHEEL CAB-STANDARD TRIM CAB INTERIOR-HEATER LEFT AND RIGHT SUN VISORS VINYL FLOOR COVERING-NO CARPET SEATS IN VINYL, MID-BACK DRIVERS WITH TWO PASSENGER SEAT BELTS RADIO-AM/FM INSTRUMENTATION- AIR CLEANING WARNING LIGHT ON DASH RESTRICTION INDICATOR AND PARKING BRAKE CONTROL DASH MOUNTED, SPEEDOMETER MPH/		

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
4	8.00	EA	KMH WITH ODOMETER. TURN SIGNAL SWITCH, BACK-UP CAMERA, WARNING LIGHTS- LOW OIL PRESSURE, LOW COOLANT LEVEL, HIGH COOLANT TEMPERATURE, FUEL WARNING LIGHT, WATER IN FUEL WARNING LIGHT. BUZZER: LOW AIR PRESSURE GAUGES-VOLTMETER OR AMPMETER OIL PRESSURE, TEMPERATURE, FUEL, AIR PRESSURE, TACHOMETER CAB EXTERIOR-WEST COAST MIRRORS 7 IN X 16 IN. WITH 8 IN. ROUND CONVEX MIRROR MOUNTED BELOW. WINDSHIELD WIPERS-2 SPEED INTERMITTENT WITH WASHER. WHEELS-22.5 X 8.25 10 HOLE STEEL DISC. ISO HUB PILOT MOUNTED SEVEN WIRE TRAILER CONNECTORS IN REAR OF TRUCK. BRAKE CONTROLLERS MOUNTED IN TRUCK TO CONTROL TRAILERS WITH ELECTRICAL BRAKES. PINTLE HOOK-HOLLAND PH-T125A 30,000 LB. GROSS TRAILER WEIGHT 6,000 LB. VERTICAL SPRING LOADED PIVOT MOUNTED TO FRAME. AC-FACTORY INSTALLED 2 SERVICE MANUALS 2 PARTS MANUALS 2 WIRING DIAGRAMS IF MFG. STILL PROVIDES, IF NO MANUAL OR DIAGRAM, CD'S WILL BE ACCEPTED. 2 UNIT OVERHAUL MANUALS 4 SETS OF KEYS ALL STANDARD FACTORY EQUIPMENT SERVICE ABILITY-TRUCK TO BE DELIVERED COMPLETELY SERVICED AND IN READY TO WORK CONDITION. ALL SAFETY AND FEDERAL STANDARDS MUST BE MET.		
			0004 - 2020 52,000 GVWR CAB AND CHASSIS GVW: 52,000 LBS. CA 108 IN. ENGINE-MINIMUM STANDARD ENGINE C.I.D.-9 LITERS H.P-300 MIN. TORQUE-860 LBS. FT. TORQUE AIR FILTER-DRY TYPE PAPER ELEMENT SINGLE EXHAUST-HORIZONTAL MUFFLER VERTICAL STACK 12 VOLT STARTER OIL FLOW-FULL FLOW FUEL.WATER SEPARATOR ENGINE OIL COOLER FILTER/CONDITIONER TRANSMISSION-AUTOMATIC ALLISON WITH PTO NEW WORLD CURRENT YEAR MODEL MD 35600 6 SPEED REAR AXLE-ROCKWELL RT 40-145 STEEL 40,000 LBS. TOP SPEED: 60 MPH FRONT AXLE-12,000 LB. CAPACITY	\$72,889.00	\$583,112.00

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
			REAR SUSPENSION-40,000 LBS HENDRICKSON SUSPENSION BRAKES-FULL AIR FRONT CAM-16.5 IN X 5.0 IN. REAR CAM-16.5 IN X 7 IN. AIR PARKING BRAKES, SPRINT SET TYPE WITH DASH MOUNTED CONTROL AIR COMPRESSOR-MIN. 13.2 CFM WATER COOLED. AIR DRYER-BENDIX-WESTINGHOUSE AD-9 HEATED AUTOMATIC SLACK ADJUSTERS AUTOMATIC MOISTURE EJECTOR ON WET TANK DRIVESHAFT-SPICER-U-JOINTS 1710 H.D. FRAME-13.72 SM 110,000 PSI DOUBLE CHANNEL BOLTED. DUAL AIR HORN. HOOD AND FENDER ASSEMBLY-TILT TYPE INTEGRAL POWER STEERING PINTLE HITCH-HOLLAND PHT 760 PINTLE HITCH PROVIDED WITH FULL REINFORCED ELEMENTS TO TRUCK FRAME AND MOUNTED AT PROPER HEIGHT TO MATCH TRAILER. TOW HOOKS-HEAVY DUTY REAR TOW HOOKS MOUNTED ON THE OUSIDE OF FRAME WITH CASE HARDENED BOLTS. ELECTRICAL-ALTERNATOR-90 AMPS BATTERIES-MIN. NO 2 TOTAL CCA 1850 EMERGENCY FLASHERS FIVE CAB LIGHTS HALOGEN HEADLIGHTS TURN SIGNAL-STANDARD TAIL LIGHTS-TWO WITH INTEGRAL STOP/TURN TWO REVERSE LIGHTS BACK-UP ALARM-CAMERA TYPE CIRCUIT PROTECTORS REAR CLEARENCE LIGHT TRIO BAR FUEL TANK-LH STEP TYPE-45 GALLON TIRES-11 R22.5 HIGHWAY TREAD FRONT MUD AND SNOW REAR SPARE-WHEEL CAB-STANDARD TRIM CAB INTERIOR-HEATER SUN VISORS-LEFT AND RIGHT VINYL FLOOR COVERINGS-NO CARPET SEAT IN VINYL-MID-BACK DRIVERS WITH TWO PASSENGERS. SEAT BELTS RADIO-AM/FM INSTRUMENTATION-AIR CLEANER RESTRICTION INDICATOR PARKING BRAKE CONTROLS DASH MOUNTED SPEEDOMETER MPH/KMH WITH ODOMETER WARNING LIGHTS: AMPS FUEL WARNING LIGHT WATER IN FUEL WARNING LIGHT LOW OIL PRESSURE LOW COOLANT LEVEL HIGH COOLANT LEVEL BUZZER: AIR PRESSURE		

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00130136

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
5	25.00	EA	<p>GAUGES- VOLTMETER OR AMPMETER OIL PRESSURE TEMPERATURE FUEL AIR PRESSURE TACHOMETER CAB EXTERIOR-WEST COAST MIRRORS 7 IN X 16 IN WITH 5 IN. ROUND COMPLES MIRRORS MOUNTED BELOW. WINDSHIELD TINTED WINDSHIELD WIPERS-2 SPEED INTERMITTENT WITH WASHER WHEELS-22.5 X 8.25 10 HOLE STEEL DISC. ISO HUB PILOT MOUNTED TRAILER PACKAGE WITH AIR AND ELECTRIC CONNECTION (7 PIN TRAILER PLUG)TO REAR OF FRAME. AC-FACTORY INSTALLED 2 SERVICE MANUALS 2 PARTS MANUALS 2 WIRING DIAGRAMS IF MFG. STILL PROVIDES, IF NO MANUAL OR DIAGRAM, CD'S WILL BE ACCEPTABLE. 2 UNIT OVERHAUL MANUALS 4 SETS OF KEYS ALL STANDARD FACTORY EQUIPMENT SERVICABILITY-VEHICLE WILL BE IN READY TO WORK CONDITION.</p> <p>0005 - OPTIONS SEE PRICING SECTION IN SPECIFICATIONS</p> <p>** DO NOT BID THIS LINE ITEM: THIS WILL BE USED FOR INVOICING AND PAYMENT PURPOSES FOR OPTIONS TO VEHICLES. ALL OPTIONS SHALL BE INVOICED PER THE MANUFACTURER'S COST LIST WHICH MUST BE INCLUDED IN THE BID SUBMISSION.</p> <p>Trucks Meet all Specifications See Options List Attached</p> <p>Service Facility is located at: 301 Hord St. Harahan, LA 70123</p>		

Non-Public Works Bid Affidavit Instructions

- Affidavit is supplied as a courtesy to Affiants, but it is the responsibility of the affiant to insure the affidavit they submit to Jefferson Parish complies, in both form and content, with federal, state and parish laws.
- Affidavit must be signed by an authorized representative of the entity or the affidavit will not be accepted.
- Affidavit must be notarized or the affidavit will not be accepted.
- Notary must sign name, print name, and include bar/notary number, or the affidavit will not be accepted.
- Affiant **MUST** select either A or B when required or the affidavit will not be accepted.
- Affiants who select choice A must include an attachment or the affidavit will not be accepted.
- If both choice A and B are selected, the affidavit will not be accepted.
- Affidavit marked N/A will not be accepted.
- It is the responsibility of the Affiant to submit a new affidavit if any additional campaign contributions are made after the affidavit is executed but prior to the time the council acts on the matter.

Instruction sheet may be omitted when submitting the affidavit

STANDARD INSURANCE REQUIREMENTS FOR BIDDING PURPOSES

All required insurance under this bid shall conform to Jefferson Parish Resolution No. 113646 or No. 113647, as applicable. Contractors may not commence any work under any ensuing contract unless and until all required insurance and associated evidentiary requirements thereto have been met, along with any additional specifications contained in the **Invitation to Bid**. Except as where otherwise precluded by law, the Parish Attorney or his designee, with the concurrence of the Director of Risk Management or his designee, may agree on a case-by-case basis, to deviate from Jefferson Parish's standard insurance requirements, as provided in this Section. Vendors requesting deviation therefrom shall submit such requests in writing, along with compelling substantiation, to the Purchasing Department prior to the bid's due date. Any changes to the insurance requirements will be reflected in the bid specifications and addenda. Prior to contract execution and at all times thereafter during the term of such contract, contractors must provide and continuously maintain all coverages as required by the foregoing Resolutions, and the contract documents. Failure to do so shall be grounds for suspension, discontinuation or termination of the contract.

For bidding purposes, bidders must submit with bid submission a current (valid) insurance certificate evidencing the required coverages. Failure to comply will cause bid to be rejected. The current insurance certificate will be used for proof of insurance at time of evaluation. Thereafter, and prior to contract execution, the low bidder will be required to provide final insurance certificates to the Parish which shall name **the Jefferson Parish, its Districts Departments and Agencies under the direction of the Parish President and the Parish Council** as additional insureds regarding negligence by the contractor for the Commercial General Liability and the Comprehensive Automobile Liability policies. Additionally, said certificates should reflect the name of the Parish Department receiving goods and services and reference the respective Jefferson Parish bid number.

JEFFERSON PARISH REQUIRED STANDARD INSURANCE

☐ WORKER'S COMPENSATION INSURANCE

As required by Louisiana State Statute, exception; Employer's Liability, Section B shall be \$1,000,000 per occurrence when Work is to be over water and involves maritime exposures to cover all employees not covered under the State Worker's Compensation Act, otherwise this limit shall be no less than \$500,000 per occurrence.

Note: If your company is not required by law to carry workmen's compensation insurance, i.e. not a Louisiana company, sole employee of the company, then bidders must request a workmen's compensation insurance declaration affidavit prior to the bid opening date. This insurance declaration affidavit must be fully completed, signed, properly notarized and submitted with the bid. A scanned copy may be submitted with the bid; however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being

rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.

☐ **COMMERCIAL GENERAL LIABILITY**

Shall provide limits not less than the following: \$1,000,000.00 Combined Single Limit per Occurrence for bodily injury and property damage.

☐ **COMPREHENSIVE AUTOMOBILE LIABILITY**

Bodily injury liability \$1,000,000.00 each person; \$1,000,000.00 each occurrence.
Property Damage Liability \$1,000,000.00 each occurrence.

Note: This category may be omitted if bidders do not/will not utilize company vehicles for the project or do not possess company vehicles. Bidder must request an automobile insurance declaration affidavit prior to the bid opening date. This insurance declaration affidavit must be fully completed, signed, properly notarized and submitted with the bid. A scanned copy of the completed, signed and properly notarized affidavit may be submitted with the bid; however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.

DEDUCTIBLES - The Parish Attorney with concurrence of the Director of Risk Management have waived the deductible section of the Terms and Conditions for all Invitations to Bid, until further notice.

UMBRELLA LIABILITY COVERAGE

An umbrella policy or excess may be used to meet minimum requirements.

FOR CONSTRUCTION AND RENOVATION PROJECTS:

The following are required unless otherwise specified in the bid. Such insurance is due upon contract execution.

1) **OWNER'S PROTECTIVE LIABILITY**

To be for the same limits of liability for bodily injury and property damage liability established for commercial general liability.

2) **BUILDER'S RISK INSURANCE**

The contractor shall maintain Builder's Risk Insurance at his own expense to insure both the owner (Parish of Jefferson) and contractor as their interest may appear.



JEFFERSON PARISH

DEPARTMENT OF PURCHASING

CYNTHIA LEE SHENG
PARISH PRESIDENT

RENNY SIMNO
DIRECTOR

January 2020

Changes to Jefferson Parish Bidding Information

The Jefferson Parish Purchasing Department would like to make vendors aware of the following changes:

Probable Construction Cost: Per Jefferson Parish Administrative Policy, the probable construction cost is not revealed in the Jefferson Parish Bidding Documents. Jefferson Parish Administrative Policy has changed and a range of the probable construction cost will be stated in the Jefferson Parish bidding document, entitled Important Notice to All Bidders – Bid Requirements. Per Louisiana Public Bid Law, the probable construction cost will be read at the bid opening.

Insurance Requirement: All bidders must provide proof of valid insurance in the required amounts as stated in the Standard Insurance Requirements for bidding purposes. Failure to provide the proof of valid insurance in all of the required coverage amounts will result in bid rejection.

GENERAL GOVERNMENT BLDG. – 200 DERBIGNY ST., SUITE 4400. GRETN, LA 70053
OFFICE 504.364.2678

JOSEPH S. YENNI BLDG. – 1221 ELMWOOD PARK BLVD., SUITE 404, JEFFERSON, LA 70123
OFFICE 504.364.2678

EMAIL: PURCHASING@JEFFPARISH.NET WEBSITE: WWW.JEFFPARISH.NET

CORPORATE RESOLUTION

EXCERPT FROM MINUTES OF MEETING OF THE BOARD OF DIRECTORS OF
ITA Truck Sales & Service, LLC
INCORPORATED.

AT THE MEETING OF DIRECTORS OF ITA Truck Sales & Service
INCORPORATED, DULY NOTICED AND HELD ON 3/5/20,
A QUORUM BEING THERE PRESENT, ON MOTION DULY MADE AND SECONDED. IT
WAS:

RESOLVED THAT Ben Springer, BE AND IS HEREBY
APPOINTED, CONSTITUTED AND DESIGNATED AS AGENT AND ATTORNEY-IN-
FACT OF THE CORPORATION WITH FULL POWER AND AUTHORITY TO ACT ON
BEHALF OF THIS CORPORATION IN ALL NEGOTIATIONS, BIDDING, CONCERNS
AND TRANSACTIONS WITH THE PARISH OF JEFFERSON OR ANY OF ITS AGENCIES,
DEPARTMENTS, EMPLOYEES OR AGENTS, INCLUDING BUT NOT LIMITED TO, THE
EXECUTION OF ALL BIDS, PAPERS, DOCUMENTS, AFFIDAVITS, BONDS, SURETIES,
CONTRACTS AND ACTS AND TO RECEIVE ALL PURCHASE ORDERS AND NOTICES
ISSUED PURSUANT TO THE PROVISIONS OF ANY SUCH BID OR CONTRACT, THIS
CORPORATION HEREBY RATIFYING, APPROVING, CONFIRMING, AND ACCEPTING
EACH AND EVERY SUCH ACT PERFORMED BY SAID AGENT AND ATTORNEY-IN-
FACT.

I HEREBY CERTIFY THE FOREGOING TO BE
A TRUE AND CORRECT COPY OF AN
EXCERPT OF THE MINUTES OF THE ABOVE
DATED MEETING OF THE BOARD OF
DIRECTORS OF SAID CORPORATION, AND
THE SAME HAS NOT BEEN REVOKED OR
RESCINDED.



SECRETARY-TREASURER

3/19/2020

DATE

Non-Public Works Bid

AFFIDAVIT

STATE OF Louisiana

PARISH/COUNTY OF Lafayette

BEFORE ME, the undersigned authority, personally came and appeared: Ben
Springer, (Affiant) who after being by me duly sworn, deposed and said that
he/she is the fully authorized Agent of ITA Truck Sales Service (Entity),
the party who submitted a bid in response to Bid Number 50-0013036 to the Parish of
Jefferson.

Affiant further said:

Campaign Contribution Disclosures

(Choose A or B, if option A is indicated please include the required
attachment):

Choice A _____ Attached hereto is a list of all campaign contributions, including
the date and amount of each contribution, made to current or
former elected officials of the Parish of Jefferson by Entity,
Affiant, and/or officers, directors and owners, including
employees, owning 25% or more of the Entity during the two-year
period immediately preceding the date of this affidavit or the
current term of the elected official, whichever is greater. Further,
Entity, Affiant, and/or Entity Owners have not made any
contributions to or in support of current or former members of the
Jefferson Parish Council or the Jefferson Parish President through
or in the name of another person or legal entity, either directly or
indirectly.

Choice B ✓ there are NO campaign contributions made which would require
disclosure under Choice A of this section.

Debt Disclosures

(Choose A or B, if option A is indicated please include the required attachment):

Choice A Attached hereto is a list of all debts owed by the affiant to any elected or appointed official of the Parish of Jefferson, and any and all debts owed by any elected or appointed official of the Parish to the Affiant.

Choice B ✓ There are NO debts which would require disclosure under Choice A of this section.

Affiant further said:

That Affiant has employed no person, corporation, firm, association, or other organization, either directly or indirectly, to secure the public contract under which he received payment, other than persons regularly employed by the Affiant whose services in connection with the construction, alteration or demolition of the public building or project or in securing the public contract were in the regular course of their duties for Affiant; and


[The remainder of this page is intentionally left blank.]

That no part of the contract price received by Affiant was paid or will be paid to any person, corporation, firm, association, or other organization for soliciting the contract, other than the payment of their normal compensation to persons regularly employed by the Affiant whose services in connection with the construction, alteration or demolition of the public building or project were in the regular course of their duties for Affiant.


Signature of Affiant

Ben Springer
Printed Name of Affiant

SWORN AND SUBSCRIBED TO BEFORE ME
ON THE 19th DAY OF March, 2020.


Notary Public

Christopher D. Shoues
Printed Name of Notary

31538
Notary/Bar Roll Number

My commission expires At Death.

License No. N -2019-00232
DPS Code: NLIB

2019-2021

Not Transferable
Valid Only at Address Below

Louisiana Motor Vehicle Commission

This Certifies that

ITA Truck Sales & Service, L.L.C.
2835 Northwest Evangeline Thruway
Lafayette, LA 70507
Christopher D. Schouest, Dealer-Operator

is duly licensed as a

New Motor Vehicle Dealer

of the following make or makes

AEV Technologies, IC BUS, International Series

For the period ending October 31, 2021, unless license is sooner revoked.

In Witness whereof, LOUISIANA MOTOR VEHICLE COMMISSION, under and by virtue of the authority vested in it by the laws of the State of Louisiana, has caused this license to be issued with its seal imprinted hereon.

LOUISIANA MOTOR VEHICLE COMMISSION

Dated November 1, 2019
Signed, Sealed and Attested




Executive Director


Chairman

(To be prominently displayed in place of business)

CERTIFICATE OF LIABILITY INSURANCE

DATE(MM/DD/YY)
3/12/20


Producer LA Automobile Dealers Association-SIF 7526 Picardy Ave. Baton Rouge, LA 70808-3598	THIS CERTIFICATE IS ISSUED AS A MATTER OF INFORMATION ONLY AND CONFERS NO RIGHTS UPON THE CERTIFICATE HOLDER. THIS CERTIFICATE DOES NOT AMEND, EXTEND OR ALTER THE COVERAGE AFFORDED BY THE POLICIES BELOW.	
Insured ITA Truck Sales & Service, L.L.C. 2835 N.W. Evangeline Thruway Lafayette, LA 70507-3420	INSURERS AFFORDING COVERAGE	NAIC #
	INSURER A: LA AUTOMOBILE DEALERS ASSOC. SIF	
	INSURER B:	
	INSURER C:	
	INSURER D:	
INSURER E:		

COVERAGES

THE POLICIES OF INSURANCE LISTED BELOW HAVE BEEN ISSUED TO THE INSURED NAMED ABOVE FOR THE POLICY PERIOD INDICATED, NOTWITHSTANDING ANY REQUIREMENT TERM OR CONDITION OF ANY CONTRACT OR OTHER DOCUMENT WITH RESPECT TO WHICH THIS CERTIFICATE MAY BE ISSUED OR MAY PERTAIN THE INSURANCE AFFORDED BY THE POLICIES DESCRIBED HEREIN IS SUBJECT TO ALL THE TERMS, EXCLUSIONS AND CONDITIONS OF SUCH POLICIES. AGGREGATE LIMITS SHOWN MAY HAVE BEEN REDUCED BY PAID CLAIMS.

INSR LTR	ADD'L INSRD	TYPE OF INSURANCE	POLICY NUMBER	POLICY EFFECTIVE DATE (MM/DD/YY)	POLICY EXPIRATION DATE (MM/DD/YY)	LIMITS	
		GENERAL LIABILITY COMMERCIAL GENERAL LIABILITY <input type="checkbox"/> CLAIMS MADE <input type="checkbox"/> OCCUR <hr/> GEN'L AGGREGATE LIMIT APPLIES PER: <input type="checkbox"/> POLICY <input type="checkbox"/> PRO-JECT <input type="checkbox"/> LOC				EACH OCCURRENCE	\$
		FIRE DAMAGE (Any one fire)				\$	
		MED EXP (Any one person)				\$	
		PERSONAL & ADV INJURY				\$	
		GENERAL AGGREGATE				\$	
		PRODUCTS - COM/OP AGG				\$	
		AUTOMOBILE LIABILITY ANY AUTO ALL OWNED AUTOS SCHEDULED AUTOS HIRED AUTOS NON-OWNED AUTOS				COMBINED SINGLE LIMIT (Ea accident)	\$
		BODILY INJURY (Per person)				\$	
		BODILY INJURY (Per accident)				\$	
		PROPERTY DAMAGE (Per accident)				\$	
		GARAGE LIABILITY ANY AUTO				AUTO ONLY - EA ACCIDENT	\$
		OTHER THAN EA ACC				\$	
		AUTO ONLY AGG				\$	
		EXCESS LIABILITY OCCUR <input type="checkbox"/> CLAIMS MADE DEDUCTIBLE RETENTION \$				EACH OCCURRENCE	\$
		AGGREGATE				\$	
						\$	
						\$	
						\$	
						\$	
A		WORKERS COMPENSATION AND EMPLOYERS LIABILITY ANY PROPRIETER/PARTNER/EXECUTIVE OFFICER/MEMBER EXCLUDED? YES If yes, describe under SPECIAL PROVISIONS below	073000000601120	1/01/20	1/01/21	<input checked="" type="checkbox"/> WC STATUTORY LIMITS <input type="checkbox"/> OTH-ER	
		E.L. EACH ACCIDENT				\$ 500,000	
		E.L. DISEASE - EA EMPLOYEE				\$ 500,000	
		E.L. DISEASE - POLICY LIMIT				\$ 500,000	
		OTHER					

DESCRIPTION OF OPERATIONS/ LOCATIONS/ VEHICLES/ EXCLUSIONS ADDED BY ENDORSEMENT / SPECIAL PROVISIONS
 STATE OF LOUISIANA EMPLOYEES ONLY Additional insured locations: Idealease of Acadiana in Lafayette, LA, ITA in Harahan, LA, ITA-Houma in Houma, LA, ITA Truck Sales & Service, LLC in Lake Charles, LA and ITA-Slidell in Slidell, LA

CERTIFICATE HOLDER	ADDITIONAL INSURED: INSURER LETTER:	CANCELLATION
The Jefferson Parish, its Districts Departments and Agencies under the direction of the Parish President and the Parish Council Bid No: 50-130136 General Gov't Building, Suite 4400 200 Derbigny Street Gretna, LA 70053		SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, THE ISSUING INSURER WILL ENDEAVOR TO MAIL <u>30</u> DAYS WRITTEN NOTICE TO THE CERTIFICATE HOLDER NAMED TO THE LEFT, BUT FAILURE TO DO SO SHALL IMPOSE NO OBLIGATION OR LIABILITY OF ANY KIND UPON THE INSURER, ITS AGENTS OR REPRESENTATIVES. AUTHORIZED REPRESENTATIVE 



ITATRUC-01

KAUCOIN

CERTIFICATE OF LIABILITY INSURANCE

DATE (MM/DD/YYYY)

3/12/2020

THIS CERTIFICATE IS ISSUED AS A MATTER OF INFORMATION ONLY AND CONFERS NO RIGHTS UPON THE CERTIFICATE HOLDER. THIS CERTIFICATE DOES NOT AFFIRMATIVELY OR NEGATIVELY AMEND, EXTEND OR ALTER THE COVERAGE AFFORDED BY THE POLICIES BELOW. THIS CERTIFICATE OF INSURANCE DOES NOT CONSTITUTE A CONTRACT BETWEEN THE ISSUING INSURER(S), AUTHORIZED REPRESENTATIVE OR PRODUCER, AND THE CERTIFICATE HOLDER.

IMPORTANT: If the certificate holder is an ADDITIONAL INSURED, the policy(ies) must have ADDITIONAL INSURED provisions or be endorsed. If SUBROGATION IS WAIVED, subject to the terms and conditions of the policy, certain policies may require an endorsement. A statement on this certificate does not confer rights to the certificate holder in lieu of such endorsement(s).

PRODUCER License # 231432 Hub International Gulf South 8550 United Plaza Blvd. Suite 500 Baton Rouge, LA 70809	CONTACT NAME: PHONE (A/C, No, Ext): (800) 789-7365		FAX (A/C, No): (225) 218-2401
	E-MAIL ADDRESS:		
	INSURER(S) AFFORDING COVERAGE		NAIC #
	INSURER A : New York Marine & General Insurance		16608
	INSURER B : AGCS Marine Insurance Company		22837
	INSURER C : Great American Assurance Company		26344
INSURED ITA Truck Sales & Service, LLC 2835 NW Evangeline Thruway Lafayette, LA 70507	INSURER D :		
	INSURER E :		
	INSURER F :		

COVERAGES

CERTIFICATE NUMBER:

REVISION NUMBER:

THIS IS TO CERTIFY THAT THE POLICIES OF INSURANCE LISTED BELOW HAVE BEEN ISSUED TO THE INSURED NAMED ABOVE FOR THE POLICY PERIOD INDICATED. NOTWITHSTANDING ANY REQUIREMENT, TERM OR CONDITION OF ANY CONTRACT OR OTHER DOCUMENT WITH RESPECT TO WHICH THIS CERTIFICATE MAY BE ISSUED OR MAY PERTAIN, THE INSURANCE AFFORDED BY THE POLICIES DESCRIBED HEREIN IS SUBJECT TO ALL THE TERMS, EXCLUSIONS AND CONDITIONS OF SUCH POLICIES. LIMITS SHOWN MAY HAVE BEEN REDUCED BY PAID CLAIMS.

INSR LTR	TYPE OF INSURANCE	ADDL INSD	SUBR WVD	POLICY NUMBER	POLICY EFF (MM/DD/YYYY)	POLICY EXP (MM/DD/YYYY)	LIMITS
A	<input checked="" type="checkbox"/> COMMERCIAL GENERAL LIABILITY <input type="checkbox"/> CLAIMS-MADE <input checked="" type="checkbox"/> OCCUR <input checked="" type="checkbox"/> Garage Liability GEN'L AGGREGATE LIMIT APPLIES PER: <input checked="" type="checkbox"/> POLICY <input type="checkbox"/> PRO-JECT <input type="checkbox"/> LOC OTHER:			AU2019DOP00207	10/1/2019	10/1/2020	EACH OCCURRENCE \$ 1,000,000 DAMAGE TO RENTED PREMISES (Ea occurrence) \$ MED EXP (Any one person) \$ 5,000 PERSONAL & ADV INJURY \$ GENERAL AGGREGATE \$ 3,000,000 PRODUCTS - COMP/OP AGG \$ \$
A	<input checked="" type="checkbox"/> AUTOMOBILE LIABILITY <input checked="" type="checkbox"/> ANY AUTO OWNED AUTOS ONLY <input type="checkbox"/> SCHEDULED AUTOS <input type="checkbox"/> HIRED AUTOS ONLY <input type="checkbox"/> NON-OWNED AUTOS ONLY			AU2019DOP00207	10/1/2019	10/1/2020	COMBINED SINGLE LIMIT (Ea accident) \$ 1,000,000 BODILY INJURY (Per person) \$ BODILY INJURY (Per accident) \$ PROPERTY DAMAGE (Per accident) \$ \$
A	<input checked="" type="checkbox"/> UMBRELLA LIAB <input checked="" type="checkbox"/> OCCUR <input type="checkbox"/> EXCESS LIAB <input type="checkbox"/> CLAIMS-MADE <input type="checkbox"/> DED <input checked="" type="checkbox"/> RETENTION \$ 10,000			UM2019DOP00205	10/1/2019	10/1/2020	EACH OCCURRENCE \$ 10,000,000 AGGREGATE \$ 10,000,000 \$ PER STATUTE <input type="checkbox"/> OTH-ER <input type="checkbox"/> E.L. EACH ACCIDENT \$ E.L. DISEASE - EA EMPLOYEE \$ E.L. DISEASE - POLICY LIMIT \$
	WORKERS COMPENSATION AND EMPLOYERS' LIABILITY ANY PROPRIETOR/PARTNER/EXECUTIVE OFFICER/MEMBER EXCLUDED? (Mandatory in NH) <input type="checkbox"/> Y / N If yes, describe under DESCRIPTION OF OPERATIONS below		N / A				
B	Dealer Open Lot			MXI93079185	8/6/2019	6/1/2020	Total Limit 8,195,000
C	Contingent Lease			190537805	10/1/2019	10/1/2020	Liability 5,000,000

DESCRIPTION OF OPERATIONS / LOCATIONS / VEHICLES (ACORD 101, Additional Remarks Schedule, may be attached if more space is required)

Garage Liability Deductible - \$2,500

Dealer Open Lot Deductible - \$2,500 per vehicle for Collision & Comprehensive

Contingent Lease Physical Damage Deductible - \$2,500, Max Limit Per Vehicle \$75,000

Named Insureds:

ITA Truck Sales & Service, LLC

Idealease of Acadiana, LLC

SEE ATTACHED ACORD 101

CERTIFICATE HOLDER

CANCELLATION

Jefferson Parish, its Districts Departments & Agencies under the direction of the Parish President & the Parish Council
 200 Derbigny St.
 General Govnt. Bldg. Suite 4400
 Gretna, LA 70053

SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, NOTICE WILL BE DELIVERED IN ACCORDANCE WITH THE POLICY PROVISIONS.

AUTHORIZED REPRESENTATIVE



ADDITIONAL REMARKS SCHEDULE

AGENCY Hub International Gulf South		License # 231432	NAMED INSURED ITA Truck Sales & Service, LLC 2835 NW Evangeline Thruway Lafayette, LA 70507
POLICY NUMBER SEE PAGE 1			
CARRIER SEE PAGE 1	NAIC CODE SEE P 1	EFFECTIVE DATE: SEE PAGE 1	

ADDITIONAL REMARKS

THIS ADDITIONAL REMARKS FORM IS A SCHEDULE TO ACORD FORM,
FORM NUMBER: ACORD 25 FORM TITLE: Certificate of Liability Insurance

Description of Operations/Locations/Vehicles:

Atterberry Truck Sales, Inc.
Atterberry Idealease
Schilling Acquisitions, LLC

Locations:

2835 NW Evangenlie Thruway, Lafayette, LA 70507
2845 NW Evangenlie Thruway, Lafayette, LA 70507
301 Hord St. Harahan, LA 70123
102 Clendenning Rd, Houma, LA 70363
524 Pamco Rd, Lake Charles, LA 70615
6035 Beven St. New Orleans, LA 70123
2399 Gause Blvd. Slidell, LA 70460

Jefferson Parish, its Districts Departments & Agencies under the direction of the Parish President & the Parish Council is additional insureds regarding negligence by the contractor in reference to bid #50- 130136, as required by written contract.

Prepared For:

Jefferson Parish
Nicholas DiGerolamo
200 Derbigny St.
Gretna, LA 70053-5850
(504)364 - 2678
Reference ID: 25/29 MV 20

Presented By:

ITA-NOLA, LLC
Ben Springer
301 HORD
HARAHAN LA 70123 -
(504)733-7711

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2021 MV607 SBA (MV607)

AXLE CONFIG:	4X2
APPLICATION:	Stake Flat
MISSION:	Requested GVWR: 25500. Calc. GVWR: 25500 Calc. Start / Grade Ability: 26.26% / 1.57% @ 55 MPH Calc. Geared Speed: 81.0 MPH
DIMENSION:	Wheelbase: 175.00, CA: 107.90, Axle to Frame: 75.00
ENGINE, DIESEL:	{Cummins B6.7 220} EPA 2017, 220HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 220 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 2100 HS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 26,000-lb GVW and GCW Max
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity
AXLE, REAR, SINGLE:	{Dana Spicer 17060S} Single Reduction, 17,500-lb Capacity, 190 Wheel Ends Gear Ratio: 6.17
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 10R22.5 Load Range G AH37 (HANKOOK), 517 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 10R22.5 Load Range G DH01 (HANKOOK), 512 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, SINGLE:	18,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs
PAINT:	Cab schematic 100WP Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>
MV60700	Base Chassis, Model MV607 SBA with 175.00 Wheelbase, 107.90 CA, and 75.00 Axle to Frame.
1ANA	AXLE CONFIGURATION {Navistar} 4x2
	<u>Notes</u> : Pricing may change if axle configuration is changed.
1CAD	FRAME RAILS High Strength Low Alloy Steel (80,000 PSI Yield); 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm); 455.0" (11557mm) Maximum OAL
1LLD	BUMPER, FRONT Contoured, Steel
1WEH	WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)
2ATK	AXLE, FRONT NON-DRIVING {Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity
3ADA	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 8,000-lb Capacity, with Shock Absorbers
	<u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes) : SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes) : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System
4EBS	AIR DRYER {Bendix AD-9} with Heater
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
4JCG	BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM
4VJE	AIR TANK LOCATION (2) Mounted Inline Under Left Rail, Back of Cab
4VJL	AIR DRYER LOCATION Mounted Outside Left Rail, 51" Back of Cab
5AAA	STEERING COLUMN Stationary
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
5PRG	STEERING GEAR {TRW (Ross) TAS40} Power
6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2
7BEV	AFTERTREATMENT COVER Steel, Black

<u>Code</u>	<u>Description</u>
7BKS	EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab
7WDM	EXHAUST HEIGHT 10'
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum
7WDT	TAIL PIPE (1) Straight Type
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	<u>Includes</u>
	: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
	: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
	: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
	: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
	: STARTER SWITCH Electric, Key Operated
	: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
	: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
	: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
	: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
	: WIRING, CHASSIS Color Coded and Continuously Numbered
8GXD	ALTERNATOR {Leece-Neville AV1160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, with Remote Sense
8HAB	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn
8NBR	BATTERY SYSTEM {JCI} Maintenance-Free, (3) 12-Volt 2100CCA Total, Top Threaded Stud
8RMV	SPEAKERS (2) 6.5" Dual Cone Mounted in Doors
8RPT	RADIO AM/FM/WB/Clock/USB Input/Auxiliary Input
8VAY	HORN, ELECTRIC Disc Style
8VUL	BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab
8WTK	STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt, Less Thermal Over-Crank Protection
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm
8WZK	HEADLIGHTS Halogen, Composite Aero Design
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
8XHN	HORN, AIR Black, Single Trumpet, with Lanyard Pull Cord
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
9HAD	GRILLE Chrome
9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
	<u>Includes</u>
	: PAINT SCHEMATIC ID LETTERS "WP"

<u>Code</u>	<u>Description</u>
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
10WUE	MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension
11001	CLUTCH Omit Item (Clutch & Control)
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12EJG	ENGINE, DIESEL {Cummins B6.7 220} EPA 2017, 220HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 220 Peak HP (Max)
12EMZ	VENDOR WARRANTY, ENGINE {Cummins} B6.7 Engine, 3-Year Unlimited Miles Standard Warranty
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On
	<u>Includes</u> : FAN Nylon
12UYE	RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, with 313 SqIn Charge Air Cooler. with In-Tank Transmission Cooler
	<u>Includes</u> : DEAERATION SYSTEM with Surge Tank : HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber
12VBR	AIR CLEANER with Service Protection Element
12VHH	FEDERAL EMISSIONS {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2020
12VXV	THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Mobile, Variable Speed; (Range 2 to 20 MPH) Mounted on Steering Wheel
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations
12XAT	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines
13ATC	TRANSMISSION, AUTOMATIC {Allison 2100 HS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 26,000-lb GVW and GCW Max
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints
13WVS	TRANSMISSION SHIFT CONTROL T-Handle
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming
14AGE	AXLE, REAR, SINGLE {Dana Spicer 17060S} Single Reduction, 17,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 6.17
14VAD	SUSPENSION, REAR, SINGLE 18,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs
15LMS	FUEL/WATER SEPARATOR 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor, Cummins Supplied on Engine
15SGJ	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab
15WDG	DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab
16030	CAB Conventional, Day Cab

<u>Code</u>	<u>Description</u>
	<u>Includes</u> : CLEARANCE/MARKER LIGHTS (5) Flush Mounted
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16GDC	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display
16HGN	GAUGE, AIR APPLICATION
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16KAV	SEAT, DRIVER {National} Non-Suspension, High Back with Integral Head Rest, Vinyl, with Fixed Back
16SMP	SEAT, TWO-MAN PASSENGER {National} Vinyl, Less Under Seat Storage Compartment
16SNL	MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width
	<u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"
16VKB	CAB INTERIOR TRIM Classic, for Day Cab
	<u>Includes</u> : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger : DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16VLK	CAB REAR SUSPENSION Air Suspension, for Mid Cab Height
16XCK	WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors
16XJN	INSTRUMENT PANEL Flat Panel
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab
26DTU	WHEEL, SPARE, DISC {Accuride 29001} 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole 10-Stud, 285.75mm BC, Hub-Piloted
27DTU	WHEELS, FRONT {Accuride 29001} DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DTU	WHEELS, REAR {Accuride 29001} DUAL DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7372115808	(4) TIRE, REAR 10R22.5 Load Range G DH01 (HANKOOK), 512 rev/mile, 75 MPH, Drive
7372115809	(2) TIRE, FRONT 10R22.5 Load Range G AH37 (HANKOOK), 517 rev/mile, 75 MPH, All-Position

Services Section:

40129	WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A
1	Back Up Camera Installed

MV™ SERIES

Configuration: 107" BBC
Application: Truck or Tractor
Engine: Cummins B6.7, L9



- ▶ UTILITY
- ▶ DRY VAN
- ▶ DIGGER DERRICK
- ▶ RECOVERY
- ▶ CONSTRUCTION DUMP
- ▶ FIRE AND EMERGENCY

Introducing the new International® MV™ Series, a medium duty truck that's built with everything you need to conquer your daily grind. It's designed and engineered to set new standards for quality and productivity, with a spacious new cab interior crafted through driver input for optimal comfort, control and safety. The MV Series offers the industry-leading intelligence of the Diamond Logic® electrical system, as well as OnCommand® Connection, the industry's first and only all-makes diagnostic system for unrivaled connectivity. With virtually limitless customization options, the MV Series provides the ideal truck for your demanding application.





KEY FEATURES:

- ▶ HSLA reinforced, cold-rolled steel cab for long-term durability
- ▶ New one-piece steel door frame and panels improve cab durability, structure and sealing
- ▶ New door, side glass and mirror designs improve lateral visibility and workplace safety
- ▶ All-new interior offers best-in-class room and driver-centric design for optimal productivity
- ▶ Driver controls can easily be operated while wearing gloves
- ▶ Available premium gauge cluster is customizable with virtual gauges
- ▶ All-new HVAC system, designed for reliability, includes a best-in-class MAX defrost feature
- ▶ Industry-leading Diamond Logic® electrical system
- ▶ Column-mounted shifter integrated with engine braking helps keep hands on the wheel



107" BBC SET-BACK FRONT AXLE

GVW

- ▶ 21,500 - 54,600 lbs.

Models/BBC/BA

- ▶ MV607: 107" BBC, 40" BA
- ▶ MV60H: 107" BBC, 40" BA (Low Profile)

Cab Configurations

- ▶ Day Cab
- ▶ Extended Cab
- ▶ Crew Cab

Wheelbase Options

- ▶ 128" - 311"

Axle Configurations

- ▶ 4x2, 6x4

Rear Axle

- ▶ Single Rear Axle (4x2)
 - Meritor: 13,500 - 30,000 lbs.
 - Dana Spicer: 13,500 - 30,000 lbs.
- ▶ Tandem Rear Axle (6x4)
 - Meritor: 34,000 - 40,000 lbs.
 - Dana Spicer: 40,000 lbs.
- ▶ Front Axle
 - Meritor: 8,000 - 14,600 lbs. (4x2, 6x4)
 - Dana Spicer: 8,000 - 14,000 lbs.

Frames

- ▶ High Strength Low-alloy Steel 50,000 - 80,000 PSI
- ▶ Heat Treated Alloy Steel 120,000 PSI
- ▶ Clean CA available for body mounting

Front Suspension

- ▶ Spring, Parabolic Taper Leaf: 8,000 - 14,600 lbs.

Rear Suspension

- ▶ Spring, Single Vari-Rate: 13,500 - 31,000 lbs.
- ▶ Tandem, 4-Spring Multileaf: 34,000 - 40,000 lbs.
- ▶ IROS Air Suspension available for Single and Tandem Axle

Electrical System

- ▶ Diamond Logic® Electrical System
- ▶ Alternators
 - 12 Volt 160 - 325 Amp.
- ▶ Battery Systems
 - 12 Volt, 2 to 3 Batteries
- ▶ Headlights
 - Long Life Halogen

Exhaust System

- ▶ Single, Horizontal, After-treatment Device Frame Mounted Right, Under Cab or Back of Cab, Horizontal or Vertical Tailpipe

Brakes

- ▶ Hydraulic Disc with Four Channel ABS, Optional Traction Control
- ▶ Air Brakes with ABS, Optional Traction Control, Optional Electronic Stability Program with Traction Control

Steering

- ▶ TRW/Ross Power
- ▶ Sheppard Power

Engines

- ▶ Cummins B6.7: 200 - 325 hp and 520 - 750 lb.-ft. of torque*
- ▶ Cummins L9: 260 - 350 hp and 720 - 1000 lb.-ft. of torque

Transmissions

- ▶ Eaton® Fuller: 6, 10 Speed Manual
- ▶ Eaton: Prociption™ 7 Speed Dual Clutch Automatic
- ▶ Allison: 1000, 2000, 3000 Series (HS, EVS, RDS, MH) Automatic
- ▶ Allison: 3000 TRV Series Automatic
- ▶ Eaton® Fuller: Advantage 10 Speed Fully Automated Manual

Fuel Tank

- ▶ 40 - 140 Gallon Non-Polished and Polished Aluminum, Mounted Right Side, Left Side or Dual Under Cab

DEF Tank

- ▶ 5-15 Gallon

Tires

- ▶ Continental, Michelin, Goodyear, Bridgestone, Hankook, Yokohama

* 340 hp and 700 lb.-ft. of torque / 360 hp and 800 lb.-ft. torque ratings available for emergency vehicles only

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice. TAD18001 1/2018

©2018 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.

LIMITED WARRANTY FOR MV MODEL SERIES

*Effective with vehicles built July 01, 2017 or later

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or ReNEWed® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE	Months	Miles/Km (000)
Basic Vehicle Warranty (See exceptions listed below)	24	Unlimited
Towing (First 90 days see below) (Vehicle Down Situations Only) (See exceptions listed below)	3	Unlimited
Note: Items not listed in warranty exceptions follow base warranty.		
WARRANTY EXCEPTIONS		
CHASSIS COVERAGE	Months	Miles/Km (000)
Frame side rails	84	Unlimited
Cab/cowl structure	60	Unlimited
Cab/cowl perforation corrosion	60	Unlimited
DRIVETRAIN COVERAGE	Months	Miles/Km (000)
Meritor Axles	36	Unlimited
Eaton Prociision Transmission	24	Unlimited
MISCELLANEOUS COVERAGE	Months	Miles/Km (000)
Batteries	12	Unlimited
Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited

FIRST 90 DAYS FROM DELIVERY TO USER (DTU)

Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless specific coverage is stated above). Adjustments and Maintenance (e.g. aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Warranted by their respective manufacturers (e.g., non-International® brand engines, tires, Allison Transmissions, Eaton Hybrid components, lubricants, etc.)
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments

Repairs & Maintenance

- Maintenance-related items/repairs, or those, as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension

Other

- Vehicles sold and/or operated outside the United States and Canada
 - This exception does not apply to vehicles that meet current USA EPA emission standards, which were sold by an International dealer located in Mexico, if the vehicle is authorized by the U.S D.O.T to operate in long-haul, cross border transportation and the vehicle is only operated in the United States, Canada, and Mexico
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note: The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:
I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

<hr/>		<hr/>	
Customer Signature		Date	
<hr/>		<hr/>	
Owner's Address	City	State/Prov	Postal Code
<hr/>		<hr/>	
Truck Model	Vehicle Identification Number		
<hr/>		<hr/>	
Engine Number	Engine Serial Number		
<hr/>		<hr/>	
Date Delivered to User (DTU)	Odometer Reading at Delivery		

IMPORTANT: The information contained in this Warranty Policy explains the coverage provided on your new International® vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty service.

Prepared For:

Jefferson Parish
Nicholas DiGerolamo
200 Derbigny St.
Gretna, LA 70053-5850
(504)364 - 2678
Reference ID: 33/37 20 MV

Presented By:

ITA-NOLA, LLC
Ben Springer
301 HORD
HARAHAN LA 70123 -
(504)733-7711

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2021 MV607 SBA (MV607)

AXLE CONFIG:	4X2
APPLICATION:	Stake Flat
MISSION:	Requested GVWR: 33000. Calc. GVWR: 33000 Calc. Start / Grade Ability: 21.05% / 2.12% @ 55 MPH Calc. Geared Speed: 80.0 MPH
DIMENSION:	Wheelbase: 171.00, CA: 103.90, Axle to Frame: 65.00
ENGINE, DIESEL:	{Cummins B6.7 250} EPA 2017, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 250 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 2500 RDS} 5th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-122A} I-Beam Type, 12,000-lb Capacity
AXLE, REAR, SINGLE:	{Dana Spicer 21060S} Single Reduction, Hypoid Gearing, 21,000-lb Capacity, 200 Wheel Ends Gear Ratio: 5.29
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, SINGLE:	23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs
PAINT:	Cab schematic 100WP Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>
MV60700	Base Chassis, Model MV607 SBA with 171.00 Wheelbase, 103.90 CA, and 65.00 Axle to Frame.
1ANA	AXLE CONFIGURATION {Navistar} 4x2
	<u>Notes</u> : Pricing may change if axle configuration is changed.
1CAD	FRAME RAILS High Strength Low Alloy Steel (80,000 PSI Yield); 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm); 455.0" (11557mm) Maximum OAL
1LLD	BUMPER, FRONT Contoured, Steel
1WEH	WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)
2ASC	AXLE, FRONT NON-DRIVING {Meritor MFS-12-122A} I-Beam Type, 12,000-lb Capacity
3ADC	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity, with Shock Absorbers
	<u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes) : SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes) : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System
4EBS	AIR DRYER {Bendix AD-9} with Heater
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
4JCG	BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM
4VJE	AIR TANK LOCATION (2) Mounted Inline Under Left Rail, Back of Cab
4VJL	AIR DRYER LOCATION Mounted Outside Left Rail, 51" Back of Cab
5AAA	STEERING COLUMN Stationary
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
5PSA	STEERING GEAR {Sheppard M100} Power
6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2
7BEV	AFTERTREATMENT COVER Steel, Black

<u>Code</u>	<u>Description</u>
7BKS	EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab
7WAE	RAIN CAP with Single Exhaust, Non-Bright Finish
7WDM	EXHAUST HEIGHT 10'
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum
7WDT	TAIL PIPE (1) Straight Type
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	<u>Includes</u>
	: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
	: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
	: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
	: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
	: STARTER SWITCH Electric, Key Operated
	: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
	: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
	: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
	: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
	: WIRING, CHASSIS Color Coded and Continuously Numbered
8GXD	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, with Remote Sense
8HAB	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn
8HAH	ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket
8NBR	BATTERY SYSTEM {JCI} Maintenance-Free, (3) 12-Volt 2100CCA Total, Top Threaded Stud
8RMV	SPEAKERS (2) 6.5" Dual Cone Mounted in Doors
8RPT	RADIO AM/FM/WB/Clock/USB Input/Auxiliary Input
8VAY	HORN, ELECTRIC Disc Style
8VUL	BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab
8WTK	STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt, Less Thermal Over-Crank Protection
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm
8WZK	HEADLIGHTS Halogen, Composite Aero Design
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
8XHN	HORN, AIR Black, Single Trumpet, with Lanyard Pull Cord
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
9HAD	GRILLE Chrome

<u>Code</u>	<u>Description</u>
9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
	<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WP"
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
10WUE	MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension
11001	CLUTCH Omit Item (Clutch & Control)
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12EJS	ENGINE, DIESEL {Cummins B6.7 250} EPA 2017, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 250 Peak HP (Max)
12EMZ	VENDOR WARRANTY, ENGINE {Cummins} B6.7 Engine, 3-Year Unlimited Miles Standard Warranty
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On
	<u>Includes</u> : FAN Nylon
12UYE	RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, with 313 SqIn Charge Air Cooler. with In-Tank Transmission Cooler
	<u>Includes</u> : DEAERATION SYSTEM with Surge Tank : HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber
12VBR	AIR CLEANER with Service Protection Element
12VHH	FEDERAL EMISSIONS {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2020
12VXV	THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Mobile, Variable Speed; (Range 2 to 20 MPH) Mounted on Steering Wheel
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations
12XAT	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines
13ASP	TRANSMISSION, AUTOMATIC {Allison 2500 RDS} 5th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, On/Off Highway
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints
13WVS	TRANSMISSION SHIFT CONTROL T-Handle
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming
13XAK	PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission
14AET	AXLE, REAR, SINGLE {Dana Spicer 21060S} Single Reduction, Hypoid Gearing, 21,000-lb Capacity, 200 Wheel Ends . Gear Ratio: 5.29
14VAH	SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

<u>Code</u>	<u>Description</u>
15LMR	FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor
15LMY	LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 20" Back of Cab
15SGJ	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab
15WDG	DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab
16030	CAB Conventional, Day Cab
	<u>Includes</u> : CLEARANCE/MARKER LIGHTS (5) Flush Mounted
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16GDC	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display
16HGN	GAUGE, AIR APPLICATION
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16KAV	SEAT, DRIVER {National} Non-Suspension, High Back with Integral Head Rest, Vinyl, with Fixed Back
16SMP	SEAT, TWO-MAN PASSENGER {National} Vinyl, Less Under Seat Storage Compartment
16SNL	MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width
	<u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"
16VKB	CAB INTERIOR TRIM Classic, for Day Cab
	<u>Includes</u> : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger : DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16VLK	CAB REAR SUSPENSION Air Suspension, for Mid Cab Height
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature
16XJN	INSTRUMENT PANEL Flat Panel
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab
26DTU	WHEEL, SPARE, DISC {Accuride 29001} 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole 10-Stud, 285.75mm BC, Hub-Piloted
27DTU	WHEELS, FRONT {Accuride 29001} DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DTU	WHEELS, REAR {Accuride 29001} DUAL DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7372135810	(4) TIRE, REAR 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive
7382135809	(2) TIRE, FRONT 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position

<u>Code</u>	<u>Description</u>
	Services Section:
40129	WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A
2	30K Pintle Hitch Installed

MV™ SERIES

Configuration: 107" BBC
Application: Truck or Tractor
Engine: Cummins B6.7, L9



- ▶ UTILITY
- ▶ DRY VAN
- ▶ DIGGER DERRICK
- ▶ RECOVERY
- ▶ CONSTRUCTION DUMP
- ▶ FIRE AND EMERGENCY

Introducing the new International® MV™ Series, a medium duty truck that's built with everything you need to conquer your daily grind. It's designed and engineered to set new standards for quality and productivity, with a spacious new cab interior crafted through driver input for optimal comfort, control and safety. The MV Series offers the industry-leading intelligence of the Diamond Logic® electrical system, as well as OnCommand® Connection, the industry's first and only all-makes diagnostic system for unrivaled connectivity. With virtually limitless customization options, the MV Series provides the ideal truck for your demanding application.





KEY FEATURES:

- ▶ HSLA reinforced, cold-rolled steel cab for long-term durability
- ▶ New one-piece steel door frame and panels improve cab durability, structure and sealing
- ▶ New door, side glass and mirror designs improve lateral visibility and workplace safety
- ▶ All-new interior offers best-in-class room and driver-centric design for optimal productivity
- ▶ Driver controls can easily be operated while wearing gloves
- ▶ Available premium gauge cluster is customizable with virtual gauges
- ▶ All-new HVAC system, designed for reliability, includes a best-in-class MAX defrost feature
- ▶ Industry-leading Diamond Logic® electrical system
- ▶ Column-mounted shifter integrated with engine braking helps keep hands on the wheel



107" BBC SET-BACK FRONT AXLE

GVW

- ▶ 21,500 - 54,600 lbs.

Models/BBC/BA

- ▶ MV607: 107" BBC, 40" BA
- ▶ MV60H: 107" BBC, 40" BA (Low Profile)

Cab Configurations

- ▶ Day Cab
- ▶ Extended Cab
- ▶ Crew Cab

Wheelbase Options

- ▶ 128" - 311"

Axle Configurations

- ▶ 4x2, 6x4

Rear Axle

- ▶ Single Rear Axle (4x2)
 - Meritor: 13,500 - 30,000 lbs.
 - Dana Spicer: 13,500 - 30,000 lbs.
- ▶ Tandem Rear Axle (6x4)
 - Meritor: 34,000 - 40,000 lbs.
 - Dana Spicer: 40,000 lbs.
- ▶ Front Axle
 - Meritor: 8,000 - 14,600 lbs. (4x2, 6x4)
 - Dana Spicer: 8,000 - 14,000 lbs.

Frames

- ▶ High Strength Low-alloy Steel 50,000 - 80,000 PSI
- ▶ Heat Treated Alloy Steel 120,000 PSI
- ▶ Clean CA available for body mounting

Front Suspension

- ▶ Spring, Parabolic Taper Leaf: 8,000 - 14,600 lbs.

Rear Suspension

- ▶ Spring, Single Vari-Rate: 13,500 - 31,000 lbs.
- ▶ Tandem, 4-Spring Multileaf: 34,000 - 40,000 lbs.
- ▶ IROS Air Suspension available for Single and Tandem Axle

Electrical System

- ▶ Diamond Logic® Electrical System
- ▶ Alternators
 - 12 Volt 160 - 325 Amp.
- ▶ Battery Systems
 - 12 Volt, 2 to 3 Batteries
- ▶ Headlights
 - Long Life Halogen

Exhaust System

- ▶ Single, Horizontal, After-treatment Device Frame Mounted Right, Under Cab or Back of Cab, Horizontal or Vertical Tailpipe

Brakes

- ▶ Hydraulic Disc with Four Channel ABS, Optional Traction Control
- ▶ Air Brakes with ABS, Optional Traction Control, Optional Electronic Stability Program with Traction Control

Steering

- ▶ TRW/Ross Power
- ▶ Sheppard Power

Engines

- ▶ Cummins B6.7: 200 - 325 hp and 520 - 750 lb.-ft. of torque*
- ▶ Cummins L9: 260 - 350 hp and 720 - 1000 lb.-ft. of torque

Transmissions

- ▶ Eaton® Fuller: 6, 10 Speed Manual
- ▶ Eaton: Prociion™ 7 Speed Dual Clutch Automatic
- ▶ Allison: 1000, 2000, 3000 Series (HS, EVS, RDS, MH) Automatic
- ▶ Allison: 3000 TRV Series Automatic
- ▶ Eaton® Fuller: Advantage 10 Speed Fully Automated Manual

Fuel Tank

- ▶ 40 - 140 Gallon Non-Polished and Polished Aluminum, Mounted Right Side, Left Side or Dual Under Cab

DEF Tank

- ▶ 5-15 Gallon

Tires

- ▶ Continental, Michelin, Goodyear, Bridgestone, Hankook, Yokohama

* 340 hp and 700 lb.-ft. of torque / 360 hp and 800 lb.-ft. torque ratings available for emergency vehicles only

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice. TAD18001 1/2018

©2018 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.

LIMITED WARRANTY FOR MV MODEL SERIES

*Effective with vehicles built July 01, 2017 or later

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or ReNEWed® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE	Months	Miles/Km (000)
Basic Vehicle Warranty (See exceptions listed below)	24	Unlimited
Towing (First 90 days see below) (Vehicle Down Situations Only) (See exceptions listed below)	3	Unlimited
Note: Items not listed in warranty exceptions follow base warranty.		
WARRANTY EXCEPTIONS		
CHASSIS COVERAGE	Months	Miles/Km (000)
Frame side rails	84	Unlimited
Cab/cowl structure	60	Unlimited
Cab/cowl perforation corrosion	60	Unlimited
DRIVETRAIN COVERAGE	Months	Miles/Km (000)
Meritor Axles	36	Unlimited
Eaton Procion Transmission	24	Unlimited
MISCELLANEOUS COVERAGE	Months	Miles/Km (000)
Batteries	12	Unlimited
Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited

FIRST 90 DAYS FROM DELIVERY TO USER (DTU)

Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless specific coverage is stated above). Adjustments and Maintenance (e.g. aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Warranted by their respective manufacturers (e.g., non-International® brand engines, tires, Allison Transmissions, Eaton Hybrid components, lubricants, etc.)
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments

Repairs & Maintenance

- Maintenance-related items/repairs, or those, as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension

Other

- Vehicles sold and/or operated outside the United States and Canada
 - This exception does not apply to vehicles that meet current USA EPA emission standards, which were sold by an International dealer located in Mexico, if the vehicle is authorized by the U.S D.O.T to operate in long-haul, cross border transportation and the vehicle is only operated in the United States, Canada, and Mexico
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note: The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:

I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

 Customer Signature

 Date

 Owner's Address

 City

 State/Prov

 Postal Code

 Truck Model

 Vehicle Identification Number

 Engine Number

 Engine Serial Number

 Date Delivered to User (DTU)

 Odometer Reading at Delivery

IMPORTANT: The information contained in this Warranty Policy explains the coverage provided on your new International® vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty service.

Prepared For:

Jefferson Parish
Bruce Vosbein
200 Derbigny St.
Gretna, LA 70053-5850
(504)364 - 2678
Reference ID: N/A

Presented By:

ITA-NOLA, LLC
Ben Springer
301 HORD
HARAHAN LA 70123 -
(504)733-7711

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2021 HV507 SFA (HV507)

AXLE CONFIG:	6X4
APPLICATION:	Construction Dump
MISSION:	Requested GVWR: 52000. Calc. GVWR: 52000 Calc. Start / Grade Ability: 22.96% / 1.61% @ 55 MPH Calc. Geared Speed: 76.3 MPH
DIMENSION:	Wheelbase: 183.00, CA: 108.00, Axle to Frame: 59.00
ENGINE, DIESEL:	{Cummins L9 300} EPA 2017, 300HP @ 2000 RPM, 860 lb-ft Torque @ 1300 RPM, 2200 RPM Governed Speed, 300 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 3500 RDS} 5th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-4DFR} Single Reduction, 40,000-lb Capacity, w/.433"(11mm) Wall Housing Thickness, R Wheel Ends Gear Ratio: 4.63
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, TANDEM:	{Hendrickson RT-403} Walking Beam, 40,000-lb Capacity, 52" Axle Spacing, Multileaf Springs, with Rubber Center Bushings
FRAME REINFORCEMENT:	Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL
PAINT:	Cab schematic 100WK Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>
HV50700	Base Chassis, Model HV507 SFA with 183.00 Wheelbase, 108.00 CA, and 59.00 Axle to Frame.
1572	TOW HOOK, REAR (2)
1AND	AXLE CONFIGURATION {Navistar} 6x4
	<u>Notes</u> : Pricing may change if axle configuration is changed.
1CBU	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL
1GBP	FRAME REINFORCEMENT Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL
1LLA	BUMPER, FRONT Swept Back, Steel, Heavy Duty
1WGB	WHEELBASE RANGE 177" (450cm) Through and Including 226" (575cm)
2ARW	AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
3ADC	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity, with Shock Absorbers
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes) : SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes) : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4196	BRAKES, FRONT, AIR CAM 16.5" x 5", Includes 24 SqIn Long Stroke Brake Chambers
4619	TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck
	<u>Notes</u> : When electronic stability control is ordered with trailer connections on a 4x2 truck, please check the operator manual for trailer weight restrictions.
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System
4EBS	AIR DRYER {Bendix AD-9} with Heater
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
4EXV	BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM
4VKC	AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab
4VKJ	AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Back of Cab, Perpendicular to Rail

<u>Code</u>	<u>Description</u>
5AAA	STEERING COLUMN Stationary
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
5PSA	STEERING GEAR {Sheppard M100} Power
6DGZ	DRIVELINE SYSTEM {Dana Spicer} 1710 Main Driveline with 1710 Interaxle Shaft, for 6x4
7BEV	AFTERTREATMENT COVER Steel, Black
7BKS	EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab
7WAZ	TAIL PIPE (1) Turnback Type
7WDM	EXHAUST HEIGHT 10'
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	<u>Includes</u>
	: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
	: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
	: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
	: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
	: STARTER SWITCH Electric, Key Operated
	: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
	: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
	: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
	: WIRING, CHASSIS Color Coded and Continuously Numbered
8GXD	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, with Remote Sense
8HXT	HORN, AIR (2) Single Tone, Chrome, Roof Mounted, with Lanyard Pull Cord
8MJT	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (2) 12-Volt 1900CCA Total, Top Threaded Stud
8RMV	SPEAKERS (2) 6.5" Dual Cone Mounted in Doors
8RPT	RADIO AM/FM/WB/Clock/USB Input/Auxiliary Input
8THB	BACK-UP ALARM Electric, 102 dBA
8TKB	STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn & Tail Lights, Truck Lite Super 40 for Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes Incandescent License Plate Light
8TMG	TRAILER CONNECTION SOCKET 7-Way, Mounted at Rear of Frame, Wired for Turn Signals Combined with Stop, Compatible with Trailers with Combined Stop, Tail, Turn Lamps
8VAY	HORN, ELECTRIC Disc Style
8VUL	BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm
8WXG	STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

<u>Code</u>	<u>Description</u>
8XGT	TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
9HBM	GRILLE Stationary, Chrome
9WBC	FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
	<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WK"
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
11001	CLUTCH Omit Item (Clutch & Control)
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12EHU	ENGINE, DIESEL {Cummins L9 300} EPA 2017, 300HP @ 2000 RPM, 860 lb-ft Torque @ 1300 RPM, 2200 RPM Governed Speed, 300 Peak HP (Max)
12THT	FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed
	<u>Includes</u> : FAN Nylon
12UWZ	RADIATOR Cross Flow, Series System; 1228 SqIn Aluminum Radiator Core with Internal Water to Oil Transmission Cooler and 1167 In Charge Air Cooler
	<u>Includes</u> : DEAERATION SYSTEM with Surge Tank : HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber
12VBC	AIR CLEANER Single Element
12VHJ	FEDERAL EMISSIONS {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2020
12VXT	THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations
12XAT	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines
13AVG	TRANSMISSION, AUTOMATIC {Allison 3500 RDS} 5th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway
13WET	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released
13WYU	SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming
13XAK	PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission

<u>Code</u>	<u>Description</u>
14GVY	AXLE, REAR, TANDEM {Meritor MT-40-14X-4DFR} Single Reduction, 40,000-lb Capacity, w/.433"(11mm) Wall Housing Thickness, R Wheel Ends . Gear Ratio: 4.63
14UHC	SUSPENSION, REAR, TANDEM {Hendrickson RT-403} Walking Beam, 40,000-lb Capacity, 52" Axle Spacing, Multileaf Springs, with Rubber Center Bushings
14WAL	SUSPENSION/REAR-AXLE IDENTITY for Meritor Tandem Rear Axles with Bar-Pin Beam Attachment Type Suspensions
15LLZ	LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 41" Back of Cab
15LMR	FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor
15SGJ	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab
15WDG	DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab
16030	CAB Conventional, Day Cab
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16GDC	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16HLX	GAUGE, VOLTMETER Auxiliary Gauge, Located in Center Panel. Standard Cluster Also Includes Digital Voltage Readout
16KAV	SEAT, DRIVER {National} Non-Suspension, High Back with Integral Head Rest, Vinyl, with Fixed Back
16PJW	SEAT, TWO-MAN PASSENGER {National} Mid Back, Fixed Back, Vinyl, with Under Seat Storage
16SNL	MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width
	<u>Notes</u>
	: Mirror Dimensions are Rounded to the Nearest 0.5"
16VKB	CAB INTERIOR TRIM Classic, for Day Cab
	<u>Includes</u>
	: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger
	: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted
	: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16WSK	CAB REAR SUSPENSION Air Bag Type
16XCK	WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors
16XJN	INSTRUMENT PANEL Flat Panel
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab
27DTJ	WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DTJ	WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

<u>Code</u>	<u>Description</u>
29PAR	PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint
29PAS	PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint
7372135809	(2) TIRE, FRONT 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
7372135810	(8) TIRE, REAR 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive
Services Section:	
40128	WARRANTY Standard for HV507, HV50B, HV607 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A

HV507



Configuration: 107" BBC Set-Forward Front Axle
Application: Truck or Tractor
Engine: Cummins B6.7, L9



- ▶ MUNICIPAL PLOW
- ▶ CONSTRUCTION DUMP
- ▶ BRIDGE FORMULA APPLICATIONS
- ▶ 4X4 FIRE & EMERGENCY

The new HV507 from International® has the uptime, productivity and safety needed to deliver on the most demanding jobs. Its standard wide-track front axle provides excellent maneuverability and its compact 107" BBC and set-forward axle configuration is ideal for weight-sensitive bridge formula applications. The HV507 features a new, roomier interior with a powerful new HVAC system and new controls that help keep drivers comfortable and productive over long hours on the job. The advanced and dependable Diamond Logic® Electrical System offers custom, user-programmable interlocks to enhance operator safety. Whether you're restoring power following a major storm, clearing the way after a heavy snowfall or performing other key roadwork, the HV507 is a hard-working addition to your fleet.





KEY FEATURES:

- ▶ Heavy duty, double-sided galvanized steel cab for long-term durability
- ▶ New door, side glass and mirror designs improve lateral visibility and workplace safety
- ▶ All-new dash designed for the driver with more space for additional rocker switches
- ▶ Available premium gauge cluster designed with driver input is customizable with virtual gauges
- ▶ Best-in-class Diamond Logic® electrical system for all applications
- ▶ Easy-access column-mounted shifter integrated with engine braking helps keep hands on the wheel
- ▶ New industry-standard J1939 electrical system architecture and improved harnessing to maximize uptime
- ▶ All-new HVAC system, designed for reliability, now includes a high-performance MAX defrost feature
- ▶ .5" thick super single frame rail rated up to 3.35M RBM



107" BBC SET-FORWARD FRONT AXLE

GVW

- ▶ 53,000 - lbs. (4x2)
- ▶ 50,000 - lbs. (4x4)
- ▶ 68,000 - lbs. (6x4)
- ▶ 66,000 - lbs. (6x6)

Models/BBC/BA

- ▶ 107" BBC / 32.4" BA

Wheelbase Options

- ▶ 144 - 311"

Axle Configurations

- ▶ 4x2
- ▶ 4x4
- ▶ 6x4
- ▶ 6x6

Rear Axle

- ▶ SINGLE REAR AXLE (4x2)
 - Meritor
 - Single Reduction: 17,000 - 30,000 lbs.
 - Double Reduction: 26,000 - 38,000* lbs.
 - Two-Speed: 21,000 - 23,000 lbs.
 - Dana Spicer
 - Single Reduction: 17,500 - 31,000 lbs.
 - Two-Speed: 19,000 - 23,000* lbs.
- ▶ TANDEM REAR AXLE (6x4)
 - Meritor:
 - Single Reduction: 34,000 - 46,000 lbs.
 - Dana Spicer:
 - Single Reduction: 46,000 lbs.

Front Axle

- Dana Spicer
 - Non-Driving: 10,000 - 20,000 lbs.
- Meritor
 - Non-Driving: 10,000 - 22,000 lbs.
 - Driving: 10,000 - 18,000 lbs.
- Fabco
 - Driving: 10,000 - 20,000 lbs.

Frames

- ▶ Heat Treated Alloy Steel 120,000 PSI
- ▶ 11.25" x .5" thick super single rail

Front Suspension

- ▶ Spring Multileaf: 14,000 - 20,000 lbs.
- ▶ Parabolic Taperleaf: 8,000 - 22,000 lbs.

Rear Suspension

- ▶ Chalmers: 23,000 - 46,000 lbs.
- ▶ Hendrickson
 - RT: 34,000 - 46,000 lbs.
 - HAS: 40,000 - 46,000 lbs.
 - HMX: 40,000 - 46,000 lbs.
 - PRIMAAX: 20,000 - 46,000 lbs.
- ▶ Link: 46,000 lbs.

Electrical System

- ▶ ALTERNATORS
 - Bosch: 12 Volt, 160 - 200 Amp
 - Leece-Neville: 12 Volt, 160 - 325 Amp
 - Delco Remy: 12 Volt, 165 - 240 Amp
- ▶ BATTERY SYSTEMS
 - JCI: 12 Volt 1400 - 2100 CCA
 - Fleetrite®: 12 Volt 1320 - 3800 CCA
 - Deka: 12 Volt 2775 CCA

Exhaust System

- ▶ Single canister after-treatment device
- ▶ Frame Mounted Right Side, Back of Cab
- ▶ Short Horizontal Tailpipe

Brakes

- ▶ Air Drum Brakes with ABS, Optional Traction Control, Optional Electronic Stability Program with Traction Control
- ▶ Air Disc Brakes

Power Steering

- ▶ Single Power
- ▶ Dual Power on Front Axle 16,000 lbs. and Above

Engines

- ▶ Cummins® B6.7: Up to 360** hp, 800 lb.-ft. of torque
- ▶ Cummins® L9: Up to 450** hp, 1250 lb. -ft of torque

Transmissions

- ▶ Eaton® Fuller: 6-, 10-, 13-Speed Manual
- ▶ Eaton UltraShift+®: 10-Speed Automated Manual
- ▶ Eaton Fuller Advantage™ Series: 10-speed Automated Manual
- ▶ Allison: 2000, 3000 Series (HS, EVS, RDS) Automatic

Fuel Tanks

- ▶ 40 - 120 Gallons, Single or Dual, Non-Polished or Polished Aluminum, Mounted Right or Left Side Under Cab

Tires

- ▶ Continental, Michelin, Goodyear, Bridgestone

* Application Restriction

** Higher ratings limited to fire and rescue applications

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice. TAD17026 9/2017

©2017 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.

LIMITED WARRANTY FOR HV MODELS

HV507 & HV607

*Effective with vehicles built July 01, 2017 or later

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or ReNEWed® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE	Months	Miles/Km (000)
Basic Vehicle Warranty (See exceptions listed below)	12	Unlimited
Towing (First 90 days see below) (Vehicle Down Situations Only) (See exceptions listed below)	3	Unlimited
Note: Items not listed in warranty exceptions follow base warranty.		
WARRANTY EXCEPTIONS		
CHASSIS COVERAGE	Months	Miles/Km (000)
Frame side rails	84	Unlimited
Cab/cowl structure	60	Unlimited
Cab/cowl perforation corrosion	60	Unlimited
DRIVETRAIN COVERAGE	Months	Miles/Km (000)
Spicer axles, Propeller shaft, Eaton clutch, TTC Transmission	24	Unlimited
Eaton/Fuller Transmission	24	Unlimited
Meritor Axles	24	Unlimited
MISCELLANEOUS COVERAGE	Months	Miles/Km (000)
Batteries	12	Unlimited
Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited
FIRST 90 DAYS FROM DELIVERY TO USER (DTU)		
Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless specific coverage is stated above). Adjustments and Maintenance (such as aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).		

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Components warranted by their respective manufacturers (such as, non-International® brand engines, tires, Allison Transmissions, lubricants, etc.)
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments.

Repairs & Maintenance

- Maintenance-related items/repairs, or those needed as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension.

Other

- Vehicles sold and/or operated outside the United States and Canada
 - This exception does not apply to vehicles that meet current USA EPA emission standards, which were sold by an International dealer located in Mexico, if the vehicle is authorized by the U.S D.O.T to operate in long-haul, cross border transportation and the vehicle is only operated in the United States, Canada, and Mexico
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note:The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

Revised 4/1/2019

Telematics Data Disclosure

Your new Navistar vehicle is automatically equipped with Telematics. Navistar, Inc. or its affiliates will collect and send diagnostic and system data from your vehicle and use it for various purposes as further set forth in our Privacy Policy, posted at www.oncommandconnection.com, such as improving uptime for your vehicle, improving our vehicles in the future and reducing warranty events. By accepting this Limited Warranty, you consent to our collection and use of data from your vehicle as set forth at www.oncommandconnection.com on behalf of yourself and any vehicle operators and passengers. Your use and access to any related data subscription service from Navistar, Inc. or its affiliates, such as OnCommandConnection, are subject to additional Terms of Service. You will receive additional information follow purchase regarding any such subscriptions as well as your ability to opt-out of data collection.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:

I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

Customer Signature	Date		
Owner's Address	City	State/Prov	Postal Code
Truck Model	Vehicle Identification Number		
Engine Number	Engine Serial Number		
Date Delivered to User (DTU)	Odometer Reading at Delivery		

IMPORTANT:The information contained in this Warranty Policy explains the coverage provided on your new International® vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.

LIMITED WARRANTY FOR HV MODELS

HV507 & HV607

***Effective with vehicles built July 01, 2017 or later**

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or ReNEWed® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE	Months	Miles/Km (000)
Basic Vehicle Warranty (See exceptions listed below)	12	Unlimited
Towing (First 90 days see below) (Vehicle Down Situations Only) (See exceptions listed below)	3	Unlimited
Note: Items not listed in warranty exceptions follow base warranty.		
WARRANTY EXCEPTIONS		
CHASSIS COVERAGE	Months	Miles/Km (000)
Frame side rails	84	Unlimited
Cab/cowl structure	60	Unlimited
Cab/cowl perforation corrosion	60	Unlimited
DRIVETRAIN COVERAGE	Months	Miles/Km (000)
Spicer axles, Propeller shaft, Eaton clutch, TTC Transmission	24	Unlimited
Eaton/Fuller Transmission	24	Unlimited
Meritor Axles	24	Unlimited
MISCELLANEOUS COVERAGE	Months	Miles/Km (000)
Batteries	12	Unlimited
Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited
FIRST 90 DAYS FROM DELIVERY TO USER (DTU)		
Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless specific coverage is stated above). Adjustments and Maintenance (such as aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).		

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Components warranted by their respective manufacturers (such as, non-International® brand engines, tires, Allison Transmissions, lubricants, etc.)
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments.

Repairs & Maintenance

- Maintenance-related items/repairs, or those needed as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension.

Other

- Vehicles sold and/or operated outside the United States and Canada
 - This exception does not apply to vehicles that meet current USA EPA emission standards, which were sold by an International dealer located in Mexico, if the vehicle is authorized by the U.S D.O.T to operate in long-haul, cross border transportation and the vehicle is only operated in the United States, Canada, and Mexico
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note:The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

Revised 4/1/2019

Telematics Data Disclosure

Your new Navistar vehicle is automatically equipped with Telematics. Navistar, Inc. or its affiliates will collect and send diagnostic and system data from your vehicle and use it for various purposes as further set forth in our Privacy Policy, posted at www.oncommandconnection.com, such as improving uptime for your vehicle, improving our vehicles in the future and reducing warranty events. By accepting this Limited Warranty, you consent to our collection and use of data from your vehicle as set forth at www.oncommandconnection.com on behalf of yourself and any vehicle operators and passengers. Your use and access to any related data subscription service from Navistar, Inc. or its affiliates, such as OnCommandConnection, are subject to additional Terms of Service. You will receive additional information follow purchase regarding any such subscriptions as well as your ability to opt-out of data collection.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:

I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

Customer Signature	Date		
Owner's Address	City	State/Prov	Postal Code
Truck Model	Vehicle Identification Number		
Engine Number	Engine Serial Number		
Date Delivered to User (DTU)	Odometer Reading at Delivery		

IMPORTANT:The information contained in this Warranty Policy explains the coverage provided on your new International® vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.

Prepared For:

Jefferson Parish
 Bruce Vosbein
 200 Derbigny St.
 Gretna, LA 70053-5850
 (504)364 - 2678
 Reference ID: 52K HD

Presented By:

ITA-NOLA, LLC
 Ben Springer
 301 HORD
 HARAHA LA 70123 -
 (504)733-7711

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2021 HV613 SBA (HV613)

AXLE CONFIG:	6X4
APPLICATION:	Construction Dump
MISSION:	Requested GVWR: 52000. Calc. GVWR: 52000 Calc. Start / Grade Ability: 47.14% / 3.12% @ 55 MPH Calc. Geared Speed: 84.3 MPH
DIMENSION:	Wheelbase: 177.00, CA: 109.90, Axle to Frame: 57.00
ENGINE, DIESEL:	{International A26} EPA 2017, 390HP @ 1700 RPM, 1450 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 390 Peak HP (Max)
TRANSMISSION, MANUAL:	{Eaton Fuller Advantage FAO-14810C-EA3} 10-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Electronic Shift Controls and Clutch Actuation, Air Range Shift, Internal Lube Oil Pump, Hill Start Aid
CLUTCH:	{Eaton Fuller ECA-1850} Two-Plate, Ceramic, 7-Spring with Pre-Damper, 15.5" Diameter, with Adjustment-Free Feature, 1850 lb-ft Torque Capacity
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-5DFR} Single Reduction, 40,000-lb Capacity, w/.5"(12.7mm) Wall Housing Thickness, R Wheel Ends Gear Ratio: 4.11
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(9) 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, TANDEM:	{Hendrickson RT-403} Walking Beam, 40,000-lb Capacity, 52" Axle Spacing, Multileaf Springs, with Rubber Center Bushings
FRAME REINFORCEMENT:	Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL
PAINT:	Cab schematic 100WN Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>
HV61300	Base Chassis, Model HV613 SBA with 177.00 Wheelbase, 109.90 CA, and 57.00 Axle to Frame.
1572	TOW HOOK, REAR (2)
1AND	AXLE CONFIGURATION {Navistar} 6x4
	<u>Notes</u> : Pricing may change if axle configuration is changed.
1CBU	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL
1GBP	FRAME REINFORCEMENT Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL
1LLA	BUMPER, FRONT Swept Back, Steel, Heavy Duty
1WHN	WHEELBASE RANGE 152" (385cm) Through and Including 181" (460cm)
1WMA	CROSSMEMBER, INTERMEDIATE (1) 5-Piece in lieu of Each Single Dogbone with 4x2 & 4x4 Chassis; Each Double Dogbone with 6x4, 6x6 & 8x6 Tridem Chassis
2ARW	AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
3ADC	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity, with Shock Absorbers
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes) : SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes) : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4196	BRAKES, FRONT, AIR CAM 16.5" x 5", Includes 24 SqIn Long Stroke Brake Chambers
4619	TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck
	<u>Notes</u> : When electronic stability control is ordered with trailer connections on a 4x2 truck, please check the operator manual for trailer weight restrictions.
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4AZJ	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control
4EBS	AIR DRYER {Bendix AD-9} with Heater
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
4EXV	BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
4SPM	AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM
4VKA	AIR DRYER LOCATION Mounted Outside Right Rail, Back of Cab

<u>Code</u>	<u>Description</u>
4VKJ	AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Back of Cab, Perpendicular to Rail
5AAA	STEERING COLUMN Stationary
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
5PSA	STEERING GEAR {Sheppard M100} Power
6DHB	DRIVELINE SYSTEM {Dana Spicer} 1810HD Main Driveline with 1710 Interaxle Shaft, for 6x4
7BEV	AFTERTREATMENT COVER Steel, Black
7BKS	EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab
7SDK	ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch
7WAZ	TAIL PIPE (1) Turnback Type
7WDM	EXHAUST HEIGHT 10'
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	<u>Includes</u>
	: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
	: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
	: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
	: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
	: STARTER SWITCH Electric, Key Operated
	: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
	: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
	: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
	: WIRING, CHASSIS Color Coded and Continuously Numbered
8GXJ	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount
8HAB	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn
8HXT	HORN, AIR (2) Single Tone, Chrome, Roof Mounted, with Lanyard Pull Cord
8MSG	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud
8RMV	SPEAKERS (2) 6.5" Dual Cone Mounted in Doors
8RPT	RADIO AM/FM/WB/Clock/USB Input/Auxiliary Input
8THB	BACK-UP ALARM Electric, 102 dBA
8TMG	TRAILER CONNECTION SOCKET 7-Way, Mounted at Rear of Frame, Wired for Turn Signals Combined with Stop, Compatible with Trailers with Combined Stop, Tail, Turn Lamps
8VAY	HORN, ELECTRIC Disc Style
8VUL	BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
8WXG	STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

<u>Code</u>	<u>Description</u>
8XGT	TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
9585	FENDER EXTENSIONS Rubber
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
9HBM	GRILLE Stationary, Chrome
9HBN	INSULATION, SPLASH PANELS for Sound Abatement
9WBK	FRONT END Tilting, Fiberglass, with Three Piece Construction, Includes Long Hood
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
	<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WN"
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
11MGP	CLUTCH {Eaton Fuller ECA-1850} Two-Plate, Ceramic, 7-Spring with Pre-Damper, 15.5" Diameter, with Adjustment-Free Feature, 1850 lb-ft Torque Capacity
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12BDZ	ENGINE, DIESEL {International A26} EPA 2017, 390HP @ 1700 RPM, 1450 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 390 Peak HP (Max)
12THT	FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed
	<u>Includes</u> : FAN Nylon
12VBC	AIR CLEANER Single Element
12VHK	FEDERAL EMISSIONS {International A26} EPA, OBD and GHG Certified for Calendar Year 2020
12WTA	FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations
12XBD	RADIATOR Aluminum; Welded, Front to Back CrossFlow System, 1292 SqIn, 1008 SqIn CAC
	<u>Includes</u> : DEAERATION SYSTEM with Surge Tank : HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber
13GYC	TRANSMISSION, MANUAL {Eaton Fuller Advantage FAO-14810C-EA3} 10-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Electronic Shift Controls and Clutch Actuation, Air Range Shift, Internal Lube Oil Pump, Hill Start Aid
13WET	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter
13WLW	TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints
13XAS	PTO LOCATION Customer Intends to Install PTO at Rear of Transmission
14GVZ	AXLE, REAR, TANDEM {Meritor MT-40-14X-5DFR} Single Reduction, 40,000-lb Capacity, w/.5"(12.7mm) Wall Housing Thickness, R Wheel Ends . Gear Ratio: 4.11
14UHC	SUSPENSION, REAR, TANDEM {Hendrickson RT-403} Walking Beam, 40,000-lb Capacity, 52" Axle Spacing, Multileaf Springs, with Rubber Center Bushings

<u>Code</u>	<u>Description</u>
14WAL	SUSPENSION/REAR-AXLE IDENTITY for Meritor Tandem Rear Axles with Bar-Pin Beam Attachment Type Suspensions
15DYP	DEF TANK 9.5 US Gal (36L) Capacity, Frame Mounted Outside Left Rail, Under Cab
15LKU	FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor
15LLP	LOCATION FUEL/WATER SEPARATOR Mounted Inside Left Rail, Back of Cab
15SGJ	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab
15WCS	FUEL COOLER Less Thermostat; Mounted in Front of Cooling Module
16030	CAB Conventional, Day Cab
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16GDC	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16KAV	SEAT, DRIVER {National} Non-Suspension, High Back with Integral Head Rest, Vinyl, with Fixed Back
16PJW	SEAT, TWO-MAN PASSENGER {National} Mid Back, Fixed Back, Vinyl, with Under Seat Storage
16SNL	MIRRORS (2) C-Loop, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width
	<u>Notes</u>
	: Mirror Dimensions are Rounded to the Nearest 0.5"
16VKB	CAB INTERIOR TRIM Classic, for Day Cab
	<u>Includes</u>
	: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger
	: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted
	: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16WSK	CAB REAR SUSPENSION Air Bag Type
16XCK	WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors
16XJN	INSTRUMENT PANEL Flat Panel
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab
26DTJ	WHEEL, SPARE, DISC {Maxion 90541} 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted
27DTJ	WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DTJ	WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
29007	TIRE, SPARE Equal to Model Standard
29PAR	PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint

<u>Code</u>	<u>Description</u>
29PAS	PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint
7372135809	(2) TIRE, FRONT 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
7372135810	(9) TIRE, REAR 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive

Services Section:

40127	WARRANTY Standard for HV513, HV613 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2030A
-------	---

HV613



Configuration: 113" BBC, Set-Back Front Axle
Application: Truck or Tractor
Engine: International A26



- ▶ REFUSE
- ▶ HEAVY CONSTRUCTION DUMP
- ▶ RECOVERY
- ▶ CONCRETE MIXER

International® trucks have always answered the call for the toughest jobs around. Now there's a new breed of vocational truck that redefines the standard for uptime and productivity. Introducing the new International HV™ Series. The HV613 offers the superior maneuverability of a set-back, wide-track front axle. It also includes the industry standard for operator safety, versatility and dependability in its Diamond Logic® Electrical System. Plus, the HV613 reaches new levels of uptime, efficiency and performance with its advanced new A26™ engine and new interior that includes new, driver-focused controls and a new class-leading HVAC system.





KEY FEATURES:

- ▶ New International® A26™ 12.4L engine with class-leading two-year unlimited mile warranty
- ▶ Wide-track axles providing maximum maneuverability and up to a 50-degree wheel cut
- ▶ New door, side glass and mirror designs improve lateral visibility and workplace safety
- ▶ All-new dash designed for the driver with more space for additional rocker switches
- ▶ Available premium gauge cluster designed with driver input is customizable with virtual gauges
- ▶ Best-in-class Diamond Logic® electrical system with new industry-standard J1939 architecture
- ▶ Easy-access column-mounted shifter integrated with engine braking helps keep hands on the wheel
- ▶ All-new HVAC system, designed for reliability, now includes a high-performance MAX defrost feature



113" BBC SET-BACK FRONT AXLE

GVW

- ▶ 53,000 - lbs. (4x2)
- ▶ 74,000 - lbs. (6x4)
- ▶ 73,000 - lbs. (8x6)

Models/BBC/BA

- ▶ 113" BBC / 45.9" BA

Wheelbase Options

- ▶ 146 - 311"

Axle Configurations

- ▶ 4x2
- ▶ 6x4
- ▶ 8x6 Tridem

Rear Axle

- ▶ SINGLE REAR AXLE (4x2)
 - Meritor
 - Single Reduction: 20,000 - 30,000 lbs.
 - Double Reduction: 26,000 - 38,000* lbs.
 - Two-Speed: 23,000 lbs.
 - Dana Spicer
 - Single Reduction: 23,000 - 31,000 lbs.
 - Two-Speed: 23,000 lbs.
- ▶ TANDEM REAR AXLE (6x4)
 - Meritor:
 - Single Reduction: 40,000 - 52,000 lbs.
 - Dana Spicer:
 - Single Reduction: 46,000 lbs.
- ▶ TRIDEM REAR AXLE (8x6)
 - Meritor:
 - Single Reduction: 53,000 lbs.

Front Axle

- ▶ Dana Spicer
 - Non-Driving: 12,000 - 22,000 lbs.
- ▶ Meritor
 - Non-Driving: 12,000 - 22,000 lbs.

Frames

- ▶ Heat Treated Alloy Steel 120,000 PSI

Front Suspension

- ▶ Spring Multileaf: 14,000 - 20,000 lbs.
- ▶ Parabolic Taperleaf: 12,000 - 22,000 lbs.

Rear Suspension

- ▶ Chalmers: 23,000 - 52,000 lbs.
- ▶ Hendrickson
 - RT: 40,000 - 52,000 lbs.
 - HAS: 23,000 - 46,000 lbs.
 - HMX: 40,000 - 46,000 lbs.
 - PRIMAAX: 23,000 - 46,000 lbs., 69,000 lbs. (Tridem)
- ▶ Link: 46,000 lbs.
- ▶ International: 20,000 - 40,000* lbs.

Electrical System

- ▶ ALTERNATORS
 - Bosch: 12 Volt, 160 - 200 Amp
 - Leece-Neville: 12 Volt, 160 - 325 Amp
 - Delco Remy: 12 Volt, 165 - 240 Amp
- ▶ BATTERY SYSTEMS
 - JCI: 12 Volt 2100 CCA
 - Fleetrite®: 12 Volt 1950 - 3800 CCA
 - Deka: 12 Volt 2775 CCA

Exhaust System

- ▶ Single canister after-treatment device
- ▶ Frame Mounted Right Side, Back of, or Under Cab
- ▶ Single Vertical Tailpipe, Right Side Back of Cab

Brakes

- ▶ Air Drum Brakes with ABS, Optional Traction Control, Optional Electronic Stability Program with Traction Control
- ▶ Air Disc Brakes

Power Steering

- ▶ Single Power
- ▶ Dual Power on Front Axle 16,000 lbs. and Above

Engine

- ▶ International A26: Up to 475 hp, 1700 lb. -ft of torque

Transmissions

- ▶ Eaton® Fuller: 10-, 11-, 13-, 15-Speed Manual
- ▶ Eaton UltraShift+®: 10-, 11-, 13-, 18-Speed Automated Manual
- ▶ Eaton Fuller Advantage™ Series: 10-speed Automated Manual
- ▶ Allison: 3000, 4000 Series (HS, EVS, RDS, HS*) Automatic

Fuel Tanks

- ▶ 40 - 120 Gallons, Single or Dual, Non-Polished or Polished Aluminum, Mounted Right or Left Side Under Cab

Tires

- ▶ Continental, Michelin, Goodyear, Bridgestone

* Application Restriction

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice. TAD17025 9/2017

©2017 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.

LIMITED WARRANTY FOR HV MODELS HV513 & HV613

***Effective with vehicles built July 01, 2017 or later**

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or ReNEWed® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE	Months	Miles/Km (000)
Basic Vehicle Warranty ((See exceptions listed below)	12	Unlimited
Towing (Vehicles with International A26 engine failures only)	24	Unlimited
Towing (First 90 days see below) (Vehicle Down Situations Only) (See exceptions listed below)	3	Unlimited
Note: Items not listed in warranty exceptions follow base warranty.		
WARRANTY EXCEPTIONS		
CHASSIS COVERAGE	Months	Miles/Km (000)
Frame side rails	60	Unlimited
Cab/cowl structure	60	Unlimited
Cab/cowl perforation corrosion	60	Unlimited
ENGINE COVERAGE	Months	Miles/Km (000)
Non-Rescue Applications		
International A26	24	Unlimited
International A26 Major Components	60	500/800
<i>Major Components are cylinder block, main bearing bolts, cylinder head casting and capscrews, crankshaft, camshaft, cam follower, connecting rods/caps/bolts, intake manifold castings, and gear train gears.</i>		
Rescue Application Only (Fire Truck, Ambulance, Emergency)		
International A26	60	100/160
DRIVETRAIN COVERAGE	Months	Miles/Km (000)
Rear Axle Weight Ratings Greater than 52,000 lb		
Front Axle Assembly	12	Unlimited
Rear Axle and Differential	12	Unlimited
Transmission	12	Unlimited
Rear Axle Weight Ratings of 52,000 lb and Less		
Front Axle Assembly	36	300/480
Rear Axle and Differential	36	300/480
Transmission	36	300/480
MISCELLANEOUS COVERAGE	Months	Miles/Km (000)

Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited
FIRST 90 DAYS FROM DELIVERY TO USER (DTU)		
Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless specific coverage is stated above). Adjustments and Maintenance (such as aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).		

Navistar Diesel Engine Coverage Includes:

Engine block, cylinder heads, internally lubricated components fuel pump, high pressure pump, turbocharger, water pump, air compressor, injectors/nozzles; electronic engine modules, engine relays, engine sensors and regulators required for electronic engine operation, and certain aftertreatment components. Excluding: attaching accessories (e.g., fan clutch, alternator, starter, etc.), and externally mounted electrical and filtration systems.

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Components warranted by their respective manufacturers (such as non-International® brand engines, tires, Allison Transmissions, lubricants,
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments

Repairs & Maintenance

- Maintenance-related items/repairs, or those needed as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension

Other

- Vehicles sold and/or operated outside the United States and Canada
 - This exception does not apply to vehicles that meet current USA EPA emission standards, which were sold by an International dealer located in Mexico, if the vehicle is authorized by the U.S D.O.T to operate in long-haul, cross border transportation and the vehicle is only operated in the United States, Canada, and Mexico
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses

- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note:The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

Revised 4/1/2019

Telematics Data Disclosure

Your new Navistar vehicle is automatically equipped with Telematics. Navistar, Inc. or its affiliates will collect and send diagnostic and system data from your vehicle and use it for various purposes as further set forth in our Privacy Policy, posted at www.oncommandconnection.com, such as improving uptime for your vehicle, improving our vehicles in the future and reducing warranty events. By accepting this Limited Warranty, you consent to our collection and use of data from your vehicle as set forth at www.oncommandconnection.com on behalf of yourself and any vehicle operators and passengers. Your use and access to any related data subscription service from Navistar, Inc. or its affiliates, such as OnCommandConnection, are subject to additional Terms of Service. You will receive additional information follow purchase regarding any such subscriptions as well as your ability to opt-out of data collection.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:

I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

<hr/>		<hr/>	
Customer Signature		Date	
<hr/>		<hr/>	
Owner's Address	City	State/Prov	Postal Code
<hr/>		<hr/>	
Truck Model		Vehicle Identification Number	
<hr/>		<hr/>	
Engine Number		Engine Serial Number	
<hr/>		<hr/>	
Date Delivered to User (DTU)		Odometer Reading at Delivery	

IMPORTANT:The information contained in this Warranty Policy explains the coverage provided on your new International® vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.