

HOSE FITTINGS

Cam & Groove

Aluminum – Stainless Steel – Carbon Steel – Brass – Poly

Cam & Groove quick connect couplings are designed for rapid connection/disconnection of hoses.



Aluminum Camlocks

- Die Cast SS 304 Arms, Steel safety pins, Steel rings, NBR gasket
- Multiple serrations on hose shank for better coupling retention

Interchangeable with all manufacturers who are compliant to the A-A59326 specification.

Pressure ratings for all: 1" through 4" 150psi
6" 2 cam 75psi / 4 cam 150psi

Description	Aluminum Part #					
Part	1"	1-1/2"	2"	3"	4"	6"
A	030-01016-816CI	030-01024-824CI	030-01032-832CI	030-01048-848CI	030-01064-864CI	030-01096-896CI
B	030-02016-816CI	030-02024-824CI	030-02032-832CI	030-02048-848CI	030-02064-864CI	030-02096-896CI
C	030-03016-816CI	030-03024-824CI	030-03032-832CI	030-03048-848CI	030-03064-864CI	030-03096-896CI
D	030-04016-816CI	030-04024-824CI	030-04032-832CI	030-04048-848CI	030-04064-864CI	030-04096-896CI
E	030-05016-816CI	030-05024-824CI	030-05032-832CI	030-05048-848CI	030-05064-864CI	030-05096-896CI
F	030-06016-816CI	030-06024-824CI	030-06032-832CI	030-06048-848CI	030-06064-864CI	030-06096-896CI
DC	030-07016-800CI	030-07024-800CI	030-07032-800CI	030-07048-800CI	030-07064-800CI	030-07096-800CI
DP	030-08016-800CI	030-08024-800CI	030-08032-800CI	030-08048-800CI	030-08064-800CI	030-08096-800CI

Description	(SS 316) Stainless Steel Part #			
Part	1"	2"	3"	4"
C	030-03016-416I	030-03032-432I	030-03048-448I	030-03064-464I
E	030-05016-416I	030-05032-432I	030-05048-448I	030-05064-464I

Description	Carbon Steel Part #
Part	4"
C	030-03064-164I
E	030-05064-164I

WARNING: UNDER NO CIRCUMSTANCES should Cam and Groove couplings be used for compressed air or steam service!

Note: JGB couplings are designed to comply with the dimensional requirements of MIL A-A59326.