

DATE: 6/17/2019

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00127017

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETNA, LA. 70054-0009
504-364-2678

VENDOR: 27118 BLANK BID COPY VENDOR

BUYER: BBELLOW

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH	
INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES	<u>7-1-19</u>
INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK	_____
INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK	_____

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: 13

NUMBER: _____

NUMBER: _____

NUMBER: _____

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***	
FIRM NAME: <u>D & S Steering Service, Inc.</u>	
SIGNATURE: <u>[Signature]</u> (Must be signed here)	TITLE: <u>Vice president</u>
PRINT OR TYPE NAME: <u>David Springer</u>	
ADDRESS: <u>4129 Euphrosine St.</u>	
CITY, STATE: <u>New Orleans, LA</u>	ZIP: <u>70125</u>
TELEPHONE: <u>(504) 579-3328</u>	FAX: <u>()</u>
EMAIL ADDRESS: <u>dpspringiub@gmail.com</u>	

TOTAL PRICE OF ALL BID ITEMS: \$ 1776.00

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	600.00	EA	<p>Purchase of Grease</p> <p>0010 Grease, lithium complex, multi-purpose, 14 ounce cartridge, extreme pressure, high temperature, base oil viscosity 220 at 40 degrees C and 18.3 at 100 degrees C, Albida EP no. 2, Shell no. S3 V220C 2 (0017010)</p> <p>will provide equivalent Product: Mag1, part # 733. Spec sheet is attached.</p>	2.96	1776.00

MAG 1® MULTI-PURPOSE LITHIUM GREASE WITH MOLY

GREASES INDUSTRIAL LUBRICANTS AND GREASES



Featuring MAG 1® with FMX® Technology – Friction Management for Xtreme protection™. MAG 1® provides unsurpassed protection and performance.

MAG 1® Multi-Purpose Lithium Grease with Moly is suitable for use in a wide variety of applications, MAG 1 Super Lithium EP Moly Grease has been fortified with molybdenum disulfide and graphite to provide protection against seizure under high loads and severe shock load conditions.

POWERFUL ANTI-FRICTION, ANTI-WEAR CHEMISTRY

MAG 1® provides outstanding control of friction and wear. Advanced molecules bond together to create a wear-resistant shield that works to build barriers that reduce friction and wear.

WITHSTANDS THE MOST EXTREME CONDITIONS

MAG 1® provides unsurpassed protection even in the harshest conditions of hot and cold climates, pressure, micropitting or oxidation.

EVOLUTIONARY PERFORMANCE™

OEMs continue to evolve equipment designs and operating conditions are becoming more severe. These changes increase stress on plain bearings, roller bearings, gears and couplings. One brand has evolved right alongside today's equipment – MAG 1®. Only the most advanced greases meet the difficult challenges of effectively balancing performance, strength and durability.

MAG 1® Grease is specially engineered and formulated to provide:

PERFORMANCE

- Protection for equipment life and reliability.

STRENGTH

- Excellent wear, pitting and corrosion protection.

DURABILITY

- Longer equipment life.
- Optimized maintenance cost and uptime.

TYPICAL PROPERTIES

Color		Grey
Dropping Point, °C (°F), Min.	ASTM D 2265	177°C (350°F)
Four Ball EP Weld Point, Min	ASTM D2596	250
Four Ball Load Wear Index, Kgf	ASTM D2596	40
Four Ball Wear, mm Scar Dia	ASTM D2266	0.6
NLGI Grade		2
Oil Separation, % Loss Max.	ASTM D1742	10
Operating Temp Range		-25 to 250°F
Oxidation Stability, PSI loss	ASTM D942	5
Roll Stability, % Change	ASTM D1831	10
Rust Prevention	ASTM D1743	Pass
Thickener Type		Lithium
Timken OK Load, LB	ASTM D2509	45
Water Washout % Loss	ASTM 1264	10
Worked Penetration @ 77°F	ASTM D217	265-295

CONTAINER/BULK AVAILABILITY

35lb Bucket	Product Number - 00735
10/14oz Tube	Product Number - 00733

Information accurate as of June 6, 2019