


# Shackles

## Screw Pin Chain Shackles

- Forged Carbon Steel with Alloy Pins
- Hot Dip Galvanized

ITEM#	Size in Inches (A)	Working Load Limit in Tons (Vertical)	Pin Diam. in Inches (B)	Approx. Wt. Each in Pounds	Dimensions in Inches		
					C	D	E
SHA14LRC	1/4	1/2	5/16	.10	.88	.47	.61
SHA516LRC	5/16	3/4	3/8	.19	1.03	.53	.75
SHA38LRC	3/8	1	7/16	.30	1.25	.66	.91
SHA716LRC	7/16	1 1/2	1/2	.43	1.44	.75	1.06
SHA12LRC	1/2	2	5/8	.59	1.63	.81	1.19
SHA58LRC	5/8	3 1/4	3/4	1.25	2.00	1.06	1.50
SHA34LRC	3/4	4 3/4	7/8	2.63	2.38	1.25	1.81
SHA78LRC	7/8	6 1/2	1	3.16	2.81	1.44	2.09
SHA1LRC	1	8 1/2	1 1/8	4.75	3.19	1.69	2.38



Screw Pin Chain Shackles meet the requirements of Federal Specification RR-C-271D Type IVB, Grade A, Class 2.


**Angle loads must be applied to the bow of an anchor shackle only (reduce WLL by 30% at 45 degree angle). Inspect before each use. Never use damaged, cracked, rusted or worn items.**

**Do not use screw pin shackles if the pin can roll under load and unscrew.**

## Screw Pin Anchor

- Forged Carbon Steel with Alloy Pins
- Hot Dip Galvanized

ITEM#	Size in Inches (A)	Working Load Limit in Tons (Vertical)	Pin Diam. in Inches (B)	Approx. Wt. Each in Pounds	C	D	E	F
SHA316LR	*3/16	1/3	1/4	.06	.88	.38	.56	.63
SHA14LR	*1/4	1/2	5/16	.10	1.06	.47	.66	.75
SHA516LR	*5/16	3/4	3/8	.19	1.25	.53	.81	.84
SHA38LR	*3/8	1	7/16	.30	1.44	.63	.91	1.00
SHA716LR	*7/16	1 1/2	1/2	.38	1.69	.75	1.06	1.13
SHA12LR	*1/2	2	5/8	.70	1.88	.81	1.31	1.25
SHA58LR	*5/8	3 1/4	3/4	1.37	2.44	1.06	1.56	1.69
SHA34LR	*3/4	4 3/4	7/8	2.35	2.88	1.19	1.88	1.94
SHA78LR	*7/8	6 1/2	1	3.62	3.38	1.44	2.13	2.19
SHA1LR	*1	8 1/2	1 1/8	5.03	3.81	1.69	2.38	2.63
SHA118LR	*1 1/8	9 1/2	1 1/4	7.41	4.25	1.75	2.63	2.88
SHA114LR	*1 1/4	12	1 3/8	9.50	4.69	2.00	3.00	3.13
SHA138LR	1 3/8	13 1/2	1 1/2	13.53	5.31	2.13	3.25	3.50
SHA112LR	1 1/2	17	1 5/8	17.20	5.69	2.31	3.50	3.75
SHA134LR	1 3/4	25	2	27.78	7.06	2.88	4.25	4.88
SHA2LR	2	35	2 1/4	45.00	7.75	3.31	4.88	5.44
SHA212LR	2 1/2	55	2 3/4	85.75	10.75	4.13	5.88	7.25



Screw Pin Anchor Shackles meet the requirements of Federal Specification RR-C-271D, Type IV A, Grade A, Class 2.

**• Commercial grade "fishing shackles" also available**  
**Commercial grade shackles are unrated and not approved for lifting or towing and have no working load.**

[Back To Top^](#)