

DATE: 5/12/2021

Page: 6

BID NO.: 50-00134464

BID FORM
Non Public Works

All Public Work Projects are required to use the Louisiana Uniform Public Work Bid Form

All prices must be held firm unless an escalation provision is requested in this bid. Jefferson Parish will allow one escalation during the term of the contract, which may not exceed the U.S. Bureau of Labor Statistics National Index for all Urban Consumers, unadjusted 12 month figure. The most recently published figure issued at the time an adjustment is requested will be used. A request must be made in writing by the vendor, and the escalation will only be applied to purchases made after the request is made.

Are you requesting an escalation provision?

YES _____ NO X

MAXIMUM ESCALATION PERCENTAGE REQUESTED _____%

INITIAL BID PRICES WILL REMAIN FIRM THROUGH THE DATE OF 5/27/2022.

For the purposes of comparison of bids when an escalation provision is requested, Jefferson Parish will apply the maximum escalation percentage quoted by the bidder to the period to which it is applied in the bid. The initial price and the escalation will be used to calculate the total bid price. It will be assumed, for comparison of prices only, that an equal amount of material or labor is purchased each month throughout the entire contract.

DELIVERY: FOB JEFFERSON PARISH

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

48-72 hr Delivery (faster if stocked items)

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

THIS SECTION MUST BE COMPLETED BY BIDDER:

FIRM NAME: The McPherson Companies, Inc.

ADDRESS: 5051 Cardinal Street

CITY, STATE: Trussville, AL ZIP: 35173

TELEPHONE: (205) 308-3028 (888) 802-5700 FAX: (205) 661-4597

EMAIL ADDRESS: rharrison@mcphersonoil.com / lubesorders@mcphersonoil.com

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form by placing the addendum number as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: None

NUMBER: _____

NUMBER: _____

NUMBER: _____

TOTAL PRICE OF ALL BID ITEMS: \$ 28,170.15

AUTHORIZED SIGNATURE: 

TITLE: Govt. & Municipal Sales Contract Manager

Ryan Harrison

Printed Name

SIGNING INDICATES YOU HAVE READ AND COMPLY WITH THE INSTRUCTIONS AND CONDITIONS.

NOTE: All bids should be returned with the BID NUMBER and BID OPENING DATE indicated on the outside of the envelope submitted to the Purchasing Department.

DATE: 5/12/2021

INVITATION TO BID FROM JEFFERSON PARISH - continued

Page 7

BID NO.: 50-00134464

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	2.00	DRUM	<p>TWO YEAR CONTRACT FOR A SUPPLY OF PETROLEUM PRODUCTS FOR THE JEFFERSON PARIAH DEPARTMENT OF FLEET MANAGEMENT.</p> <p>0001 - CROWN 85W A40 GL5- 55 GALLON DRUM PETROLEUM PRODUCTS</p> <p>(MORE OR LESS)(AS PER SPECS BELOW) GRAVITY,API-25.5 FLASH,COC.F-375 PROTECK 85W140 400LB POUR-PT., F-0 VISCOSITY CST AT 40 C-310 CST AT 100C-24.7 SSU AT 100 F-1668 STRAIGHT MINERAL GEAR LUBRICANT MEETING API GL5 SPECIFICATIONS</p>	\$632.00 / Dr	\$1,264.00
2	1.00	DRUM	<p>0002 - CROWN ATF DERON/MERON 55 GAL. DRUM, PETROLEUM PRODUCTS</p> <p>SYNTHETIC (MORE OR LESS)(AS PER SPECS BELOW) FLASH,F-360 POUR F,(30) VISCOSITY CST AT 40 C-39.7 SCT AT 100 C-6.5 SSU AT 100 F-204 PROTECK SYN BLD MV ATF 55GA SSU AT 210 F-47.1 VISCOSITY INDEX-102 USED IN ALLISON POWERSHIFT AND MODEL CL(8)T700 AUTOMATIC TRANSMISSIONS AND OTHER EQUIPMENT REQUIRING EITHER TYPE C-1, TYPE C-2, OR TYPE C-3 HYDRAULIC TRANSMISSION FLUID</p>	\$454.85 / Dr	\$454.85
3	2.00	DRUM	<p>0003 - CROWN HYDRAULIC A.W.46 55 GALLON DRUM</p> <p>PETROLEUM PRODUCTS CROWN HYDRAULIC A.W.46. (MORE OR LESS)(AS SPECS BELOW) FLASH, F-441 POUR, F-0 VISCOSITY CST AT 40 C-43.3 SSU AT 100F-155 VISCOSITY INDEX-95 PROTECK HYD AW 46 55GA ISO VG-46 FOAM ASTM D-892 SEW. I,II,III OXIDATION STABILITY ASTM D-942 HRS-1000+ HYDROLYTIC STABILITY ASTM D-655 A & B VANE PUMP TEST ASTM D-2882 35V Q 25 VANE PUMP TEST.</p>	\$388.30 / Dr	\$776.60
4	1.00	DRUM	<p>0004 - CROWN HYDRUALIC A.W.32 LLDR, 55 GALLON DRUM</p> <p>PETROLEUM PRODUCTS</p> <p>PROTECK HYD AW 32 55GA</p>	\$388.30 / Dr	\$388.30

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00134464

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
5	6.00	DRUM	HYDRAULIC OIL (MORE OR LESS)(AS PER SPECS BELOW) FLASH, F-432 POUR, F-0 VISCOSITY CST AT 40 C-30.1 SSU AT 100F-155 VISCOSITY INDEX-95 ISO VG-32 FOAM ASTM D-892 SEZ I,II,III OXIDATION STABILITY ASTM D943-1000+ HYDROLYTIC STABILITY ASTM D-665A & B POINT PETROLEUM ASTM D-665A & B VANE PUMP TEST ASTM D-2882 35V Q VAN PUMP TEST.		
			0005 - CROWN UTF 55 GALLON DRUM PETROLEUM PRODUCTS FLD. LLDR (MORE OR LESS)(AS PER SPECS BELOW) FLASH, COC F-392 POUR, PT., F(-25) VISCOSITY CST AT 40 C-57.8 CROWN UTF CST AT 100C-9.1 SSU AT 100F-272 SSU AT 210F-55.7 VISCOCITY INDEX-135 PREMIUM UNIVERSAL LUBRICANT FOR ALL TRACTORS THAT REQUIRE A SINGLE OIL FOR LUBRICATION OF TRANSMISSION, DIFFERENTIAL AND DRIVE GEARS. IT CAN BE USED AS POWER BRAKE, POWER TAKE-OFF AND POWER STEERING FLUID WHERE MINERAL OILS ARE RECOMMENDED. MEETS SPECS FOR AC POWER FLUID 821. ALLISON C1,C2,C3,C4 CATERPILLAR T02, FORD/NEW HOLLAND ESNM2C41B, ESNMC-248-B,ESBN2C53C, ESNM2C77A, ESNM2C868, ESNM2C124A,B,C,D CASE INTERNATIONS JIC 185,JIC 145, JIC 144, JIC 143, MS 1205, MS 1204, MS 1210 (TCH), MS 1206 (POWER GRATE PTE) JOHN DEERE J20A (JY GARD), J1145 (303 FLUID), J145, J21A.	\$419.65 / Dr	\$2,519.90
6	2.00	DRUM	0006 - CROWN ATF DEXRON/MERCON LLDR 55 GAL. DRUM, PETROLEUM PRODUCTS SYNTHETIC (MORE OR LESS) (AS PER BELOW SPECS) COLOR-RED GRAVITY, API-29.5 FLASH, POINT F-360 POUR, PTX, F(-40) VISCOSITY C-P, AT(-40) C-40,000 CST AT 40C-37 CST AT 100C-7.4 SSU AT 100F-190 SSU AT 210F-51 VISCOSITY INDEX-160		
			PROTECK FULL SYN MV LV ATF 55GA	\$652.30 / Dr	\$1,304.60

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00134464

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
7	10.00	DRUM	PHOSPHORUS % MASS-050 CALCIUM % MASS-013 MEETS TRANSMISSION FLUID REQUIREMENTS FOR ALL ALLISON AUTOMATIC TRANS. ALLISON C3 & C4 AND CATERPILLAR T02 GM DEXROM II, AMERICAN MOTORS, CHRYSLER AND MERCON, ESP-M2C 166H AS ESP-M2C133C.		
			0007 - CROWN HD 15 W40 MOTOR OIL 55 GAL. DRUM, PETROLEUM PRODUCTS FULL SYNTHETIC-DELIVERED IN TOTES (MORE OR LESS)(AS PER SPECS BELOW) GRAVITY, API-28.4 FLASH, COC, F-399 POUR, PT., F(-17) VISCOSITY CST AT 40C-120.5 CST AT 100C-15.4 VISCOSITY INDEX-136 ASH(SULFATE),% MAX-8 TBS (ASTM D-2896)-9 D-664-7.5 PROTECK ELITE K FULL SYN ZINC % MASS-13 15W40 55GA CALCIUM % MASS-02 MEETS API CC,CD,CD-11,CE,SG & API SAE OIL REQUIREMENTS FOR GASOLINE ENGINES. MEETS SHEAR STABILITY REQUIREMENTS OF CCMS (CED-L-14-T74)AS MEASURED IN ASTM D-3945 SHEAR STABILITY TESTS. ALSO MEETS VISCOSITY GRADE FOR CUMMINS, DDC SERIES 60, NAVISTAR, INTERNATIONAL, AND MACK TRUCK ENGINES.	\$848.10 / Dr	\$8,481.00
8	2.00	DRUM	0008 - CROWN 5W,30, LLDR 55 GAL. DRUM, PETROLEUM PRODUCTS SYNTHETIC (AS PER SPECS BELOW) GRAVITY, API-30.0 FLASH, COC, F-410 POUR, F(-22) VISCOSITY CST AT 40 C-70 CST AT 100C-10.2 VISCOSITY INDEX-146 ASH (SULFATE)-81 ZINC % MASS-09 PROTECK ELITE FULL SYN DEXOS MAGNESIUM % MASS-13 5W30 55GA COPPER PPM-100 API LEVEL-SC UNILUSE API DIESEL ENGINE CATEGORY CC.	\$553.30 / Dr	\$1,106.60
			0009 - CROWN K-1 KEROSENE, 55 GALLON CONTAINER KEROSENE 55GA	\$327.25 / Dr	\$654.50
10	1.00	EA	0010- CROWN 55 GALLON CONTAINER MINERAL SPIRITS PROTECK MINERAL SPIRITS 55GA	\$311.30 / Dr	\$311.30

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00134464

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
11	1.00	DRUM	0011 - CROWN ISO 46 HYDRAULIC OIL 55 GALLON DRUM PETROLEUM PORDUCTS PRODUCT CODE: 65209 VISCOSITY @ 40 DEGREE C, CST 46.00 @ 100 DEGREE C, CST 6.8 @ 100 DEGREE F, SUS 237 @ 210 DEGREE F, SS 449 VISCOSITY INDEX 102 GRAVITY DEGREE API @ 60 DEGREE 29.5 FLASH POINT, COC, DEGREE F 420 POUR POINT, DEGREE F-20 COPPER CORROSION 1A EMULSION TEST @ 130 DEGREE F 30 MINUTES MAX PASS RUST TEST PASS- TURBINE OIL STABILITY TEST, HOURS 3000 PLUS	\$388.30 / Dr	\$388.30
12	1.00	DRUM	0012 - CROWN ISO 68 55 GALLON DRUM PETROLEUM PRODUCTS PRODUCT CODE : 65211 VISCOSITY: PROTECK HYD AW 68 55GA @40 DEGREE C. CST 68.0 @100 DEGREE C. CST 8.3 @100 DEGREE F. SUS 353 @210 DEGREE F. SUS 554.2 VISCOSITY INDEX 97 GRAVITY DEGREE API @60 DEGREE F 28.5 FLASH POINT. COC. DEGREE F 440 POUR POINT. DEGREE F -20 COOPER CORROSION 1A EMULSION TEST @ 1130 DEGREE F 30 MINUTES PASS RUST TEST PASS TURBINE OIL STABILITY TEST, HOUR 3000 PLUS.	\$388.30 / Dr	\$388.30
13	1.00	DRUM	0013 - CROWN HI-TEMP 2 55 GALLON DRUM CONTAINER PRODUCT CODE 70311 PROTECK TACKY RED 400LB COLOR BLUE SOAP TYPE LITHIUM COMPLEX BASE OIL VISCOSITY @40 DEGREE C. CST 150 @100 DEGREE C. CST 14.5 NLGI CLASSIFICATION GC/LB DROPPING POINT DEGREE F 536 WATER WASHOUT WT % LOSS @ 175 DEGREE F 6.8 TIMEKEN OK LOAD. LBS 45 RUST TEST PASS WORKED PENETRATION. DMM @77 DEGREE F 60 STROKES 280	\$796.00 / Dr	\$796.00

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
14	7.00	GL	BOMB OXIDATION 100 HRS @210 DEGREE F. PSI DROP 5 MAX 0014 - ILC MULTIGRADE, 5W20 MOTOR OIL IS A HIGH QUALITY MOTOR OIL THAT PROVIDES ANTI-WEAR PROTECTION AND PROTECTION AGAINST SLUDGE AND DEPOSIT FORMATION. SYNTHETIC ILC MULTI-GRAD 5W20 MOTOR OIL IS THE HIGHEST API QUALITY OIL RECOMMENDATION FOR GASOLINE POWERED VEHICLES. TYPICAL TEST DATA: PROTECK ELITE SYN BLD SAE GRADE 5W20 5W20 55GA API GRAVITY @60 DEGREE 33.6 VISCOSITY: CST @40 DEG. C 47.0 CST @100 DEG. C 8.3	\$395.45 / Dr	\$2,768.15
15	1.00	GL	0015 - TORQUE DRIVE SYNTHETIC TRANSMISSION FLUID-55 GALLON DRUM. PHYSICAL DATA: KINEMATIC VISCOSITY @ 100 C, CST (ASTM D-445) TORQUE DRIVE: 7.4 BROOKFIELD VISCOSITY @ -40C (CP) TORQUE DRIVE: 8400 VISCOSITY INDEX (ASTM D 2270) TORQUE DRIVE: 170 MAG1 HD FULL SYN DENSITY @ 60 F (LB/GAL) ATF 55GA TORQUE DRIVE: 7.038 FLASH POINT C (F) (ASTM D 92) TORQUE DRIVE: 230 (446) POUR POINT C (F) (ASTM D 97) TORQUE DRIVE: -55 (-67) FOUR BALL WEAR TEST (ASTM D-4172B: 40KG 75C, 1200 RPM 1 HR) MM TORQUE DRIVE: 0.45 COPPER CORROSION (150 C, 3 HR) TORQUE DRIVE: 1B SPECTROGRAPHIC ANALYSIS: BORON (PPM) TORQUE DRIVE:133 CALCUIM (PPM) TORQUE DRIVE: 28 PHOSPOROUS (PPM) TOURQUE DRIVE: 230 RECOMMENDED FOR US IN APPLICATIONS SPECIFYING ALLSION TES-295, TES-389 OR C-4, DEXRON III, MERCON, VOITH 55.6336.X X(G-1363)ZF-TE-MML14C TORQUE DRIVE: SYNTHETIC	\$1,099.45 / Dr	\$1,099.45
16	1.00	DRUM	0016 - 75-140 SYNTHEIC GEAR OIL-55 GALLON DRUM PROTECK FULL SYN 75W140 55GA	\$1,221.55 / Dr	\$1,221.55

