

DATE: 5/24/2019

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00126749

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETN, LA. 70054-0009
504-364-2678

VENDOR:

BUYER: DABRAHAM

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

5-7 DAYS

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: _____

NUMBER: _____

NUMBER: _____

NUMBER: _____

Gas And Supply

Jimmy Gibbs

Phone 504-392-2400

Fax 504-392-1500

jimmy.gibbs@gasandsupply.com

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***

| | |
|------------------------------|--------------|
| FIRM NAME: | |
| I.W.S. GAS AND SUPPLY | |
| SIGNATURE: | TITLE: |
| (Must be signed here) | SALES |
| PRINT OR TYPE NAME: | |
| Jimmy Gibbs | |
| ADDRESS: | |
| 111 BURAS DR. | |
| CITY STATE: | ZIP: |
| BELLE CHASSE, LA. | 70037 |
| TELEPHONE: | FAX: |
| 504 392-2400 | 504 392-1500 |
| EMAIL ADDRESS: | |
| Jimmy.Gibbs@GasAndSupply.com | |

TOTAL PRICE OF ALL BID ITEMS: \$ 1365.76

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00126749

SEALED BID

| ITEM NUMBER | QUANTITY | U/M | DESCRIPTION OF ARTICLES | UNIT PRICE QUOTED | TOTALS |
|----------------|----------|-----|---|----------------------|---------------|
| | | | A one time purchase of pry bars, trowels, pliers, etc. for the Department of Public Works | | |
| 1 | 24.00 | EA | 0010 - ADAPTER, HOSE, 2 IN, TYPE A, ALUMINUM, QUICK DISCONNECT, CAM LOCK <i>DIXON 200-A-AL</i> SK# 00-0487000 | <i>7.80</i> | <i>187.20</i> |
| 2 | 24.00 | EA | 0020 - PRY BAR, 24 IN WITH HANDLE, 11/16 IN TIP WIDTH, 31-7/8 IN OVERALL LENGTH, DOMESTIC, PROTO #J2148, MSC #84965367 | <i>24.67</i> | <i>592.08</i> |
| 3 | 10.00 | EA | 0030 - PLIERS, SLIP-JOINT, INSULATED HANDLES, 8 IN LONG, FULLER PRO #400-0112 <i>CHANNELLOCK 430</i> SK# 00-0584220 | <i>10.30</i> | <i>103.00</i> |
| 4 | 3.00 | EA | 0040 - CAULK IRON 1/2X1X1 PT 7/8X5.75 STK MUELER #H10685 SK# 00-0586530 | <i>N/B</i> | <i>—</i> |
| 5 | 6.00 | EA | 0050 - TROWEL, BRICK, 9 IN LONG X 4-3/4 IN WIDE, TEMPERED SPRINGS STEEL BLADE, MALLEABLE IRON SHANK RIVETED TO HICKORY HANDLE, DOMESTIC, OSBORNE #180 SK# 00-0591000 | <i>N/B</i> | <i>—</i> |
| 6 | 6.00 | EA | 0060 - TROWEL, CEMENT, POINTING, 7" BY 2.75", HYDE #18110 SK# 00-0591020 | <i>N/B</i> | <i>—</i> |
| 7 | 6.00 | EA | 0070 - SOCKET, THRU-BOLT, 7/8 IN, REED #L14 SK# 00-0610030 | <i>40.29</i> | <i>241.74</i> |
| 8 | 6.00 | EA | 0080 - SOCKET, THRU-BOLT, 1-1/16 INCH, MADE IN U.S.A., REED #L17 SK# 00-0610060 SHIP TO: BRIAN BOUDREAUX 1500 RIVER PARK BLVD BRIDGE CITY, LA 70094 504-349-5156 WAREHOUSE SUPERVISOR Gas And Supply Jimmy Gibbs Phone 504-392-2400 Fax 504-392-1500 jimmy.gibbs@gasandsupply.com | <i>40.29</i> | <i>241.74</i> |

Gas And Supply

Type A Adapters

Jimmy Gibbs
Phone 504-392-2400
Fax 504-392-1500

jimmy.gibbs@gasandsupply.com

Type A Adapters adapter x female NPT

Feature:

Pressure rating is based on the seal of the mating part. See ratings on page 124.

| Size | 356T6 Aluminum Part # | Aluminum Hard Coat Part # | Brass Part # |
|-------------|--------------------------|------------------------------|-----------------|
| 1/2" | 50-A-AL ² | --- | 50-A-BR |
| 3/4" x 1/2" | 7550-A-AL ² | --- | 7550-A-BR |
| 3/4" | 75-A-AL ² | --- | 75-A-BR |
| 1" | 100-A-AL ² | --- | 100-A-BR |
| 1 1/4" | 125-A-AL | --- | 125-A-BR |
| 1 1/2" | 150-A-AL | 150-A-ALH | 150-A-BR |
| 2" | 200-A-AL | 200-A-ALH | 200-A-BR |
| 2 1/2" | 250-A-AL | --- | 250-A-BR |
| 3" | 300-A-AL | 300-A-ALH | 300-A-BR |
| 4" | 400-A-AL | 400-A-ALH | 400-A-BR |
| 5" | 500-A-AL | --- | 500-A-BR |
| 6" | 600-A-AL | 600-A-ALH | 600-A-BR |
| 8" DIX | 800-A-AL ¹ | --- | --- |
| 8" BL | 801-A-AL ¹ | --- | --- |

Dixon® and Boss-Lock™ cam & groove couplings do not interchange in the 8" size.
made from 6061-T6 aluminum

C

Cam & Groove

C



356T6 aluminum



aluminum hardcoat



brass



unplated malleable iron



plated malleable iron



316 stainless steel

| Size | Unplated Malleable Iron Part # | Plated Malleable Iron Part # | 316 Stainless Steel Part # |
|-------------|-----------------------------------|---------------------------------|-------------------------------|
| 1/2" | --- | --- | 50-A-SS |
| 3/4" x 1/2" | --- | --- | 7550-A-SS |
| 3/4" | --- | 75-A-PM | 75-A-SS |
| 1" | --- | 100-A-PM | 100-A-SS |
| 1 1/4" | --- | --- | 125-A-SS |
| 1 1/2" | 150-A-MI | 150-A-PM | 150-A-SS |
| 2" | 200-A-MI | 200-A-PM | 200-A-SS |
| 2 1/2" | --- | --- | 250-A-SS |
| 3" | 300-A-MI | 300-A-PM | 300-A-SS |
| 4" | 400-A-MI | 400-A-PM | 400-A-SS |
| 5" | 500-A-MI | --- | 500-A-SS |
| 6" | --- | 600-A-PM ¹ | 600-A-SS |

ductile iron

adapter x female NPT with abrasion resistant inserts

Feature:

used in extreme abrasion transfer applications such as sand transfer in hydraulic fracturing

| Description | UHMW Polyethylene Insert Part # |
|--|------------------------------------|
| (400-A-AL) aluminum adapter x female NPT with UHMW insert | 400-A-ALINSERT |
| (400-A-BR) brass adapter x female NPT with UHMW insert | 400-A-BRINSERT |
| (400-A-MI) malleable iron adapter x female NPT with UHMW insert | 400-A-MIINSERT |
| (400-A-SS) stainless steel adapter x female NPT with UHMW insert | 400-A-SSINSERT |

Replacement inserts are available on page 172.

NEW



400-A-ALINSERT

TONGUE AND GROOVE

CHANNELLOCK® uses high carbon C1080 steel for superior performance on the job, and an electronic coating for ultimate rust prevention.

CHANNELLOCK® utilise un acier C1080 à haute teneur en carbone de performances supérieures, à poli électrolytique pour une protection parfaite contre la rouille.

CHANNELLOCK® utiliza acero al alto carbono C1080 para lograr un rendimiento superior en el trabajo y una capa depositada electrónicamente para la máxima prevención de la oxidación.

PermaLock® fastener eliminates nut and bolt failure.

Le rivet PermaLock® élimine le risque d'une rupture de la charnière.

Sistema de fijación PermaLock® elimina las fallas de los pernos y las tuercas.



Right angle, laser heat-treated teeth grip better and last longer.

Des dents biseautées en angle droit et thermotraitées au laser assurent une meilleure prise et une bien plus grande durabilité.

Dientes en ángulo recto y termotratados por láser agarran mejor y duran más.

Patented reinforcing edge minimizes stress breakage.

Le rebord de renforcement breveté minimise les cassures.

Borde de refuerzo patentado que minimiza la ruptura por tensión.

Undercut tongue and groove won't slip.

Les encoches profondes de l'axe d'articulation évitent tout glissement accidentel.

Perfil de ranura y lengüeta permite un agarre perfecto sin riesgo de que se zafe.

CHANNELLOCK BLUE® comfort grips

Poignées de confort CHANNELLOCK BLUE®

Empuñaduras cómodas CHANNELLOCK BLUE®

STRAIGHT JAW

BigAzz

Features

- Big as the job. Big as you need.
- Toujours à la hauteur de la tâche.
- Grande como el trabajo, tan grande como la necesite.


Gas And Supply

Jimmy Gibbs

Phone 504-392-2400

Fax 504-392-1500

jimmy.gibbs@gasandsupply.com




| PLIER | A OVERALL LENGTH | | B JAW LENGTH | | C JOINT THICKNESS | | H HANDLE SPAN | | WEIGHT | | NUMBER OF ADJUSTMENTS | JAW CAPACITY | |
|-------|------------------|--------|--------------|-------|-------------------|-------|---------------|-------|--------|---------|-----------------------|--------------|--------|
| | in | mm | in | mm | in | mm | in | mm | pounds | grams | | in | mm |
| 480 | 20.25 | 514.35 | 3.00 | 76.20 | 0.59 | 14.99 | 3.31 | 84.07 | 3.81 | 1728.19 | 12 | 5.50 | 139.70 |



| PLIER | A OVERALL LENGTH | | B JAW LENGTH | | C JOINT THICKNESS | | H HANDLE SPAN | | WEIGHT | | NUMBER OF ADJUSTMENTS | JAW CAPACITY | |
|-------|------------------|--------|--------------|-------|-------------------|-------|---------------|-------|--------|---------|-----------------------|--------------|--------|
| | in | mm | in | mm | in | mm | in | mm | pounds | grams | | in | mm |
| 460 | 16.50 | 419.10 | 2.56 | 65.02 | 0.59 | 14.99 | 1.93 | 49.02 | 3.14 | 1424.28 | 8 | 4.25 | 107.95 |
| 440* | 12.00 | 304.80 | 1.50 | 38.10 | 0.50 | 12.70 | 1.81 | 45.97 | 1.64 | 743.89 | 7 | 2.25 | 57.15 |
| 430* | 10.00 | 254.00 | 1.38 | 35.05 | 0.44 | 11.18 | 2.13 | 54.10 | 1.18 | 535.24 | 7 | 2.00 | 50.80 |
| 420* | 9.50 | 241.30 | 1.12 | 28.45 | 0.47 | 11.94 | 1.57 | 39.88 | 0.87 | 394.63 | 5 | 1.50 | 38.10 |
| 426 | 6.50 | 165.10 | 0.81 | 20.57 | 0.47 | 11.94 | 1.69 | 42.93 | 0.37 | 167.83 | 5 | 0.87 | 22.10 |

Features

- Patented SAFE-T-STOP® feature prevents finger pinch.
- Lower jaw combines with expanded reinforcing rib to prevent handles from contacting each other.
- Dispositif de sûreté breveté SAFE-T-STOP®, contre les pincements de doigt.
- La position de la mâchoire inférieure combinée à une crête de renforcement élargie empêche les poignées d'entrer en contact l'une avec l'autre.
- La característica patentada SAFE-T-STOP® previene pincharse los dedos.
- La mordaza inferior se combina con un borde saliente de refuerzo extendido para impedir que las empuñaduras hagan contacto entre sí.



| PLIER | A OVERALL LENGTH | | B JAW LENGTH | | C JOINT THICKNESS | | H HANDLE SPAN | | WEIGHT | | NUMBER OF ADJUSTMENTS | JAW CAPACITY | |
|-------|------------------|--------|--------------|-------|-------------------|-------|---------------|-------|--------|--------|-----------------------|--------------|-------|
| | in | mm | in | mm | in | mm | in | mm | pounds | grams | | in | mm |
| 421 | 9.50 | 241.30 | 1.12 | 28.45 | 0.47 | 11.94 | 1.57 | 39.88 | 0.82 | 371.95 | 5 | 1.50 | 38.10 |
| 428 | 8.00 | 203.20 | 1.12 | 28.45 | 0.40 | 10.16 | 1.57 | 39.88 | 0.79 | 358.34 | 4 | 1.50 | 38.10 |



| PLIER | A OVERALL LENGTH | | B JAW LENGTH | | C JOINT THICKNESS | | H HANDLE SPAN | | WEIGHT | | NUMBER OF ADJUSTMENTS | JAW CAPACITY | |
|-------|------------------|--------|--------------|------|-------------------|------|---------------|-------|--------|-------|-----------------------|--------------|-------|
| | in | mm | in | mm | in | mm | in | mm | pounds | grams | | in | mm |
| 424 | 4.50 | 114.30 | 0.33 | 8.38 | 0.13 | 3.30 | 1.26 | 32.00 | 0.12 | 54.43 | 3 | 0.50 | 12.70 |

e-mail: pliers@channellock.com