

24

DATE: 7/22/2019

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 4

BID NO.: 50-00127437

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETNA, LA. 70054-0009
504-364-2678

VENDOR:

Basic Supply LLC

BUYER: MBUTTERY

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH

INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES

2-3 Weeks

INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK

INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.

Acknowledge Receipt of Addenda: NUMBER: _____

NUMBER: _____

NUMBER: _____

NUMBER: _____

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) _____

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***	
FIRM NAME: John Atkinson Basic Supply LLC	
SIGNATURE: (Must be signed here)	TITLE: Manager
PRINT OR TYPE NAME: John Atkinson	
ADDRESS: PO Box 63066	
CITY, STATE: Lafayette LA	ZIP: 70596
TELEPHONE: 337-769-0122	FAX: 337-247-7699
EMAIL ADDRESS: charlotte@basicsupply.com	

TOTAL PRICE OF ALL BID ITEMS: \$ 697.00

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00127437

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	12.00	TUBE	ONE TIME PURCHASE OF PAINT FOR THE SEWERAGE DEPARTMENT 0001 - Caulk - SherMax Ultra Urethanized Elastomeric Sealant, 11 oz., White 12 tubes per case Product/Rex no. WL001360A	4.75	57.00
2	20.00	GL	0002 - LXN C & M Primer WH Product/Rex No. LX02W0050 NOTE: To be supplied in 5 gallon pails	32.00/gal	640.00
3	30.00	GL	0003 - Paint, CNFLX XL SMTH DB Product/Rex no. CF11W0053 Color: SW6187 Rosemary NOTE: To be supplied in 5 gallon pails		
4	10.00	GL	0004 - Paint, CNFLX XL SMTH EW Product/Rex no. CF11W0051 Color: SW6178 Clary Sage NOTE: To be supplied in 5 gallon pails		

Big Stretch 10016 Acrylic Caulk, White, 10.5 oz Cartridge

Seals doors, windows, siding, trim and moulding. Won't crack, just stretches. Spans gaps 2" wide. Powerful adhesion. Environmentally safe and non-toxic. Stop-flow feature, prevents waste and mess. Dry to touch in 30 minutes. Cured in 4 to 5 days. Allow 24 hour cure time before exposure to rain (2 to 3 days in cold/humid weather). Paintable in 1 hour with latex paints, in 1 week with oil paints or stains. Colors darken as they dry, most noticeable on darker colors. Water clean up.

Descripción español:

MASILLA ACRILICA COLOR BLANCO DE 297,67 G

INTERIOR/EXTERIOR

Brand: "BIG STRETCH"

10.5 Ounce Cartridge

Color : White

Information and

Product Details

Type:Elastomeric, High Performance, Non-Toxic

Size:10.5 oz

Packing Type:Cartridge

V O C Content:59.8 g/l

Form:Fluid Paste

Coverage:26 ft Linear at 1/4 in Bead

Drying Time:4 hr Exterior, 24 - 48 hr Interior

Functional Cure:4 - 5 days

Odor/ Scent:Slight Ammonia

Composition:Ethylene Glycol

Flammability Rating:0

Specific Gravity:1.14 Pigmented, 1.04 Clear

Application Temperature:40 - 120 deg F

Applicable Materials:Aluminum, Brass, Steel, PVC, Nylon, Vinyl, Tile, Wood, Fiber Cement and Glass

Shore Hardness:32 Shore A

Base Type:Water

Temperature Range:-30 TO 250 deg F

Resists:UV

Standards:ASTM C834, ASTM C920, Type S, NS, Class 25 Specified, CWA 40 CFR 122.21 and 40 CFR 122.42 Certified, TT-S-00230 C Federal Specification, Meets FHA Requirements

Usage:For Doors, Windows, Siding, Vents. Soffits, Baseboards Eaves, Crown Molding and Sound Proofing Interior Walls

Features

Keeps the weather where it belongs outside or moves, when your home moves to create a permanently waterproof and weatherproof seal

Just say no to brittle, cracked caulking and stays soft, elastic over time for a long-lasting seal

Compatible with a wide variety of building materials including difficult ones like vinyl windows, siding and requires no searching for a product specific to every different surface

Smooth formula is easy to apply and provides professional looking results every time

Paint adheres like a pro, so go ahead and paint your wall bright blue

Easy to smooth and cleanup with water

Environmentally safe



UGL DRYLOK EXTREME 28615 Masonry Waterproofer, Liquid, White, 5 gal Pail
or the most demanding conditions. For above or below grade masonry walls, basement walls, retaining walls, foundations, landscape walls, cinder blocks, concrete blocks, bare concrete swimming pools, stucco and brick. Formulated to resist mildew growth on the paint film. Stops 15 psi. Passes ASTM D-7088 Resistance to Hydrostatic pressure and ASTM D-6904 resistance to wind driven rain. Covers 75 to 125 sq. ft per gallon depending on surface porosity.

INTERIOR/EXTERIOR - LATEX-BASED

Brand: "DRYLOK - EXTREME"

5 Gallon

Color : White

Finish:Smooth

Size:5 gal

Applicable Materials:Grade Masonry Walls, Basement Walls, Retaining Walls, Foundations, Landscape Walls, Cinder Blocks, Concrete Blocks, Bare Concrete Swimming Pools, Stucco and Brick

Application Method:Nylon Bristle Brush, Roller or Sprayer

Base Type:Latex

Coverage:75 - 100 sq-ft/gal

Form:Liquid

Functional Cure:3 hr

Odor/ Scent:Ammonia

p H Range:9 - 9.9

Resists:Mildew

Special Features:9.8 - 10 lb/gal Density, Titanium Dioxide Pigment

Standards:ASTM Specified, NIOSH, OSHA Approved

Type:Extreme

Usage:For Interior/Exterior Application

Viscosity:100 - 120 KU

V O C Content:100 g/l

Features

Guaranteed to stop water

Helps protect against radon gas penetration by reducing vapor transfer

Low-odor formula complies with all current VOC requirements

Breathable film will not trap moisture in the masonry

Easy cleanup with warm, soapy water

Tintable, bright white, smooth finish formula features flexible encapsulated polymers for the ultimate in waterproof protection

Incorporation of a green biocide helps the dry paint film resist mildew growth

No pre-mixing or pre-wetting

After 24 hrs, DRYLOK® will accept a decorative topcoat using a good quality latex paint

