

TOPSTAR™

LED HID

POST TOP RETROFIT LIGHT



TOPSTAR HID LED lamp replaces a 150-400W HID and is suitable for use in totally enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for outdoor post top applications. The special designed heat sink system allows air to flow freely through the lamp. It uses an increased cooling surface area to reduce the operating temperature of the LED and power supply, thus resulting in longer lamp life and lumen maintenance.

- 150W-400W HID replacement
- Direct line voltage 120-277V - Not compatible with ballasts
- Specially designed for use in post top applications
- Fully omnidirectional 360 beam angle
- Available in 4000K & 5000K CCT
- Suitable for use in totally enclosed fixtures
- 5 years warranty
- DLC 4.1 Listed

Ordering Code	Watt (W)	Replacement Watt (W)	Initial Lumen *	Base **	CRI	Color Temp.	Rated Average life	MOL (in.)	Beam Angle
CNE26-8YY-36P-M1-BP	36	150-175	4320	E26	82	4000K/5000K	50,000	8.54	360
● CNE39-8YY-36P-M1-BP	36	150-175	4320	E39	82	4000K/5000K	50,000	8.86	360
● CNEX39-8YY-54P-M1-BP	54	250	6480	EX39	82	4000K/5000K	50,000	10.94	360
● CNEX39-8YY-75P-M1-BP	75	320-400	8700	EX39	82	4000K/5000K	50,000	12.05	360
● CNE39-8YY-100P-M1-BP	100	400	12000	E39	82	4000K/5000K	50,000	9.65	360

- DLC 4.1 Listed
- * Initial lumen is @ 5000K
- ** EX39 is compatible with E39
- *** At present, only 5000K is available in stock in US

Note: This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause an undesired operation.

Suitable for use in enclosed luminaires. This device is not intended for use with emergency exits.